# **Insulated Self-Contained Kettle**

**Electric, 2/3 Jacketed** Insulated for Safety™ **Deep Drawn Construction Made in USA** 

# Model

### Standard Features



Model LTCRE-60 shown with custom dispensing faucet

- ♦ Kettle System ◊304 stainless liner ◊304 stainless draw-off tube and welds ♦304 stainless 2" compression draw-off
- ♦ 304L stainless kettle jacket
- ♦ 304 stainless leg socket supports, welded to jacket
- ♦ 304 stainless legs provided with reinforced bracing ◊ 4 legs for 40 - 60 gallon, 1 5/8" diameter ◊ 4 legs for 80 - 150 gallon, 2" diameter
- ♦ 30 psi operating pressure up to 125 gallon; 25 psi for 150 gallon
- ♦ 304 stainless, seam welded control console
- ♦ 304 stainless, one piece, domed cover
- Recirculating pump with automatic timer and manual control
- ♦ Graduated, break-resistant coffee level sight glass
- Gridded riser basket with canvas coffee bag and stainless spreader ring
- ♦ Bag removal hoist
- ♦ Water fill connection
- ♦ Adjustable flanged feet

Legion equipment is built to comply with applicable standards fo manufacturers. Approval agencies may include ASME, NSF, UL, ETL, AGA, CSA, CGA and others. Legion reserves the right of design improvement or modification as warranted.

#### **Optional Features and Accessories Models and Capacities** See price list for supplemental information regarding options **PUMP MOTOR OPTIONS** LTCRE-40 Prison/Security: 40 gal. (151 l.) φ Phase \_Draw-off protection package Voltage H.P. **Amps** Fasteners (screws & nuts) LTCRE-60 60 gal. (227 I.)5.2 \_Nut driver tool 115 Screw driver tool LTCRE-80 80 gal. (303 I.)\_Lockable lid 220 3.2 \_Lockable control cover

1/3 1/3 230 2.6 1/3 **Other Options:** LTCRE-100 100 gal. (379 l.)\_Pressure switch Elevated draw-off faucet 1/2" 208 1.4 1/3 \_Water supply plumbing assembly \_Stainless mesh cloth coffee filter 1.2 1/3 230 \_Remote coffee fill 460 .6 1/3 **Accessories:** \_Draw-off drain with 6 foot hose \_Cloth coffee bag insert with stainless spreader ring


Revision 113

\_Care kit

## Electric, 2/3 Jacketed Insulated for Safety™ Deep Drawn Construction Made in USA

# Insulated Self-Contained Kettle

## DRAWING REPRESENTS MODEL LTCRE-100 WITH OPTIONAL ELEVATED SWING FAUCET



MODEL LTCRE DIMENSIONS													
GAL.	Α	В	С	D	E	F	Н	J	S	Т	U	W	AA & BB
40	23.0	35.5	53.5	28.6	13.6	54.6	14.6	70.5	20.0	49.1	28.9	18.4	11.9
60	25.5	40.5	58.5	31.3	15.0	58.0	14.6	75.5	21.4	52.9	30.1	19.6	12.9
80	29.5	41.5	60.5	35.3	17.0	59.0	15.9	76.5	23.4	58.9	32.1	21.6	14.3
100	32.5	42.5	61.8	38.3	18.5	62.0	16.0	83.3	24.5	63.4	33.6	23.1	15.4

MODEL LTCRE ELECTRICAL SPECIFICATIONS (AMPERES PER LEG)													
GAL	KW	208 Volt		240 Volt		380 Volt		415 Volt		440 Volt		480 Volt	
		1ø	3ø										
40	12	57.7	33.3	50.0	28.9	31.6	18.2	28.9	16.7	27.3	15.7	25.0	14.4
60	24	115.4	66.6	100.0	57.7	63.2	36.5	57.8	33.4	54.5	31.5	50.0	28.9
80	36	173.1	99.9	150.0	86.6	94.7	54.7	86.7	50.1	81.8	47.2	75.0	43.3
100	36	173.1	99.9	150.0	86.6	94.7	54.7	86.7	50.1	81.8	47.2	75.0	43.3

Revision 113

