


SPIKA MS700-22

115 V / 60 Hz

MODULAR 22 INCH ICE CUBE MACHINE

3 YEARS
WARRANTY
PARTS & LABOR



FEATURES

- ▶ PRODUCES FULL DICE OR HALF DICE ICE CUBES
- ▶ HIGH EFFICIENCY EVAPORATOR
- ▶ SMART WATER DISTRIBUTOR THAT IMPROVES DROP-OFF EFFICIENCY
- ▶ EASY ACCESS FOR SERVICE BY REMOVING THE PANELS WITH A SINGLE SCREWDRIVER
- ▶ SMART ELECTRONIC BOARD CONTROLS EVERY PARAMETER IN THE MACHINE AND SHOWS THE DIAGNOSIS OF POSSIBLE INCIDENCES
- ▶ HIGH RESISTANCE EXTERNAL FRAME IN AISI 304 STAINLESS STEEL



	 lbs 24 H	 70°F/20°C lbs (Kg)	 50°F/10°C lbs (Kg)	 90°F/32°C lbs (Kg)	 70°F/21°C lbs (Kg)	 in (mm)	 in (mm)	 SPIKA HALF DICE 0,9" (W) x 0,4" (D) x 1" (H) 23 mm (W) x 11 mm (D) x 26 mm (H) Average dimensions
SPIKA MS700-22 H		705 (320)	606 (275)	Width 22" (559)	Width 25.6" (650)	Depth 24.45" (621)	Depth 27.96" (710)	 SPIKA FULL DICE 1" (W) x 0,9" (D) x 1" (H) 26 mm (W) x 23 mm (D) x 26 mm (H) Average dimensions
SPIKA MS700-22 F		-	-	Height 25.95" (659)	Height 32.29" (820)			

ACCESSORIES

INCLUDED



SCOOP


NOT INCLUDED



DOUBLE 10" FILTER
ANTI-LIMESCALE + ANTI-CHLORINE
CS102



10" REPLACEMENT CARTRIDGE
ANTI-LIMESCALE + ANTI-CHLORINE
CS10



ADAPTER PLATES



SCALE KLEEN

RECOMMENDED BINS

RECOMMENDED



S400
+
SPIKA
MS700-22



SCS350
+
SPIKA
MS700-22

OTHER POSSIBLE OPTIONS



S500
+
SPIKA
MS700-22



S750
+
SPIKA
MS700-22



S900
+
SPIKA
MS700-22



S1050
+
SPIKA
MS700-22



SCS700
+
SPIKA
MS700-22



SCD900
+
1/2 SPIKA
MS700-22



SCD1350
+
1/2 SPIKA
MS700-22




SCD1800
+
1/2 SPIKA
MS700-22


TECHNICAL SCHEME

SPIKA MS700-22


LEFT SIDE VIEW




FRONTAL VIEW



REAR VIEW



BOTTOM VIEW



* All dimensions in inches (and mm)

OPERATING CONDITIONS

PRODUCTION (LBS) 60Hz

±10% V

41°F/109°F

41°F/95°F

14.5 psi (1 bar) / 87 psi (6 bar)

240/480 Ice cubes/cycle

V	Hz	ph
115	60	1N



HALF DICE

SPIKA MS700-22 AIR COOLED

	50° 10°	60° 15°	70° 21°	86° 30°
50° 10°	723	705	683	679
68° 21°	705	683	661	657
90° 32°	650	628	606	602
109° 43°	529	507	485	480



FULL DICE

SPIKA MS700-22 AIR COOLED

	50° 10°	60° 15°	70° 21°	86° 30°
50° 10°	707	703	647	567
68° 21°	676	678	625	546
90° 32°	613	602	527	483
109° 43°	472	462	416	378

MODELS

	ASHRAE CONDITIONS (BTU/h) (W)	(W) 109°F	(AWG/mm ²) (n.)	FUSE	100lbs 90°F / 70°F (Kwh/100 lbs)	gal 100lbs (l/h)	HEAT REJECTED (BTU/h) (W)	(lbs)	(lbs)
SPIKA MS700-22 A	13,853 4,060	1,350	14/2.5 3	25	10.850	15.28 17	9,076 2,660	155.21	181
SPIKA MS700-22 W	13,853 4,060	1,070	14/2.5 3	25	8.4	71.31 78.6	9,076 2,660	155.21	181



ITV Ice Makers, Inc.
9550 Satellite Blvd, Suite 100
Orlando, FL 32837
Phone: 1 407 826 1860 | Fax: 1 407 826 1861
Toll Free: 1 888 488 1423
sales@itvice.com | www.itvice.com



SERVICE
service@itvice.com
Skype: service@itvice.com
PHONE: +1 888 488 1423
FROM 8AM TO 5PM EST



2 ADDITIONAL YEARS
ON COMPRESSOR &
EVAPORATOR
Read our warranty policy
to know more about
limitations and exclusions



VERTICAL SYSTEM