



TRUE MANUFACTURING CO., INC.
U.S.A. FOODSERVICE DIVISION

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400
Fax (636)272-2408 • Toll Free (800)325-6152 • Intl Fax# (001)636-272-7546
Parts Dept. (800)424-TRUE • Parts Dept. Fax# (636)272-9471 • www.truemfg.com

AIA #

SIS #

Project Name: _____

Location: _____

Item #: _____ Qty: _____

Model #: _____

Model:

TGN-1F-1S**T-Series:***Reach-In Solid Swing Door Freezer with Hydrocarbon Refrigerant***TGN-1F-1S**

- True's solid door reach-in's are designed with enduring quality that protects your long term investment.
- Designed using the highest quality materials and components to provide the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace.
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & 0.02 global warming potential (GWP).
- High capacity, factory balanced refrigeration system that maintains cabinet temperatures of -10°F (-23.3°C).

Stainless steel front. Anodized quality aluminum ends. Corrosion resistant GalFan coated steel back and top.

Interior - Clear coated aluminium, stainless steel base.

Bottom mounted units feature:

- "No stoop" lower shelf.
- Compressor performs in coolest, most grease free area of kitchen.
- Easily accessible condenser coil for cleaning.
- True's self-cleaning reverse condensing unit technology eliminates the need to clean the condenser coil by reversing the fan direction upon each startup of the unit, which causes air to blow through the condensing coil and effectively removes any dirt, dust, and debris.

ROUGH-IN DATA

Specifications subject to change without notice.
Chart dimensions rounded up to the nearest $\frac{1}{8}$ " (millimeters rounded up to next whole number).

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
			W	D	H*						
TGN-1F-1S	1	3	28 $\frac{3}{4}$ 729	33 $\frac{3}{4}$ 858	78 $\frac{1}{2}$ 1994	1/2 1/6	120/60/1 220-240V/50-60Hz	1.6 0.65	5-15P ▲	10 3.05	320 145

* Height does not include 5" (127 mm) for castors or 6" (153 mm) for optional legs.

* Depth does not include 1 $\frac{3}{4}$ " (44mm) for handle.

▲ Plug type varies by country.

**APPROVALS:****AVAILABLE AT:**

Model:

TGN-1F-1S**T-Series:***Reach-In Solid Swing Door Freezer with Hydrocarbon Refrigerant***STANDARD FEATURES****DESIGN**

- True's commitment to using the highest quality materials and oversized refrigeration systems provides the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace.

REFRIGERATION SYSTEM

- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydro carbon refrigerant that has zero (0) ozone depletion potential (ODP), & 0.02 global warming potential (GWP).
- Extra large evaporator coil balanced with higher horsepower compressor and large condenser; maintains -10°F (-23.3°C).
- State of the art, electronically commutated evaporator and condenser fan motors. ECM motors operate at higher peak efficiencies and move a more consistent volume of air which produces less heat, reduces energy consumption and provides greater motor reliability.
- Bottom mounted condensing unit positioned for easy cleaning. Compressor runs in coolest and most grease free area of the kitchen. Allows for storage area on top of unit.
- Automatic defrost system time-initiated, temperature-terminated. Saves energy consumption and provides shortest possible defrost cycle.
- True's self-cleaning reverse condensing unit technology eliminate the need to clean the condenser coil by reversing the fan direction upon each startup of the unit, which causes air to blow through the condensing coil and effectively removes any dirt, dust, and debris.

CABINET CONSTRUCTION

- Exterior -Stainless steel front. Anodized quality aluminum ends. Corrosion resistant GalFan coated steel back and top.
- Interior - Clear coated aluminum, stainless steel base.
- Insulation - entire cabinet structure and solid door are foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- Welded, heavy duty steel frame rail, black powder coated for corrosion protection.
- Frame rail fitted with 4" (102 mm) diameter stem castors - locks provided on front set.

DOOR

- Stainless steel exterior with clear aluminum liner to match cabinet interior. Door extend full width of cabinet shell.
- Barrel locks standard.
- Magnetic door gasket of one piece construction, removable without tools for ease of cleaningPositive seal self-closing door. Lifetime guaranteed door hinges and torsion type closure system.
- Lifetime guaranteed chrome plated handle. Door fitted with 12" (305 mm) long recessed handle that is foamed-in-place with a sheet metal interlock to ensure permanent attachment. Magnetic door gasket of one piece construction, removable without tools for ease of cleaning.
- Positive seal self-closing door. Lifetime guaranteed door hinges and torsion type closure system.
- Field reversible door hinging.

SHELVING

- Gastronorm slides with Three (3) gray wire shelves 20 7/8" L x 25 1/32" D (531 mm x 650 mm). Four (4) stainless steel polished shelf clips included per shelf.
- Shelf support pilasters made of same material as cabinet interior; shelves are adjustable on 1/2" (13 mm) increments.

LIGHTING

- LED Interior lighting.

MODEL FEATURES

- Exterior temperature display.
- Evaporator is epoxy coated to eliminate the potential of corrosion.




ELECTRICAL

- Unit completely pre-wired at factory and ready for final connection to a 120/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.

**OPTIONAL FEATURES/ACCESSORIES**

Upcharge and lead times may apply.

- 220-240V/50-60Hz
- 4" (102 mm) standard legs.
- 6" (153 mm) standard legs.
- 6" (153 mm) seismic/flanged legs.
- Additional shelves.
- Spec Kits available; universal tray slides and angle tray slides.

PLAN VIEW

METRIC DIMENSIONS ROUNDED UP TO THE NEAREST WHOLE MILLIMETER

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



Model	Elevation	Right	Plan	3D	Back
TGN-1F-1S-HC					

TRUE MANUFACTURING CO., INC.2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 • Fax (636)272-2408 • Toll Free (800)325-6152 • Intl. Fax# (001)636-272-7546 • www.truemfg.com