

Project		
ltem #		
Quantity		

# 48" GREEN FLAME RANGES WITH 26 1/2" OVEN

ARGF-8B-126-C ARGF-24G-4B-126

ARGF-36G-2B-126

#### STANDARD FEATURES

- · Stainless steel sides, front, and 6" deep front landing
- Adjustable steel legs (casters optional)
- Choice of: 6" high stainless-steel stub back, high riser, or high riser with shelf at no charge
- Two year limited warranty, parts, and labor
- · Base options are standard oven, convection, or storage base

## **OPEN BURNERS**

- 12" x 12" cast-iron top grates
- · 22,000 BTU/hr. burners with electronic ignition, no standing pilot
- Removable full-width drip pan under burner

# STANDARD 26 1/2" OVEN

- Steel oven burner rated at 35,000 BTU/hr.
- Oven dimensions: 26 1/2"W x 22 1/2"D x 13 1/2"H.
  Thermostat ranging from 250°F to 500°F (121°C to 260°C)
- · Oven Door: Spring assisted, counterweight door
- Two chrome plated oven racks (Additional racks)
- Two fixed rack positions
- · Porcelain enamel oven interior for easy cleaning
- · 100% safety gas shut off

## **CONVECTION OVEN** (In place of standard oven)

- Steel oven burner rated at 30,000 BTU/hr.
- · Convection oven fan improves heat transfer for a faster cook time
- Two chrome plated oven racks (Additional racks) optional)
- Chrome rack guides with five tray positions

# **GRIDDLES**

- 1" thick steel griddle plate3" wide grease collector

- One burner every 12", rated at 20,000 BTU/hr.
  Stainless steel pilot for each burner for automatic ignition
- Manual control valve for each burner (Thermostatic control optional)

# **AVAILABLE OPTIONS**

Swivel Casters (Set of four – two with front brakes)

**GAS TYPE:** 









## Model Shown ARGF-10-126L

Shown with optional casters

### **DESCRIPTION**

American Range, green flame range size 48" x 32-1/2" x 56" Stainless steel front, sides, backriser, shelf and 6" adjustable legs. Removable full width drip pan. Choose 22,000 BTU/hr. open burners with lift-off burner heads or 20,000 BTU/12" section griddle or a combo burner griddle. Heavy-duty cast iron grates, 12" x 12". Burner knobs are cool to the touch, high temperature material. One oven: 35,000 BTU/hr. standard oven, 30,000 BTU/hr. for convection with porcelain interior and inside door panel, oven interior measures 26-1/2"W x 22-1/2"D x 13-1/2"H. Oven thermostat adjusts from 250°F to 500°F. All ovens supplied with two racks. Oven door with a spring assisted, counterweight mechanism requiring no adjustment. Rear gas connection and pressure regulator. Requires power outlet, 115 amp three prong cord provided.












# 48" GREEN FLAME RANGES with 26 1/2" oven and storage base



Front Standard 26 1/2" Oven and Storage Base






**Side Convection Oven Base** 


Shipping Weight\*

TOP	
	Ž

MODEL	BTU/hr.	(KW)	BURNERS	GRIDDLE SIZE	LBS	(KG)
ARGF-8B-126	275,000	(81)	8	N/A	580	(264)
ARGF-8B-126-C	270,000	(79)	8	N/A	580	(264)



ARGF-24G-4B-126-C 190,000 (56) 4 24" (610 MM) 626 (284)	ARGF-24G-4B-126	195,000	(57)	4	24" (610 MM)	626	(284)
	ARGF-24G-4B-126-C	190,000	(56)	4	24" (610 MM)	626	(284)



ARGF-36G-2B-126	155,000	(46)	2	36" (914 MM)	640	(290)
ARGF-36G-2B-126-C	150,000	(44)	2	36" (914 MM)	640	(290)

"C" = Convection Oven, "SB" = Storage Base, "G" = Manual Griddle Top. Griddle on the left, storage base on the right - dimensions 11 1/4" x18" x 22 1/2"

Specify type of gas and altitude if over 2000 feet. Please specify gas type when ordering.

\*Shipping weight includes packaging and is approximate.

CONVECTION	ON OVEN ELI	ECTRICAL
VOLTAGE	PHASE	AMPS
120	1	4

NATURAL GAS	MANIFOLD PRESSU   PROPANE GAS	RE   MANIFOLD SIZE
5.0" W.C.	10.0" W.C.	3/4" (19MM)

<sup>15</sup> amps three prong cord provided





## COMBUSTIBLE WALL **CLEARANCES:**

For use only on noncombustible floors. Legs or casters are required, or 2" (51) overhang is required when curb mounted. Clearance from non-combustible walls is 0". When unit is placed next to combustible walls, clearances must exceed 12" (305) from sides, and 4" (102) from rear.

Commercial cooking equipment requires an adequate ventilation system. For additional information, refer to the National Fire Protection Association's standard.

NFPA96 "Vapor Removal from Cooking Equipment." (NOTE: For North America only)

American Range is a quality manufacturer of commercial cooking equipment. Because of continuing product improvements these specifications are subject to change without prior notice.