

HEAVY DUTY ELECTRIC SEALED WELL TABLES WITH ENCLOSED BASE



Sealed Well with Drain

Enclosed Base
HDSW-3-240-BS Shown
with Optional TA-255P Casters

Item #: _____ Qty #: _____

Model #: _____

Project #: _____



FEATURES:

Heavy duty construction
All welded 300 series stainless steel
Sealed wells with manifold drains
Thermostatic controls
Removable front panel to access elements for ease of service
Supplied with dish shelf
Stainless steel shelf with removable 3/8" thick poly cutting board - Ships K.D.

MATERIAL:

TOP: 18 gauge #304 stainless steel with die stamped pan openings and self rimmed. (12" x 20" opening size)
BODY: 18 gauge #304 stainless steel
LEGS: 18 gauge stainless steel with fully adjustable stainless steel bullet foot
INSULATION: Fiberglass insulation between each compartment
DISH SHELF: 18 gauge #304 stainless steel
CUTTING BOARD: White Thermoplastic
HEAT COMPARTMENT: Sealed well pan with "M" shaped tubular element underneath
PLUMBING: Manifold drain assembly included

ELECTRICAL:

120V units yield 640 Watts
208V/240V dual voltage units yield 825 Watts at 208V and 1100 Watts at 240V
8' electrical cord with plug
Infinite control knobs
Indicator lights

NOTE: For international applications, plug may need to be replaced (by others) in field.

Model #	Length	Width	# of Wells	Volts	Amps	Watts	NEMA Plug	Cubic Feet
HDSW-2-120-BS	31-13/16"	35-3/4"	2	120	10.67	1280	5-20P	31
HDSW-3-120-BS	47-1/8"	35-3/4"	3	120	16	1920	5-20P	45
HDSW-4-120-BS	62-7/16"	35-3/4"	4	120	21.33	2560	L5-30P	60
HDSW-2-240-BS	31-13/16"	35-3/4"	2	208/240	7.94/9.16	1650/2200	6-20P	31
HDSW-3-240-BS	47-1/8"	35-3/4"	3	208/240	11.91/13.74	2475/3300	6-20P	45
HDSW-4-240-BS	62-7/16"	35-3/4"	4	208/240	15.88/18.32	3300/4400	L6-30P	60
HDSW-5-240-BS	77-3/4"	35-3/4"	5	208/240	19.85/22.90	4125/5500	L6-30P	74
HDSW-6-240-BS	93-1/8"	35-3/4"	6	208/240	23.82/27.48	4950/6600	L6-30P	88

NOTE: Units are not designed to cook or heat frozen or refrigerated foods. Food placed in tables should already be hot, and the table will maintain the proper temperatures

NEMA PLUGS: Your plug will look like this...

Includes:



Includes Manifold Drain




NEMA 5-20P



NEMA 6-20P



NEMA L5-30P





NEMA L6-30P

DIMENSIONS and SPECIFICATIONS

TOL ± .125"

ALL DIMENSIONS ARE TYPICAL



Food Table Shelving & Accessories

Visit our website for additional accessories



Acrylic Food Shield has 10" Clearance from Deck

Double Sided Self-Serve Buffet Shelf with Built-In Food Shield

Model	Length	Approx Wt.	Cu. Ft.
TBS-2	31-13/16"	34 lbs.	2
TBS-3	47-1/8"	42 lbs.	3
TBS-4	62-7/16"	47 lbs.	4
TBS-5	77-3/4"	55 lbs.	4
TBS-6	93-1/8"	63 lbs.	4



Acrylic Side Panels for Buffet Shelf

Add side panels to meet additional NSF requirements (2 panels per end)

TBP-1 One End
TBP-2 Two Ends

Field Installation Available



Acrylic Food Shield has 1" Clearance from Deck

Single Sided Cafeteria Shelf with Built-In Food Shield

Model	Length	Approx Wt.	Cu. Ft.
TSS-2	31-13/16"	18 lbs.	2
TSS-3	47-1/8"	23 lbs.	3
TSS-4	62-7/16"	30 lbs.	4
TSS-5	77-3/4"	35 lbs.	4
TBS-6	93-1/8"	41 lbs.	4



Acrylic Side Panel for Serving Shelf

Add side panels to meet additional NSF requirements. (1 panel per end)

TSP-1 One end
TSP-2 Two Ends

Field Installation Available

SU-90 Automatically fills & maintains water level. For DISW, DISLSW, SW & HDSW Series.
Requires Manifold Drain Assembly (Included on HDSW series).



REF-V

325 Wireless Boulevard, Hauppauge, NY 11788

ADVANCE TABCO is constantly engaged in a program of improving our products. Therefore, we reserve the right to change specifications without prior notice.

© ADVANCE TABCO, SEPTEMBER 2025