Mixer Kettle:

Cleveland

MIXER KETTLE, ELECTRIC FLOOR TYPE, LEVER TILT 2/3 JACKETED

Project
Item
Quantity
FCSI Section 11400
Approved
Date

Models

MKDT-20-T



Standard Features

- Infinitely Variable Speed for all conditions; Scraper from 0-70 rpm, Agitator from 0-210 rpm
- Removable (without tools) Nylon Blade scrapes entire Jacketed surface
- 3/4 Horsepower D.C. Timing Belt Drive
- Safety Device prevents high speed starts
- Mixing stops when bridge is lifted includes safety cover and screen
- Agitator and Scraper are bayonet mounted for easy removal
- Enclosed, balanced, 10 Gauge Stainless Steel Mixer Bridge
- · Kettle and all exterior surfaces are stainless steel
- Steam Control Valve built into Trunnion
- Factory installed Steam Control Kit
- 50 psi Steam Jacket Rating
- Tilt Handle interchangeable for left or right operation
- Large Pouring Lip
- Double Pantry Faucet Standard
- Gallon Markings on Scraper Shaft
- Standard 120 volts, 60 Hz, single phase, 3 wire
- Typical approvals include NSF and ASME
- 316 Stainless Steel Interior
- Two piece cover with safety screen

Short Form Specifications

Shall be Cleveland, model MKDT-20-T, Floor Type, Lever Tilt, 20 gallon, Direct Steam Mixer Kettle, 50 psi Jacket Rating, Factory Installed Steam Control Kit, Type 316 Stainless Steel Interior, Steam Control Valve built into Trunnion. Infinitely Variable Speed, 3/4 H.P. Time Belt Drive, Bayonet Mounted Agitator and Scraper with removable Blades, Safety Device prevents high speed starts. Mixing stops when Bridge is lifted. Kettle and all Exterior Surfaces are Stainless Steel. 316 Stainless Steel Interior.

Options & Accessories

- Product Time/Temperate Controls and Indicators
- Food Strainer (FS-12)
- Flow Diverter (FD)
- · Kettle Accessory Kit (KAK) includes:
 - Clean-up Brush (CB)
- 36" Kettle Paddle (KP)
- 36" Kettle Whip (KW)
- 36" Kettle Brush (KB)
- Draw-off Brush (DB)
- 24 oz. Ladle (KL)
- · Pressure Reducing Valve (PRV-K)
- Water Meter (GMF or LMF) Wall Mount or on Stand (SWM)

KE004046-79