
APPLICATION:		PRO	PRODUCT NAME:			
				4" C/C DECK FAUCET	C.	
JOB NAME:				SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS	7	
QUANTITY:	ITEM NO.	МО	DEL:		- - -	
			3510	W/ 6" SWING SPOUT		
			3511	W/ 8" SWING SPOUT		
			3512	W/ 10" SWING SPOUT		
			3513	W/ 12" SWING SPOUT		
8" (MAX)— [203.2mm]			3514	W/ 14" SWING SPOUT		
"В"			1635	W/ 16" SWING SPOUT		
			OPTIONS OR MODIFICATIONS:			
	A A		☐ SUPPLY LINES (24" OR 36") CIRCLE LENGTH			
[50.8mm]			□ DJ SUB-ASSY (7-1/4" OR 13") CIRCLE LENGTH□ VANDAL RESISTANT KIT			


FOOTPRINT:

1/2" SLIP JOINT—/ [101.6mm]



MODEL	DIM "A"	DIM "B"	DIM "C"
3510	2-3/8"	6"	6"
	[60.3mm]	[152.4mm]	[152.4mm]
3511	2-5/8"	6-1/2"	8"
	[66.7mm]	[165.1mm]	[203.2mm]
3512	3-1/4"	7"	10"
	[82.6mm]	[177.8mm]	[254.0mm]
3513	3-7/8"	7-1/2"	12"
	[98.4mm]	[190.5mm]	[304.8mm]
3514	4-1/2"	8-3/8"	14"
	[114.3mm]	[212.7mm]	[355.6mm]
1635	5-1/8"	9"	16"
	[130.2mm]	[228.6mm]	[406.4mm]

ROUGH-IN:



ANSI/A112.18.1M

OTHER _

- * 4" C/C DECK MOUNT
- * SWIVELING SEAT DISKS
- * HOT SIDE STEM RIGHT HAND
- * COLD SIDE STEM LEFT HAND
- * STAINLESS STEEL SEATS
- * STAINLESS STEEL SEAT SCREWS
- * STAINLESS STEEL HANDLE SCREWS

☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE

* 1/2" SLIP JOINT KIT

SYSTEM LIMITS

- * TEMP: 40°F MIN. TO 140°F MAX.
- * PRESSURE 200 PSI MAX. STATIC
- * 2.20 GPM AT 80 PSI

SHIPPING WEIGHT

*4.75 LBS

