



BEVERAGE-AIR®

Project: _____	AIA# _____
Item: _____	
Location: _____	
Approved: _____	SIS# _____

BLAST CHILLING/SHOCK FREEZING

Solid Door Self-Contained Roll-In Blast Chiller

MODEL:
RCBL-202-R-PFA-HC



Note: Shown With Optional Ramp

3 Year Parts/Labor Warranty
5 Year Compressor Warranty

CABINET CONSTRUCTION

- Stainless steel exterior and interior (with rounded interior corners)
- Stainless steel door liner
- Die-formed leak-proof floor
- High density, polyurethane insulation
- Anti-condensation resistance, placed on the door under the gasket
- Hinged door with gasket and closing ramp system
- Ergonomic vertical handle with magnetic door close
- Thick stainless steel internal bumper to avoid damage caused by the cart
- Circuit breaker for compressor protection
- 5" High-definition, easy-to-use touch display
- Blast chilling and shock freezing modes
- Identifiable mode settings
- Customized blast chilling and blast freezing (100 cycles can be memorized)
- USB connection for uploading and downloading data
- Heated core probe, with 4 measuring points
- Pre-cooling function
- Maximum interior dimensions for carts: 35"W x 40"D x 74"H (not included)
- Ramp dimension: 43.2"W x 31.9"D (ramp not included)

OPTIONS & ACCESSORIES

- 4 Point sensor probe
- Ramp (not included)

REFRIGERATION SYSTEM

- Self-contained refrigeration system uses R290 refrigerant
- Copper-aluminum evaporator with anti-corrosion treatment
- High-ventilation evaporator to ensure the highest efficiency of the cooling system
- Evaporator installed on the back with accessible cover and adjustment of the speed of the evaporator fans



Please verify qualifying units by visiting:
www.energystar.gov/cfs

3779 Champion Blvd., Winston-Salem, NC 27105
1-888-845-9800 Fax: 1-336-245-6453
Beverage-Air.com Sales@bevair.com

BLAST CHILLER ROLL-IN: BLAST CHILLING AND SHOCK FREEZING



BEVERAGE-AIR®

MODEL	RCBL-202-R-PFA-HC
EXTERNAL DIMENSIONAL DATA	
Width Overall (in)	43.3"
Depth Overall (in)	64"
Height Overall (in)	94.5"
Number of Doors	1
Depth, Door Opening 90° (in)	104.46"
Door Opening (in)	35.43" x 74.8"
No. of Doors	1
INTERNAL DIMENSIONAL DATA	
Carts (not included)	1 GN 2/1
Internal Width Usable (in.)	35.2"
Internal Depth Overall (in.)	40.9"
Internal Height Overall (in.)	74.8"
Thickness	3.2"
PERFORMANCE DATA	
Chilling Capacity In 90 Min	242.6 lbs
Freezing Capacity In 240 Min	132 lbs
Climate Class	5
ELECTRICAL DATA	
Cabinet Voltage	208/230/3/60
Frequency	60 Hz
Total Amperes	13.2
NEMA Plug (8' cord)	15-20P
Total electric power	4,773 kW
REFRIGERATION DATA	
Condensing Unit Size, HP	1 1/4 x 3
Refrigerant	R290
Capacity (BTU/Hr) (113°F/-13°F)	4,579 x 3
Heat Rejection (W) (14°F/95°F)	8,800
Refrigerant Amount (lbs)	1.0 lbs (3x0.33 lbs)
WEIGHT DATA	
Gross Weight - Crated	1694 lbs
Height - Crated	102"
Width - Crated	49.2"
Depth - Crated	69.3"

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM).

12" Top And 3" Rear Clearance Is Required

* BT - Evap. temp. °C -> °F / Cond. temp. °C -> °F

Self-Contained Blast Chilling and Shock Freezing
Model: RCBL-202-R-PFA-HC

