

Camshelving® Elements XTRA Series

High Density Storage Top Rail System

High Density Stationary Units

4 Vented, Solid, or VS (3 Vented + 1 Solid)

HEIGHTS	DEPTHES	LENGTHS
1	3	5
81" (2057 mm)	18" (460 mm)	36" (915 mm) 54" (1375 mm)
	21" (540 mm)	42" (1070 mm) 60" (1525 mm)
	24" (610 mm)	48" (1220 mm)

- **Top Rail Stationary Starter Unit includes:**

2 factory-assembled stationary post kits, 8 traverses, traverse dovetails, shelf plates, and 4 floor fasteners. Units ship complete in 1 box.

Features & Benefits

- Trackless, open-floor design offers an alternative for environments where floor tracks may be less practical—such as uneven floors or high-traffic area requiring frequent cleaning. The open space beneath units allows for easy access and simplified maintenance, while still delivering smooth mobility and high-density storage.
- System composed of Top Rail End Kits installed onto Top Rail Stationary Units, joined by Top Rail Middle Kits. Top Rail Mobile Units with top rollers nest securely within the rail system.
- Withstands storage temperatures from -36° to 190°F (-38° to 88°C). Use in walk-in coolers, freezers, dry storage, warewashing areas, loading docks or front of the house. Impervious to moisture, chemicals, salt, food acids, and humidity.
- Posts and traverses are made of revolutionary, extremely strong composite material with a smooth, easy-to-clean surface. Stronger than common wire shelving and lighter in weight than Camshelving Premium Series. Shelf traverse dovetails snap easily and quickly into place.
- Anodized, matte-finish aluminum top rails and type 304 stainless-steel hardware are rust resistant. Top-mounted rollers glide effortlessly, regardless of unit weight or floor surface, for smooth, reliable mobility.
- Removable polypropylene shelf plates have permanent, molded-in Camguard®, an antimicrobial technology that inhibits the growth of mold, fungus and bacteria.
- Shelf traverses can be removed and adjusted easily at 4" (10,2 cm) increments.
- Recommend installing a stationary unit every 15' (4,6 m) of top rail to stabilize the system (must be bolted to the floor).
- Lifetime warranty against rust and corrosion.
- Available in 1 color – Speckled Gray (480).

Project _____

Item No. _____

Model No. _____

Quantity _____



camguard
ANTIMICROBIAL SHELF PLATES



Stationary Traverse



Floor Fastener

Weight Bearing Capacity

Weight must be evenly distributed across the entire shelf.

UNIT LENGTH
36" – 60" (915 - 1525 mm)

STATIONARY UNIT	Unit only	2,400 lbs. (1090 kg)
	Shelf only	800 (365)
	Unit with Dunnage Stand*	2,800 (1270)
	Shelf with Dunnage Stand*	1,200 (545)

* Dunnage Stands add stability and increase weight-bearing capacity on bottom shelf only. Add to any shelf length. Highly recommended for Stationary Units 54" (1375 mm) and longer.

Top Rail End Kits for Stationary Units

CODE	DESCRIPTION	CASE PACK
CSTRSERK18	18" (460 mm) Length Rail for 18" Deep Stationary Unit	1
CSTRSERK21	21" (540 mm) Length Rail for 21" Deep Stationary Unit	1
CSTRSERK24	24" (610 mm) Length Rail for 24" Deep Stationary Unit	1

Color: Silver (000).

- **Top Rail End Kit includes:**

2 Aluminum rails, 2 end caps, 4 joiners, joiner hardware, and 4 top rail bolts.

Approvals



Post Connectors, Identification Tags, Security Cages, Peg Board, Shelf Rails, Divider Bars, High Density Rail and Extension Kits are not NSF Listed.

COMPONENT

Camshelving® Elements XTRA Series

High Density Storage Top Rail System
 High Density Stationary Units
 4 Vented, Solid, or VS (3 Vented + 1 Solid)

81"
18"
 HEIGHT

21"
DEPTH

24"
DEPTH

18"
DEPTH

21"
DEPTH

24"
DEPTH

V4

4-Shelf Vented High Density Stationary Units

CODE	DIM. D x L x H
EST183681V4	18" x 36" x 81" (460 x 915 x 2057 mm)
EST184281V4	18" x 42" x 81" (460 x 1070 x 2057 mm)
EST184881V4	18" x 48" x 81" (460 x 1220 x 2057 mm)
EST185481V4	18" x 54" x 81" (460 x 1375 x 2057 mm)
EST186081V4	18" x 60" x 81" (460 x 1525 x 2057 mm)
EST213681V4	21" x 36" x 81" (540 x 915 x 2057 mm)
EST214281V4	21" x 42" x 81" (540 x 1070 x 2057 mm)
EST214881V4	21" x 48" x 81" (540 x 1220 x 2057 mm)
EST215481V4	21" x 54" x 81" (540 x 1375 x 2057 mm)
EST216081V4	21" x 60" x 81" (540 x 1525 x 2057 mm)
EST243681V4	24" x 36" x 81" (610 x 915 x 2057 mm)
EST244281V4	24" x 42" x 81" (610 x 1070 x 2057 mm)
EST244881V4	24" x 48" x 81" (610 x 1220 x 2057 mm)
EST245481V4	24" x 54" x 81" (610 x 1375 x 2057 mm)
EST246081V4	24" x 60" x 81" (610 x 1525 x 2057 mm)

Color: Speckled Gray (480).

VS4

4-Shelf, 3 Vented + 1 Solid High Density Stationary Units

CODE	DIM. D x L x H
EST183681VS4	18" x 36" x 81" (460 x 915 x 2057 mm)
EST184281VS4	18" x 42" x 81" (460 x 1070 x 2057 mm)
EST184881VS4	18" x 48" x 81" (460 x 1220 x 2057 mm)
EST185481VS4	18" x 54" x 81" (460 x 1375 x 2057 mm)
EST186081VS4	18" x 60" x 81" (460 x 1525 x 2057 mm)
EST213681VS4	21" x 36" x 81" (540 x 915 x 2057 mm)
EST214281VS4	21" x 42" x 81" (540 x 1070 x 2057 mm)
EST214881VS4	21" x 48" x 81" (540 x 1220 x 2057 mm)
EST215481VS4	21" x 54" x 81" (540 x 1375 x 2057 mm)
EST216081VS4	21" x 60" x 81" (540 x 1525 x 2057 mm)
EST243681VS4	24" x 36" x 81" (610 x 915 x 2057 mm)
EST244281VS4	24" x 42" x 81" (610 x 1070 x 2057 mm)
EST244881VS4	24" x 48" x 81" (610 x 1220 x 2057 mm)
EST245481VS4	24" x 54" x 81" (610 x 1375 x 2057 mm)
EST246081VS4	24" x 60" x 81" (610 x 1525 x 2057 mm)

Color: Speckled Gray (480).

S4

4-Shelf Solid High Density Stationary Units

CODE	DIM. D x L x H
EST183681S4	18" x 36" x 81" (460 x 915 x 2057 mm)
EST184281S4	18" x 42" x 81" (460 x 1070 x 2057 mm)
EST184881S4	18" x 48" x 81" (460 x 1220 x 2057 mm)
EST185481S4	18" x 54" x 81" (460 x 1375 x 2057 mm)
EST186081S4	18" x 60" x 81" (460 x 1525 x 2057 mm)
EST213681S4	21" x 36" x 81" (540 x 915 x 2057 mm)
EST214281S4	21" x 42" x 81" (540 x 1070 x 2057 mm)
EST214881S4	21" x 48" x 81" (540 x 1220 x 2057 mm)
EST215481S4	21" x 54" x 81" (540 x 1375 x 2057 mm)
EST216081S4	21" x 60" x 81" (540 x 1525 x 2057 mm)
EST243681S4	24" x 36" x 81" (610 x 915 x 2057 mm)
EST244281S4	24" x 42" x 81" (610 x 1070 x 2057 mm)
EST244881S4	24" x 48" x 81" (610 x 1220 x 2057 mm)
EST245481S4	24" x 54" x 81" (610 x 1375 x 2057 mm)
EST246081S4	24" x 60" x 81" (610 x 1525 x 2057 mm)

Color: Speckled Gray (480).

CAMBRO®

www.cambro.com

Information and specifications are subject to change without notice. Please confirm at time of order.

© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056, U.S.A.

Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003 Email: customerservice@cambro.com

Printed in USA. REV. 09/25

Project _____

Item No. _____

Model No. _____

Quantity _____

18"
 DEPTH

21"
 DEPTH

24"
 DEPTH

Optional Accessories

- Shelf Identification Tags
- Single Shelf Sheet Pan/Tray Rack
- Shelf Divider Panel
- Single Shelf Security Cage
- Shelf Divider Bars (Straight or Angled)
- Shelf Traverses (Single or Double)
- Shelf Rails
- Bottom Shelf Dunnage Stands
- Wall Fastener
- Single and Add-on Can Racks

Architect Specs

Posts and Traverses: Proprietary non-corrosive composite material.

Post Connectors: Reinforced polypropylene.

Shelf Plates: Reinforced polypropylene with Camguard® antimicrobial.

Floor Fasteners: Type 304 Stainless Steel.

Traverse Dovetails: Reinforced nylon.

Post Connector Collar Wedges: Reinforced nylon.

Approvals

 Post Connectors, Identification Tags, Security Cages, Peg Board, Shelf Rails, Divider Bars, High Density Rail and Extension Kits are not NSF Listed.

COMPONENT

EXTRAS