

Project_	
ltem # _	
Quantity	

36" GREEN FLAME RANGES

GAS TYPE:

NATURAL



ARGF-6

AR-12G-4B

ARGF-24G-2B

STANDARD FEATURES

- Stainless steel sides, front, and 6" deep front landing ledge
- Adjustable 6" steel legs (casters optional)
- Choice of: 6" high stainless steel stub back, high riser, or high riser with shelf at no charge
- Two year limited warranty, parts, and labor
- · Base options: Standard, convection, or storage base

OPEN BURNERS

- 12" x 12" cast iron top grates
- 22,000 BTU/hr. burners with electronic ignition, no standing pilot
- · Removable full width drip pan under burner

OVEN FEATURES

- Standard Oven 35.000 BTU/hr. burner
- Oven dimensions: 26 1/2"W x 22 1/2"D x 13 1/2"H
- Thermostat ranging from 250°F to 500°F (121°C to 260°C)
- Oven Door: Spring assisted, counterweight door
- Two chrome plated oven racks (Additional racks optional)
- Two fixed rack positions
- · Porcelain enamel oven interior for easy cleaning
- 100% safety gas shut off

CONVECTION OVEN (In place of standard oven)

- Steel oven burner rated at 30,000 BTU/hr.
- Convection oven fan improves heat transfer for a faster cook time
- · 5 position rack guide

GRIDDLES

- 1" thick steel griddle plate installed on the left side
- One burner every 12", rated at 20,000 BTU/hr.
- Stainless steel pilot for each burner for automatic ignition
- · Manual control valve for each burner

AVAILABLE OPTIONS

- Casters (Set of four- two with front brakes)
- Storage Cabinet Base (In place of standard oven)



Model Shown ARGF-6

Shown with optional casters

DESCRIPTION


American Range, Green Flame range size 36" x 32-1/2" x 56" Stainless steel front, sides, backriser, shelf, and 6" adjustable legs. Removable full width drip pan. 22,000 BTU/hr. Burners with electronic ignition, no standing pilot. Lift-off, no clog burners for easy cleaning. Heavy-duty cast iron grates, 12" x 12". Oven: 35,000 BTU/hr. standard oven or 30,000 BTU/hr. convection oven, with porcelain interior and inside door panel, oven interior measures 26 1/2"W x 22-1/2"D x 13-1/2"H. Oven thermostat adjusts from 250°F to 500°F. Ovens supplied with two racks, two rack guide sets, and four rack positions. Oven door with a spring assisted, counterweight mechanism requiring no adjustment. Rear gas connection and pressure regulator. Requires power outlet, 115 amp three prong cord provided.

















Shipping	Weight
Shipping	Weight

							SHIPPIN	g vveignt*
ТОР		MODEL	BTU/hr.	(KW)	BURNERS	GRIDDLE SIZE	LBS	(KG)
36"		ARGF-6	167,000	(54)	6	N/A	420	(191)
		ARGF-6-C	162,000	(53)	6	N/A	493	(224)
		ARGF-6-SB	137,000	(44)	6	N/A	350	(159)
36"		ARGF-12G-4B	143,000	(37)	2	24" (610 MM)	450	(200)
		ARGF-12G-4B-C	138,000	(35)	2	24" (610 MM)	523	(237)
		ARGF-12G-4B-SB	103,000	(26)	2	24" (610 MM)	380	(172)
36"		ARGF-24G-2B	119,000	(37)	2	24" (610 MM)	450	(200)
		ARGF-24G-2B-C	114,000	(35)	2	24" (610 MM)	523	(237)
		ARGF-24G-2B-SB	89,000	(26)	2	24" (610 MM)	380	(172)

"SB" = Storage Base, "G" = Manual Griddle Top, "B" = Burner.

Griddle on the left. Contact factory for other options.

Specify type of gas and altitude if over 2000 feet. Please specify gas type when ordering.

15 amps three prong cord provided

*Shipping weight includes packaging and is approximate.

MANIFOLD PRESSURE NATURAL GAS PROPANE GAS MANIFOLD SIZE					
5.0" W.C.	10.0" W.C.	3/4" (19MM)			

COMBUSTIBLE WALL CLEARANCES:

For use only on non-combustible floors. Legs or casters are required, or 2" (51) overhang is required when curb mounted. Clearance from non-combustible walls is 0". When unit is placed next to combustible walls, clearances must exceed 12" (305) from sides, and 4" (102) from rear.

Commercial cooking equipment requires an adequate ventilation system. For additional information, refer to the National Fire Protection Association's standard.

NFPA96 "Vapor Removal from Cooking Equipment." (NOTE: For North America only)

American Range is a quality manufacturer of commercial cooking equipment. Because of continuing product improvements these specifications are subject to change without prior notice.





