SINGLE WALL MOUNT SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS MODEL: 2.750 OPTIONS OR MODIFICATIONS: SUPPLY LINES (24" OR 36") CIRCLE LENGTH ADD-ON FAUCET (6".8".10",12",14",16") CIRCLE LGTH BACKFLOW PREVENTER PIPE HOOK NIPPLES ELBOWS VANDAL RESISTANT KIT HANDLES (CROSS OR WRIST) CIRCLE STYLE OTHER FEATURES: CONTROL VALVE SINGLE WALL MOUNT STEM - RIGHT HAND SWIVELING SEAT DISKS HOT & COLD INDEX BUTTONS STAINLESS STEEL SEAT'S STAINLESS STEEL SEAT SCREWS STAINLESS STEEL END FITTINGS STAINLESS STEEL EXTERNAL JACKET BRAIDED USDA APPROVED FOODGRADE INTERNAL HOSE REPAIRABLE IN FIELD WITH SIMPLE TOOLS
QUANTITY: ITEM NO. MODEL: 2750 OPTIONS OR MODIFICATIONS: SUPPLY LINES (24" OR 36") CIRCLE LENGTH ADD-ON FAUCET (6",8",10",12",14",16") CIRCLE LGTH BACKFLOW PREVENTER PIPE HOOK NIPPLES ELBOWS LENGTH HOSE FEATURES: CONTROL VALVE SINGLE WALL MOUNT STEM - RIGHT HAND SWIVELING SEAT DISKS HOT & COLD INDEX BUTTONS STAINLESS STEEL SEATS STAINLESS STEEL SEATS STAINLESS STEEL SEAT SCREWS STAINLESS STEEL BAT SCREWS BAIDED USDA APPROVED FOODGRADE INTERNAL HOSE
WALL HOOK 2-3/8" [60.0mm] 4-5/8" [1117.5mm] 4-3/8" (MAX) [1111.1mm] 4-3/8" (MAX) [1111.1mm] 60" LENGTH HOSE 60" LENGTH HOSE HOSE HOSE HOSE HOSE HOSE HOSE HOS
OPTIONS OR MODIFICATIONS: SUPPLY LINES (24" OR 36") CIRCLE LENGTH ADD-ON FAUCET (6",8",10",12",14",16") CIRCLE LGTH BACKFLOW PREVENTER PIPE HOOK NIPPLES ELBOWS VANDAL RESISTANT KIT HANDLES (CROSS OR WRIST) CIRCLE STYLE OTHER OTHER FEATURES: CONTROL VALVE * SINGLE WALL MOUNT * STEM - RIGH HAND * SWIVELING SEAT DISKS * HOT & COLD INDEX BUTTONS * STAINLESS STEEL SEATS * STAINLESS STEEL SEATS * STAINLESS STEEL SEATS * STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS HOSE * 60" LENGTH * STAINLESS STEEL EXTERNAL JACKET * BRAIDED USDA APPROVED FOODGRADE INTERNAL HOSE
ROUGH-IN: 1/2" NPT FEMALE 1/2" NPT FEMALE * 5.00 GPM AT 80 PSI * AERATED STREAM SWIVEL ELBOW * 360° TURNING RADIUS SYSTEM LIMITS * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE 200 PSI MAX. STATIC SHIPPING WEIGHT * 6.5 LBS

(F) ANSI/A112.18.1M