GARLAND

Designer Series Electric Griddles

| Project | |
|-------------------|---|
| | |
| Item | - |
| Quantity | |
| | |
| CSI Section 11400 | |
| Approved | |
| | _ |
| Date | |
| | |

Models

- ED-15G
- ED-24G
- ED-36G



Model ED-24G

Standard Features

- Stainless steel front and sides
- Easy clean design with recessed protected controls.
- · Heat-on indicator lamps
- Thermostat controlled, temperature settings 100°-450° F (38°-232° C).
- 18" (457mm) deep cooking surface
- 4" (102mm) stainless steel legs.
- 1/2" (13mm) polished steel griddle with 2-5/8" (67mm) welded splash guard on sides and rear of plate
- · Concealed grease drawer
- One-year limited parts & labor warranty (USA & Canada only)

Options & Accessories

- Stainless steel back and bottom
- Fully grooved griddle, add suffix U
 (i.e. GD-15GU) or grooved sections,
 add U1 for 12" (305mm) on left side
 and U2 for 24" (610mm) on left side
- Stands are available

Specifications

Electric designer series griddles in three widths: models ED-15G, 15" (381mm) wide; ED-24G, 24" (610mm) wide and ED-36G, 36" (914mm) wide.

Designed as free standing or to be banked with other ED series equipment.

24" (610mm) deep \times 13-3/4" (349mm) high, easy clean design with stainless steel front and sides.

Thermostat controlled, with improved insulation underneath the elements allowing for better heat efficiency.

Concealed grease drawer behind lower hinged panel.

Fully grooved or grooved section griddle available.









General Inquires 1-905-624-0260 USA Sales, Parts and Service 1-800-424-2411 Canadian Sales 1-888-442-7526 Canada or USA Parts/Service 1-800-427-6668


www.garland-group.com 6839A 05/25





Garland products are not approved or authorized for home or residential use, but are intended for commercial applications only. Garland will not provide service, warranty, maintenance or support of any kind other than in commercial applications.





| | Total kW Load | | | | Nominal Amperes Per Line | | | | | | | |
|--------|---------------|------|---------------|---------------|--------------------------|------|------------------|------|---------------|---------------|-------------------------|---------------|
| | | | | | North America | | | | Export | | | |
| Models | North America | | Export | | Single Phase | | Hi Line -3 Phase | | Single Phase | | Hi Line - 2 or -3 Phase | |
| | 208V | 240V | 220V/ 380V | 240V/ 415V | 208V | 240V | 208V | 240V | 220V/ 380V | 240V/ 415V | 220V/ 380V | 240V/ 415V |
| ED-15G | 3.4 | 3.4 | 3.4 | 3.4 | 17 | 14 | N/A | N/A | 16 | 14 | N/A | N/A |
| ED-24G | 6.7 | 6.7 | 6.7 | 6.7 | 33 | 28 | 28 | 25 | 31 | 28 | 16 | 14 |
| ED-36G | 10.1 | 10.1 | 10.1 | 10.1 | 49 | 42 | 28 | 25 | 46 | 42 | 16 | 14 |

| Model | Overall Dimensions | | Usable Cooking Surface | C. Et | Chin Wt I byles | | |
|--------|--------------------|-------------|------------------------|-----------------|-----------------|---------|----------------|
| | Height | Width | Depth | Width | Depth | Cu. Ft. | Ship Wt. Lb/kg |
| ED-15G | 13-3/4" (349mm) | 15" (381mm) | 24" (610mm) | 14-5/8" (371mm) | 18" (457mm) | 6 | 90/41 |
| ED-24G | 13-3/4" (349mm) | 24" (610mm) | 24" (610mm) | 23-5/8" (600mm) | 18" (457mm) | 8 | 135/61 |
| ED-36G | 13-3/4" (349mm) | 36" (914mm) | 24" (610mm) | 35-5/8" (876mm) | 18" (457mm) | 11 | 175/80 |

| Installation Clearances | | | |
|-------------------------|-------------|--|--|
| Side | Rear | | |
| 1" (25mm) | 1.5" (38mm) | | |

Garland reserves the right to make changes to the design or specifications without prior notice.

