

Project
ltem #
Quantity

LOW BOY, ROAST AND BAKE OVENS

ARDS-36 ARDS-36-C-126

ARLB-36 ARLB-36-C

STANDARD FEATURES

- Overall dimensions: 36"W x 31 5/8"D x 33 3/8"H
- Available in single (ARLB) or double stack (ARDS)
- Adjustable 6" steel legs (Casters optional)
- · Standard pilot ignition system
- Oven dimensions: 26 1/2"W x 22 1/2"D x 13 1/2"H
- Thermostat ranging from 250°F to 500°F (121°C to 260°C)
- Oven Door: Spring assisted, counterweight door
- Two chrome plated oven racks (Additional racks optional)
- Porcelain enamel oven interior for easy cleaning
- 100% safety gas shut off
- Two year limited warranty, parts, and labor

STANDARD OVEN

- Steel oven burner rated at 35,000 BTU/hr.
- · Two fixed rack positions

CONVECTION OVEN

- Steel oven burner rated at 30,000 BTU/hr.
- · Chrome rack guides with five tray positions

GAS TYPE: NATURAL | LP



Model Shown ARLB-36

Shown with optional casters

DESCRIPTION

Stainless front and sides. Oven holds 18x26 sheet pans horizontally. Porcelain enamel oven interior for easy cleaning. Oven dimensions 26 ½" wx 22 ½" D x 13 ½". Standard oven 35,000 BTU/hr. and convection oven 30,000 BTU/hr. Two oven racks standard. Standing pilot ignition system. Thermostat ranges from 250°F to 500°F. Adjustable 6" legs. Optional casters. Single unit or double stacked available. Two year limited warranty, parts, and labor.












LOW BOY, ROAST AND BAKE OVENS







SHIPPING WEIGHT*

MODEL	WIDTH (MM)	DEPTH (MM)	HEIGHT (MM)	BTU/hr.	(KW)	LBS	(KG)
26½" Standard Oven							
ARLB-36	36" (914)	31 5/8"(803)	33 3/8"(848)	35,000	(11)	300	(136)
26½" Convection Oven							
ARLB-36-C	36" (914)	31 5/8"(803)	33 3/8"(848)	30,000	(9)	350	(159)
26½" Standard Ovens, Stacked							
ARDS-36	36" (914)	31 5/8"(803)	55 1/4"(1403)	70,000	(22)	600	(273)
261/2" Convection and (1) Stand	ard Ovens						
ARDS-36-C-126	36" (914)	31 5/8"(803)	55 1/4"(1403)	60,000	(18)	700	(318)

- Specify type of gas and altitude if over 2000 feet.
- Please specify gas type when ordering.

*Shipping weight includes packaging and is approximate.

MANIFOLD PRESSURE NATURAL GAS PROPANE GAS MANIFOLD SIZE					
5.0" W.C.	10.0" W.C.	3/4" (19MM)			

COMBUSTIBLE WALL CLEARANCES:

For use only on non-combustible floors. Legs or casters are required, or 2" (51) overhang is required when curb mounted. Clearance from non-combustible walls is 0". When unit is placed next to combustible walls, clearances must exceed 12" (305) from sides, and 4" (102) from rear.

Commercial cooking equipment requires an adequate ventilation system. For additional information, refer to the National Fire Protection Association's standard.

NFPA96 "Vapor Removal from Cooking Equipment." (NOTE: For North America only)

American Range is a quality manufacturer of commercial cooking equipment. Because of continuing product improvements these specifications are subject to change without prior notice.





