

PROJECT:		
ITEM #	QTY:	
MODEL #		
AIA #	SIS #	

# **EXTRA WIDE PASS-THRU WARMING CABINET & REFRIGERATOR**

# HRS-2D-S1-EW-PT-HC



# **EXCLUSIVE WARRANTY**

- 7 Year Parts, Labor and Compressor
- Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (parts only)



### CABINET CONSTRUCTION

- · Stainless Steel Exterior And Interior
- Stainless Steel Interior Door Liner
- Warming Cabinet On The Left, Refrigerator On The Right
- · Stay-Open Door Feature For Easy Product Loading
- · 20 Gauge Stainless Steel Door
- Refrigerator Has Magnetic Door Switch Automatically Activates Interior LED Light
- Warmer Has Magnetic Door Switch Automatically Activates Interior Incandescent Light
- · Heavy-Duty Cylinder Locks
- · One-Piece, Snap-In Magnetic Door Gaskets
- · Low Profile Vertical Door Handles
- · Hinged Front Shroud
- · Thermal Breaker
- · Stainless Steel Breaker Caps
- · 6 Silver Freeze Wire Shelves
- · 6" High Adjustable Stainless Steel Legs
- · 8' Cord And Plug (see electrical data for details)

## **FEATURES**

- · Full Electronic Control With Touchpoint Interface
- Expansion Valve Technology (refrigerator only)
- Insulated Partition Wall Separates Compartments

# REFRIGERATION

- Refrigeration System Uses R290 Refrigerant To Comply With All Environmental Concerns
- · Hot Gas Condensate Evaporator
- · Automatic Non-Electric, Defrost
- · Epoxy Coated Evaporator Coil, Located Out Of The Food Zone
- Refrigerator Capable Of Maintaining Product Temperature 36°F To 38°F

# **HEATING**

- Warming Cabinet Maintains Product Temperature 80°F To 180°F



Please Verify Qualifying Units By Visiting: www.energystar.gov/cfs

#### **OPTIONS & ACCESSORIES**

c(I) W/kcl R AQ

- Stainless Steel Case BackStainless Steel Kick Plate
- Additional Shelves
- Tray Slides (type A & A/C)
- · Door Swing Orientation (at time of order)
- Exterior Door Laminate

· Glass Door Models

- 6" Casters Or 6" Seismic Legs
- Correctional Package
- Remote Models\* (refrigerators & 6" legs only) (refrigerant must be specified at time of order, see note on back on page)

3770	Champion	Blvd	Winston-Salem	NC 2710
3//7	CHAILIDIOLL	Divu,	WILISTOLI-Salelli	NC 2/ 10

ph: (888) 845-9800 fax: (800) 253-5168


Sales@VictoryRefrigeration.com VictoryRefrigeration.com


Rev. 6/26/25 Printed in the U.S.A.


\DDD(\/\I.	DATE:	











We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

### 12" Top clearance is required

CHARACTERISTICS		ELECTRICAL DATA REFRIGERATOR		SHIPPING DETAILS		
Net Capacity R/W	25.6 / 25.6	Cabinet Voltage**	115/60/1	Height	88"	
Width, Overall (in.)	58 3/8"	Total Amperes	6.5	Width	66"	
Depth, Overall (with handle)	38 3/4"	NEMA Plug (8' cord)	5-15P	Depth	41"	
Height Overall (6" legs)	84 1/4"	REFRIGERATION DATA	Crated Weight	758 lbs		
Depth, Door Open 90°	87"	Condensing Unit Size, HP	1/3			
Door Openings (in.)	23" x 54 5/8"	Refrigerant	R290			
No. Of Doors / Shelves	4/6	Capacity (BTU/HR) (100°F/20°F)	Refrigerator - 2220 Warmer - N/A	*NOTE: Remote unit are field		
ELECTRICAL DATA WARMING CABINET		Heat Rejection (BTU/HR)	3330	wired and come with 6" legs Refrigerant must be specified		
Cabinet Voltage	230/60/1	Charge (lbs/grams/ounces)	0.372 / 169 / 5.96	at time of order.		
Total Amperes	3.7					
NEMA Plug (8' cord)	6-20P					

<sup>\*\*</sup> NOTE: This unit utilizes variable speed compressor technology. The compressor can experience nuisance tripping on Class A GFCI outlets which have a trip limit of 4 mA to 6 mA. To avoid this issue in a location that requires GFCI circuit protection, Victory recommends using either an Eaton, SGF20, or HUBBELL Model Number GFRST83W 20A Heavy Duty Hospital Grade Self-Test GFCI Receptacle.

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168 

Rev. 6/26/25 Printed in the U.S.A

