

Specification/Data sheet


Integration kit UltraVent Plus US for XS model 6 2/3



Item number: 60.74.408

Description

- For hygienic integration of a XS model 6 2/3 into a wall unit
- Integrated UltraVent Plus XS with special filter technology. This prevents both vapours and the lingering smoke that builds up while grilling and roasting.
- Eliminates the need for laborious installation of separate air extraction technology
- Targeted air direction ensures necessary cooling of the unit
- Stainless steel trim kit fulfills even the most stringent hygiene requirements
- Attractive design creates a professional, harmonious overall appearance
- Prevents build-up of spoilage in difficult-to-reach places
- Easy to clean



Special feature/equipment

- Easy-to-clean grease filter (CNS), dishwasher-safe
- High-performance extraction
- Proximity door contact switch
- Extraction rate automatically increased when cabinet door is opened
- Wastewater discharged by the device - no additional discharge line needed
- Stainless steel trim kit
- Waste water removal through the unit

Capacity

- NONE

Technical Specifications

- Connection: 100-125V 1 NAC 50-60 HZ
- Connected load: 160-215W
- Extraction power: 9,900-20,000 ft³/h 280-560 m³/h
- Operating noise level less than 67dBA
- For wall unit interiors 27 1/2" (700 mm) wide, 37 3/8" (950 mm) high, 23 5/8" (600 mm) deep
- Certification: UL
- Weight: 73 lbs (33 kg)

Material

- Stainless steel (CNS 1.4301)

Note

- Adhere to all local standards and regulations regarding installation and room ventilation systems
- Usable on units with either left-sided or right-sided hinges

