



"WE MAKE THE KITCHEN BETTER!"

ATOSA USA, INC.

Toll Free: 855-855-0399 Email: info@atosausa.com

www.atosa.com | www.atosausa.com

California, Colorado, Florida, Georgia, Illinois,
New Jersey, Ohio, Texas, Washington

Top Mount Reach-In Freezers

Standard Features

- Top mount compressor with environmentally friendly R290 refrigerant
- Stainless steel exterior & interior
- Electronic temperature controller
- Maintains temperatures between -8°F – 0°F
- LED interior light(s)
- Recessed door handle(s)
- Door lock(s) standard
- Magnetic door gasket(s) standard for positive door seal
- Pre-installed casters
- Three (3) pre-installed shelves per section
- Down duct refrigeration to ensure even distribution of air
- Wall bracket standard for MBF15FSGR(L) and is required for use

Optional Accessories

- Extra shelves – includes 4 shelf clips per shelf
MBF15FSGR(L) shelf part #: R060040000003
MBF8001GR(L) shelf part #: W0402389
MBF8002GR shelf part #: W0402385
MBF8003GR shelf part #: W0402385 left/right shelf,
part #: W0402386 middle shelf

For the best results of food preservation we recommend setting your freezer between -8°F to 0°F

1. Don't forget to leave the unit some room to breathe!
2. Please clean the condenser frequently to give the unit more fresh air.

MODELS:

**MBF15FSGR / MBF15FSGRL / MBF8001GR
MBF8001GRL / MBF8002GR / MBF8003GR**



MBF15FSGR MBF15FSGRL MBF8001GR



MBF8001GRL

MBF8002GR



MBF8003GR



**2 YEAR PARTS AND LABOR WARRANTY
5 YEAR COMPRESSOR PART WARRANTY**



MBF8001GR(L)
MBF8002GR



REV. 09/25



"WE MAKE THE KITCHEN BETTER!"

ATOSA USA, INC.

Toll Free: 855-855-0399 Email: info@atosausa.com

www.atosa.com | www.atosausa.com


California, Colorado, Florida, Georgia, Illinois,
New Jersey, Ohio, Texas, Washington

SPECIFICATIONS


Models	Door	Capacity (Cu.Ft.)	Shelves	Casters (inch)	Rated Current (A)	Voltage (V/Hz/Ph)	HP	Refrigerant	Exterior Dimensions (inch)	Net Weight (lb)	Gross Weight (lb)
MBF15FSGR	1	13	3	4	6.3	115/60/1	1/2	R290	17 ^{3/4} ×37×81 ^{1/2}	198	277
MBF15FSGRL	1	13	3	4	6.3	115/60/1	1/2	R290	17 ^{3/4} ×37×81 ^{1/2}	198	277
MBF8001GR	1	21.4	3	4	6.3	115/60/1	1/2	R290	28 ^{3/4} ×31 ^{3/4} ×81 ^{3/8}	236	269
MBF8001GRL	1	21.4	3	4	6.3	115/60/1	1/2	R290	28 ^{3/4} ×31 ^{3/4} ×81 ^{3/8}	236	269
MBF8002GR	2	43.2	6	4	8.6	115/60/1	3/4	R290	51 ^{3/4} ×31 ^{3/4} ×81 ^{3/8}	353	403
MBF8003GR	3	64.9	9	4	6.2	208-230/115/60/1	1	R290	77 ^{3/4} ×31 ^{3/4} ×81 ^{3/8}	489	569

PLAN VIEW


MBF8001GR





MBF8001GRL




MBF8002GR






MBF8003GR



*Interior Dimensions









MBF15FSGR



MBF15FSGRL

SELF-CLOSING
AND STAY OPEN
DOOR FEATURE



Casters

Epoxy shelves

Door lock

Down duct

Temperature control

MBF15FSGR
MBF8003GR MBF8001GR
MBF8002GR

