

PASTRY



METAL CAGE CANDY THERMOMETER

80 to 200 °C. Centigrade only. 12" length.

U526

REPLACEMENT THERMOMETER

Fits into metal cage.

U526 R

HOLDER FOR U526 THERMOMETER

Attaches to pot and clasps onto thermometer. Stainless steel.

U526 H



CHOCOLATE TEMPERING THERMOMETER

For chocolate tempering. Durable laboratory glass. Non-mercuric column. Protective case. 40 to 130 °F. 11.75" length.

U787



CONFECTION THERMOMETER

Stainless steel and plastic construction with pot clip on back. 100 to 400 °F (40 to 200 °C). 12" length.

U505 B

PENS

Highly stable and accurate readings with a large LCD display. Designed for simple one-hand operation. The case is IP65 waterproof, and will float if accidentally dropped into the water. Comes with 4 button-cell batteries and a built-in probe with protective cap. 6.5" length.



A. ATC PH PEN

Automatically calibrates to pH 4, 7, 10 buffers and can be adjusted to recognize non-standard buffers as well. Features hold function, and auto power off with low battery indicator.

U991

B. PH BUFFER SET

Includes one 40ml bottle of each of the following: pH 4, pH 7, pH 10. Needed to recalibrate ATC pH Pen (**U991**) 2.5" height x 1.5" square.

U992

C. SALINITY PEN

Simultaneously displays the parameter being measured and temperature in °C or °F. Features automatic temperature compensation, 2-pt. calibration, auto power off, hold function, and a low battery indicator.

U993

LASER (NON-CONTACT) THERMOMETERS

Infrared laser measures surface temperature at close range and at distances of many feet.

D. FOOD SAFETY LASER/PROBE THERMOMETER

A non contact infrared (IR) and probe thermometer all in one unit. The IR portion has a temperature range of -30 to 525 °F (-35 to 275 °C). The probe has a temperature range of -40 to 390 °F (-40 to 200 °C). It is designed to support HACCP monitoring systems. The unit includes a canvas belt sheath and 9 volt battery. 1 year warranty from manufacturer.

U902

E. COOPER LASER SCANNER

Ranges -25 to 400 °F, -30 to 204 °C. 7.5" length. Powered by 9-volt battery (not included). 1 year warranty from manufacturer.

U782

F. LASER SCANNER

Ranges: -4 to 518 °F, -20% to 270 °C. 8" length. Powered by 9-volt battery (included). Five year warranty from manufacturer.

U783 A

