



Discover the Art of Display...




Provino I with optional glass side

Visit our website for optional RAL colors and Materials finishes.

[RAL Colors Website](#)

[Materials Brochure PDF](#)



Examples of optional 6mm thick stone back panel behind shelf. For full selection see our Materials Brochure.

Project Name: _____

Item #: _____ Quantity: _____

PROVINO I WINE

MODELS: PROVINO I W700, W1400, W1400-2T, W2100, W2800

STANDARD FEATURES

- Solid Side
- Dual Medium Temperature Version with intermediate double glass divider
- Triple pane glass premium door
- Steel load bearing structure
- 3000°K LED lighting with dimmer switch
- Touch Control
- Ventilated cooling
- interior vertical shelf support in stainless steel
- adjustable feet
- standard steel 304A
- stainless steel interior and exterior
- Stainless steel shelves adjustable in height on racks (4 shelves included per door)
- programmed automatic electric defrost
- Approvals: cETLus, ETL sanitation, certified CE
- Self-contained
- Condensate evaporator pan

OPTIONS

- RAL Color Option powder coated door handles exterior and interior over stainless
- Front wood laminate door and handles
- interior shelf trim
- 6mm thick stone back panel behind shelf
- Glass Sides
- Sliding Doors
- Front wood laminate storage doors finish on base
- top door and interior shelf trim
- Top door
- door locks
- Remote application
- Top mounted condensing unit
- water cooled
- central refrigeration rack
- 60 Hz components UL
- 6mm thick stone back panel behind shelf
- Glass Sides
- Narrow Depth
- front breathing available for 1400L - 2800L models
- **Shelf options:** horizontal, slanted, combination (see section views)

**Oscartek® reserves the right to change, modify, discontinue, or change any features, sizes, or capacity on any model without prior notice.*

OSCARTEK®

512 South Airport Blvd., South San Francisco, CA 94080


Tel: 855.885.2400 | 650.342.2400 | Fax: 650.342.7400

sales@oscartek.com | www.oscartek.com




MODELS: PROVINO I W700, W1400, W1400-2T, W2100, W2800

PROVINO I PLAN VIEWS



ELECTRICAL LEGEND	
	REFRIGERATION LINES
	DRAIN
	POWER

PROVINO I REAR ELEVATIONS (OPERATOR SIDE)



*Oscartek® reserves the right to change, modify, discontinue, or change any features, sizes, or capacity on any model without prior notice.

OSCARTEK®
512 South Airport Blvd., South San Francisco, CA 94080
Tel: 855.885.2400 | 650.342.2400 | Fax: 650.342.7400
sales@oscartek.com | www.oscartek.com

MODELS: PROVINO I W700, W1400, W1400-2T, W2100, W2800

PROVINO I - STANDARD DEPTH SECTION VIEWS

**STANDARD:
SELF-CONTAINED**

**STANDARD:
REMOTE WITH
VERTICAL SHELVES**


**OPTIONAL:
GLASS SIDE**

**OPTIONAL:
TOP MOUNTED
CONDENSING UNIT**

**OPTIONAL:
SLIDING DOORS
ONLY IN SOLID
SIDES & 2100, 2800
MODELS**

**OPTIONAL:
SLANTED SHELVES**

**OPTIONAL:
HORIZONTAL
SHELVES**



PROVINO I - NARROW DEPTH SECTION VIEWS


**STANDARD:
SELF-CONTAINED**

**STANDARD:
REMOTE WITH
VERTICAL SHELVES**

**OPTIONAL:
GLASS SIDE**

**OPTIONAL:
TOP MOUNTED
CONDENSING UNIT**

**OPTIONAL:
SLIDING DOORS
ONLY IN SOLID SIDES
AND 2100, 2800
MODELS**



*Oscartek® reserves the right to change, modify, discontinue, or change any features, sizes, or capacity on any model without prior notice.

OSCARTEK®
512 South Airport Blvd., South San Francisco, CA 94080
Tel: 855.885.2400 | 650.342.2400 | Fax: 650.342.7400
sales@oscartek.com | www.oscartek.com

MODELS: PROVINO I W700, W1400, W1400-2T, W2100, W2800

Project Name: _____

Item #: _____ Quantity: _____

PROVINO I WINE - SELF CONTAINED						
TECHNICAL FEATURES		MODELS				
Model Name (Model ETL Code)		PROVINO I W700 (MUROGALA1P)	PROVINO I W1400 (MUROGALA2P)	PROVINO I W1400-2T (MUROGALA1P) X2	PROVINO I W2100 (MUROGALA3P)	PROVINO I W2800 (MUROGALA4P)
External Dimensions (L-D-H) Inches-MM	Inches MM	*27 1/2" - 32 3/8" - 86 3/4" *700 - 821 - 2022	*55 1/8" - 32 3/8" - 86 3/4" *1400 - 821 - 2022	*55 1/8" - 32 3/8" - 86 3/4" *1400 - 821 - 2022	*82 5/8" - 32 3/8" - 86 3/4" *2100 - 821 - 2022	*110 1/4" - 32 3/8" - 86 3/4" *2800 - 821 - 2022
Crated Dimensions (L-D-H) Inches-MM	Inches MM	35" - 39" - 98" 880 - 970 - 2470	63" - 39" - 98" 1580 - 970 - 2470	63" - 39" - 98" 1580 - 970 - 2470	90" - 39" - 98" 2280 - 970 - 2470	118" - 39" - 98" 2980 - 970 - 2470
Refrigeration	Type	Fan - Ventilated	Fan - Ventilated	Fan - Ventilated	Fan - Ventilated	Fan - Ventilated
Refrigeration Display Area	Type	Deck	Deck	Deck	Deck	Deck
Number of Glass Doors	#	1	2	2	3	4
Wine Rack Shelves	bottle orientation: #	Vertical: 4 Horizontal: 14 Slanted: 11	Vertical: 8 Horizontal: 28 Slanted: 22	Vertical: (2) 4 Horizontal: (2) 14 Slanted: (2) 11	Vertical: 12 Horizontal: 42 Slanted: 33	Vertical: 16 Horizontal: 56 Slanted: 44
	bottle orientation: #	Vertical: 140 Horizontal: 112 Slanted: 66	Vertical: 300 Horizontal: 224 Slanted: 132	Vertical: (2) 140 Horizontal: (2) 112 Slanted: (2) 66	Vertical: 480 Horizontal: 336 Slanted: 198	Vertical: 660 Horizontal: 448 Slanted: 308
Bottle Capacity (STD size)						
Operating Temperature	°F	45°F to 58°F	45°F to 58°F	45°F to 58°F	45°F to 58°F	45°F to 58°F
Condensing Units	#	1	2	2	3	4
Compressor	Nr./Type	1 / Hermetic	1 / Hermetic	1 / Hermetic	1 / Hermetic	2 / Hermetic
Electric Supply	(V/Ph/Hz)	220/1/60	220/1/60	(2) 220/1/60	220/1/60	220/1/60
Power Consumption	(W/A)	700/3.9	1200/6.9	(2) 650/3.5	1700/9.5	2300/12.9
Defrost	Mode/Type	Automatic	Automatic	Automatic	Automatic	Automatic
Climatic Class	°F/%RH	75°F-55%RH	75°F-55%RH	75°F-55%RH	75°F-55%RH	75°F-55%RH
Refrigerant Gas	Type	R290	R290	R290	R290	R291
Net Weights	Lb	309	573	661	750	904
Crated Weights	Lb	369	633	721	810	964

*DIMENSIONS WITH POLISHED S/S SIDES

PROVINO I WINE - REMOTE						
TECHNICAL FEATURES		MODELS				
Model Name (Model Code)		PROVINO I W700 (MUROGALA1P)	PROVINO I W1400 (MUROGALA2P)	PROVINO I W1400-2T (MUROGALA1P) X2	PROVINO I W2100 (MUROGALA3P)	PROVINO I W2800 (MUROGALA4P)
External Dimensions (L-D-H) Inches-MM	Inches MM	*27 1/2" - 30 3/8" - 86 3/4" *700 - 771 - 2022	*55 1/8" - 30 3/8" - 86 3/4" *1400 - 771 - 2022	*55 1/8" - 30 3/8" - 86 3/4" *1400 - 771 - 2022	*82 5/8" - 30 3/8" - 86 3/4" *2100 - 771 - 2022	*110 1/4" - 30 3/8" - 86 3/4" *2800 - 771 - 2022
Crated Dimensions (L-D-H) Inches-MM	Inches MM	35" - 39" - 98" 880 - 970 - 2470	63" - 39" - 98" 1580 - 970 - 2470	63" - 39" - 98" 1580 - 970 - 2470	90" - 39" - 98" 2280 - 970 - 2470	118" - 39" - 98" 2980 - 970 - 2470
Refrigeration	Type	Fan - Ventilated	Fan - Ventilated	Fan - Ventilated	Fan - Ventilated	Fan - Ventilated
Refrigeration Display Area	Type	Deck	Deck	Deck	Deck	Deck
Number of Glass Doors	#	1	2	2	3	4
Wine Rack Shelves	bottle orientation: #	Vertical: 5 Horizontal: 16 Slanted: 12	Vertical: 10 Horizontal: 32 Slanted: 24	Vertical: (2) 5 Horizontal: (2) 16 Slanted: (2) 12	Vertical: 15 Horizontal: 16 Slanted: 36	Vertical: 20 Horizontal: 64 Slanted: 48
	bottle orientation: #	Vertical: 175 Horizontal: 128 Slanted: 72	Vertical: 375 Horizontal: 256 Slanted: 144	Vertical: (2) 175 Horizontal: (2) 128 Slanted: (2) 72	Vertical: 600 Horizontal: 384 Slanted: 216	Vertical: 825 Horizontal: 512 Slanted: 336
Bottle Capacity (STD size)						
Operating Temperature	°F	45°F to 58°F	45°F to 58°F	45°F to 58°F	45°F to 58°F	45°F to 58°F
Condensing Units	#	1	2	2	3	4
Compressor	Nr./Type	1 / Hermetic	1 / Hermetic	1 / Hermetic	1 / Hermetic	2 / Hermetic
BTU'S @ +14°F Evap Temperature	BTU/H	2730	4980	(2) 2500	6830	7950
Electric Supply	(V/Ph/Hz)	220/1/60	220/1/60	(2) 220/1/60	220/1/60	220/1/60
Power Consumption	(W/A)	700/3.9	1200/6.9	(2) 650/3.5	1700/9.5	2300/12.9
Defrost	Mode/Type	Automatic	Automatic	Automatic	Automatic	Automatic
Climatic Class	°F/%RH	75°F-55%RH	75°F-55%RH	75°F-55%RH	75°F-55%RH	75°F-55%RH
Refrigerant Gas	Type	R452a	R452a	R452a	R452a	R452a
Pipe Size (Suction-Liquid)	(INCHES)	15/32" - 15/64"	35/64" - 5/16"	(2) 15/32" - 15/64"	5/8" - 5/16"	45/64" - 25/64"
Net Weights	Lb	309	573	661	750	904
Crated Weights	Lb	369	633	721	810	964

*DIMENSIONS WITH POLISHED S/S SIDES

*Oscartek® reserves the right to change, modify, discontinue, or change any features, sizes, or capacity on any model without prior notice.

 OSCARTEK®
 512 South Airport Blvd., South San Francisco, CA 94080
 Tel: 855.885.2400 | 650.342.2400 | Fax: 650.342.7400
 sales@oscartek.com | www.oscartek.com
