



## Encore® Dual Extended Pedal Foot Operated Valve

### KL24-1302



Dimensions shown in inches (mm) are for reference only  
and are subject to change.

#### Pedal Valve:

(2) 1/2" NPT Female Inlets  
(1) 3/8" NPT Female Outlet  
Operating Temperature: 40°F to 140°F  
Operating Pressure: 20 - 125psi  
#10 mounting holes

Key Operated Service Stops:  
#10 mounting holes

Approximate shipping weight - 5 lbs  
Warranty - 2 years parts

Solid heavy duty cast brass

#### Commercial Quality Features

- Foot operated valve
- For use with spout bases
- Self-closing valves
- Color indexed pedals
- Dual pedal operation

#### SPECIFICATIONS:

Dual extended foot pedal to be Encore KL24-1302. Valve to be constructed of polished chrome plated brass with total lead content less than 0.25% by weighted average. Valve is designed for wall mounting and shall be self-closing and replaceable. High strength extended aluminum foot pedals have color-coded indicators for hot and cold. Pedals have a hold-up position for floor cleaning and adjustment screw for positioning.

**COMPLIES WITH:**  
THE FEDERAL "REDUCTION OF LEAD  
IN DRINKING WATER ACT" –  
2011 – US SENATE BILL NO. S.3874

