

SHELVING

ALUMINUM ADJUSTABLE SHELVING

KELMAX by
SPG



ITEM # _____ MODEL # _____ QTY: _____


PROJECT: _____

OPTIONS: ☐ YES _____ ☐ NO _____



Standard Features & Benefits

- ◆ Custom aluminum shelving unit with adjustable and interchangeable shelves allow different style shelves within the same unit
- ◆ Choose between Channel, Tubular, T-Bar and Solid shelves
- ◆ Stainless Steel 3/8" set screws securely hold shelves in place
- ◆ Reinforced shelves with marine edges prevents contamination to shelves below
- ◆ Casters available to make unit mobile
- ◆ Heavy all aluminum posts are capped at each end
- ◆ Lifetime guaranteed against rust
- ◆ Load capacity per shelf:
 - Channel – 2,100 lbs.
 - Tubular – 2,000 lbs.
 - T-Bar – 1,500 lbs.
 - Solid – 900 lbs.



Channel Shelf
AACH



Tubular Shelf
AAS



T-Bar Shelf
AATB



Solid Shelf
AASR

For SPG's complete product menu,
visit www.spgusa.com or call 877.503.4SPG (4774)

EXPECT MORE
SPG
STORAGE PRODUCTS GROUP

SHELVING

ALUMINUM ADJUSTABLE SHELVING

Specifications

SOLID (AASR): Shelves constructed of .063 aluminum and bent down 90 degrees on all sides for rigidity. Reinforced with 1-1/4" square aluminum tube for additional load capacity.

CHANNEL (AACH): Shelves constructed of 1-1/2" x 1-3/4" all welded .072 aluminum tubing. Frame center shelf consists of 4" x 1.4" x .080" aluminum cross pieces. Cross piece channels include reinforced leg to increase load capacity (two channels for 18" wide, three channels for 24" wide, four channels for 30" wide shelves).

T-BAR (AATB): Constructed of 1-1/2" x 1-3/4" all welded .072 aluminum wall tubing frame with T-Bar cross pieces. Cross pieces constructed of .080 aluminum and measure 2" apart with minimum 1-1/2" wide thickness.

TUBULAR (AAS): Constructed of 1-1/2" x 1-3/4" all welded .072 aluminum wall tubing, spaced approximately 4-1/2" on center.

Shelving Type	Description	Application
Channel	4" wide channels	Provides extra strength for large or small items. Allows for air circulation.
Tubular	4 1/2" spacing between vertical tubes	For storage of cases or large boxes.
T - Bar	2" spacing between bars	For storage that requires perpendicular support
Solid	Reinforced tubing under the skin	For storage of small items. Helps contain spills.



Shelves

Solid Shelf Model No.	Tubular Shelf Model No.	T-Bar Shelf Model No.	Channel Shelf Model No.	L x W		Weight	
				(In.)	(mm.)	(Lbs.)	(Kg.)
18" Wide Shelves							
AASR1836	AAS1836	AATB1836	AACH1836	36 x 18	914 x 457	8	4
AASR1848	AAS1848	AATB1848	AACH1848	48 x 18	1219 x 457	11	5
AASR1860	AAS1860	AATB1860	AACH1860	60 x 18	1524 x 457	13	6
20" Wide Shelves							
AASR2036	AAS2036	AATB2036	AACH2036	42 x 20	1067 x 508	9	4
AASR2048	AAS2048	AATB2048	AACH2048	54 x 20	1372 x 508	12	5
AASR2060	AAS2060	AATB2060	AACH2060	72 x 20	1829 x 508	18	8
24" Wide Shelves							
AASR2436	AAS2436	AATB2436	AACH2436	36 x 24	914 x 610	9	4
AASR2448	AAS2448	AATB2448	AACH2448	48 x 24	1219 x 610	13	6
AASR2460	AAS2460	AATB2460	AACH2460	60 x 24	1524 x 610	15	7
AASR2472	AAS2472	AATB2472	AACH2472	72 x 24	1829 x 610	18	8
30" Wide Shelves							
—	AAS3036	—	AACH3036	36 x 30	914 x 762	19	9
—	AAS3048	—	AACH3048	48 x 30	1219 x 762	21	10

Posts

Model No.	Height		Weight	
	(In.)	(mm.)	(Lbs.)	(Kg.)
Poles				
AAP12	12	305	1	0.5
AAP48	48	1219	3	1.5
AAP54	54	1372	3	1.5
AAP68	68	1727	3 1/2	2
AAP76	76	1930	4	2
AAP84	84	2134	5	2.5

AMCO • Freestyle • ISS • Kelmax • LPI • Universal Stainless • Gillis-Jarke

SPG International, LLC
11230 Harland Drive NE
Covington, GA 30014
877-503-4SPG (4774)

www.spgusa.com

The best names in the business
all have one thing in common.

EXPECT MORE
SPG
STORAGE PRODUCTS GROUP