



AMERICAN RANGE

A **HATCO** COMPANY

Project _____

Item # _____

Quantity _____

36" RAISED GRIDDLE RANGES

GAS TYPE: ☐ NATURAL ☐ LP



☐ AR-4B-12RG

STANDARD FEATURES

- Commercial gas range 36" wide and 32 1/2" depth
- Cooking height 36" and 44"
- Stainless steel sides, front, and 6" deep front landing ledge
- Adjustable steel legs (Casters optional)
- Choose: 6" high stainless steel stub back, high riser, or high riser with shelf at no charge
- Base options: Standard, convection, or storage base
- Two year limited warranty, parts, and labor

OPEN BURNERS *(Installed on the left side of range)*

- 12" x 12" cast-iron top grates
- 32,000 BTU/hr. lift-off open burners
- Removable full width drip pan under burner

STANDARD OVEN *(Two Standard 26 1/2" Ovens)*

- Steel oven burner rated at 35,000 BTU/hr.
- Oven dimensions: 26 1/2"W x 22 1/2"D x 13 1/2"H
- Thermostat ranging from 250°F to 500°F (121°C to 260°C)
- Oven Door: Spring assisted, counterweight door
- Two chrome plated oven racks (Additional racks optional)
- Two fixed rack positions
- Porcelain enamel oven interior for easy cleaning
- 100% safety gas shut off

CONVECTION OVEN *(In place of standard oven)*

- Steel oven burner rated at 30,000 BTU/hr.
- Convection oven fan improves heat transfer for a faster cook time
- Thermostat ranging from 250°F to 500°F (121°C to 260°C)
- Two chrome plated oven racks (Additional racks optional)
- Chrome rack guides with five tray positions

RAISED GRIDDLES *(Installed on right side of range)*

- 3/4" thick steel griddle plate
- 3" wide grease collector
- One burner every 12", rated at 20,000 BTU/hr.
- Stainless steel pilot for each burner for automatic ignition
- Manual control valve for each burner

AVAILABLE OPTIONS

- Swivel Casters (Set of four – Two with front brakes)
- Storage Cabinet Base (In place of standard oven)



Model Shown AR-6B-24RG

Shown with optional casters

DESCRIPTION


American Range, restaurant range size 36" x 32-1/2" x 56" Stainless steel front, sides, backriser, shelf and 6" adjustable legs. Removable full width drip pan. Choose a combo 32,000 BTU/hr. open burners with no-clog lift-off burner heads along with 20,000 BTU/hr. per 12" section raised griddle with 3/4" plate. Heavy-duty cast iron grates, 12" x 12". Burner knobs are cool to the touch, high temperature material. Two ovens: 35,000 BTU/hr. standard oven, 30,000 BTU/hr. for convection. With porcelain interior and inside door panel, oven interior measures 26-1/2"W x 22-1/2"D x 13-1/2"H. Oven thermostat adjusts from 250°F to 500°F. All ovens supplied with two racks. Oven door with a spring assisted, counterweight mechanism requiring no adjustment. Rear gas connection and pressure regulator.




AMERICAN RANGE

A **HATCO** COMPANY


36" RAISED GRIDDLE RANGES



Front Oven Base



Side Standard Oven



Side Convection Oven

TOP	MODEL	Shipping Weight*			
		BTU/hr.	(KW)	LBS	(KG)
	AR-4B-12RG	183,000	(54)	425	(193)
	AR-4B-12RG-C	178,000	(51)	505	(229)
	AR-4B-12RG-SB	148,000	(44)	355	(161)

“C” = Convection Oven, “SB” = Storage Base, “RG” = Raised Griddle Top.
Raised Griddle on the right, storage base on the right.

Combo base options available – choose standard, convection, or storage base, contact the factory.

Specify type of gas and altitude if over 2000 feet.

Please specify gas type when ordering.

COMBUSTIBLE WALL CLEARANCES:

For use only on non-combustible floors. Legs or casters are required, or 2" (51) overhang is required when curb mounted. Clearance from non-combustible walls is 0". When unit is placed next to combustible walls, clearances must exceed 12" (305) from sides, and 4" (102) from rear.

Commercial cooking equipment requires an adequate ventilation system. For additional information, refer to the National Fire Protection Association's standard.

NFPA96 "Vapor Removal from Cooking Equipment." (NOTE: For North America only)

CONVECTION OVEN ELECTRICAL		
VOLTAGE	PHASE	AMPS
120	1	4

15 amps three prong cord provided

MANIFOLD PRESSURE		
NATURAL GAS	PROPANE GAS	MANIFOLD SIZE
5.0" W.C.	10.0" W.C.	3/4" (19MM)

*Shipping weight includes packaging and is approximate.

