



	SDD-30-23	SDD-27-58	SDD-27-69	SDD-27-90
Doors	1	2	2	3
Exterior Dimensions (L x D x H)	23 ½ x 30 ¾ x 38 ¾	58 7/8 x 27 ¾ x 35 5/8	69 1/8 x 27 ¾ x 35 5/8	90 3/8 x 27 ¾ x 35 5/8
Capacity 1/2 Barrels	1	2	3	4
HP	1/6+	1/3+	1/3+	1/3+
Voltage	115/60/1	115/60/1	115/60/1	115/60/1
Amps	1.7	6.2	6.8	7.5
Nema Config	5-15P	5-15P	5-15P	5-15P
Crated/Uncrated Weight	187/165 lb	301/229 lb	339/257lb	420/319 lb

- Stainless steel tops with drain line and drip trays are standard
- Standard stainless steel floor and inner wall
- Space-saving side mounted evaporator optimizes interior cabinet space
- Cold air is directed into draft towers ensuring optimum beer dispensing
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- NSF-7 approved for packaged and bottled product
- LED lighting: Visibility of products, last longer and consume low energy
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Easily accessible condenser coil for cleaning and easy service access
- Designed to accommodate a variety of beer kegs
- Self –Closing/Lockable doors: Positive seal, self-closing door(s) to help conserve energy and security

* Specifications subject to change without notice

