

Stem Casters

- Use stem casters to add shelving mobility and increase efficiency
- Stem casters are load rated for 75 to 300 lbs
- Three caster styles available: swivel only, swivel with brake, and rigid
- Three types of tire treads available: Resilient Rubber, Polyurethane, and Conductive
 - Resilient casters are great for use on rough flooring as they are long lasting, quiet and inexpensive
 - Polyurethane casters are non-marking and prevent undue wear on carpets and floors. They are suited to demanding environments such as extreme temperatures and the presence of solvents or organic chemicals
 - Conductive casters are designed for dissipation of static charge build-up in computer, electronic or medical applications
- The forks of all stem casters are plated steel except for models CM6PS and CM6PSB which are stainless steel



Swivel Caster with brake



Swivel Caster

Swivel Model No.	Swivel With Brake Model No.	Rigid Model No.	Dia.		Face		Load Rating		Wheel Material	Weight	
			(In.)	(mm.)	In.	(mm.)	(Lbs.)	(Kg.)		(Lbs.)	(Kg.)
CM2M	N/A	N/A	2	51	$\frac{3}{4}$	19	75	34	Resilient	$\frac{1}{2}$	0.2
CM3M	CM3MB	N/A	3	76	$1\frac{1}{4}$	32	150	68	Resilient Rubber	$1\frac{1}{2}$	0.7
N/A	CM4PB	N/A	4	102	$1\frac{1}{4}$	32	200	91	Polyurethane	2	0.9
CM5M	CM5MB	CM5MR*	5	127	$1\frac{1}{4}$	32	200	91	Resilient Rubber	$2\frac{3}{4}$	1.2
CM5P	CM5PB	CM5PR*	5	127	$1\frac{1}{4}$	32	300	136	Polyurethane	3	1.4
CM5MC	CM5MCB	CM5MCR*	5	127	$1\frac{1}{4}$	32	200	91	Resilient	3	1.4

*Caster channel required. Order separately; see below.

Caster Channel

- Required on all round stem rigid casters to maintain aligned position of casters
- Order one caster channel for each pair of rigid casters
- Select caster channel length based on shelf width

Plating Plus™ Model No.	Fits Shelf Width (In.)	W x L (In.)	Weight (Lbs.) (Kg.)
		(mm.)	
CC18C	18	$2\frac{1}{4} \times 18\frac{3}{4}$	57 x 476 1.3 0.6
CC21C	21	$2\frac{1}{4} \times 21\frac{3}{4}$	57 x 553 1.5 0.7
CC24C	24	$2\frac{1}{4} \times 24\frac{3}{4}$	57 x 629 1.7 0.8

Donut Bumpers

- Donut bumpers help prevent wall damage
- Model DB5 rotates to reduce marking

Model No.	Dia.		Description
	(In.)	(mm.)	
DB4	$3\frac{1}{2}$	89	Non-Revolving
DB5	5	127	Revolving



DB4

Donut Bumpers