

Project: _____ Location: _____ Item #: _____ Quantity: _____

Standard Features

- Kettle System-Seamless deep-drawn 316 kettle liner (up to 40 gal, 304 liner for 40+ gallon) with an integrally formed radius lip, 304 stainless draw off tube and welds, 304 stainless 2" compression draw-off
- 304 stainless kettle jacket
- Kettle protection system— thermostat temperature control, 150°F - 260°F, pressure relief valve, air eliminator valve, pressure gauge, jacket-water fill, automatic low water cut off and indicator light, safety pilot control
- Full body insulation between kettle jacket and outer casing
- Electric ignition, 120V standard
- 304 stainless outer casing seam welded to radius lip
- 304 stainless, seam welded control console
- 304 stainless lift off cover on 15-30 gallon
- 304 stainless, one piece, domed cover, actuator-assisted on 40-100 gallon
- Perforated disc strainer, 1/4" holes
- Adjustable bullet feet

Optional Features

- Single or dual faucet with bracket & 12" or 18" swing nozzle*
- 60" flexible spray hose assembly (vinyl or stainless) for dual or single faucet*
- Faucet bracket (ALFBST)
- Riser for table mounted fill faucet (ALRISER)
- Automatic water filling meter (ALAC-WS)
- Mixer/agitator, two speed (Call for pricing)
- Correctional Package*
- Adjustable flanged feet (ALFF-200)
- 316 Liner for 40+ Gallon (AL316LNR)

* Call AccuTemp for additional information

Electrical Options

120V, 208V, 240V

Short Spec

AccuTemp Edges Series gas powered, 2/3 jacketed, non-tilting floor kettle, low rim model ALLGB-XXF (15-100 gallon capacity). Seamless deep-drawn 316 kettle liner (up to 40 gal, 304 liner for 40+ gallon) with integrally formed radius lip and 304 stainless steel kettle jacket. 2" compression draw-off valve that includes a perforated disc strainer (1/4" holes), pressure relief valve, air eliminator valve, pressure gauge, jacket-water fill valve, automatic low water cut off and indicator light. 304 stainless domed cover with spring assisted (40-100 gallon units). Seam welded control console with thermostat temperature control, 150°F to 260°F (65°C to 126°C). Adjustable bullet feet.

Other Approvals

GAS-FIRED



Accessories

- Care Kit (ALKCK-L)
- Electric timer with buzzer (ALAT)
- Gas quick disconnect 1/2"*
- Flexible gas hose 3/4" x 60" (ALTQDH)
- Draw off drain hose (ALDIH)
- Disc strainer; solid or perforated, 1/8" or 1/4"*
- Measuring strip (ALMS)
- Lift-off or two piece hinged*
- One piece actuator-assisted lid, 15-30 gal. (ALACT-M)
- Single basket 20-40 gal. (ALSBI-M)
- Tri-basket insert (ALTBI-S)
- Nylon bag insert with spreader ring (ALNBI)
- 3" draw off valve optional

* Call AccuTemp for additional information



Model ALLGB-40F shown with included tangent draw off valve and lid

INSULATED SELF-CONTAINED KETTLE- ALLGB-F

15-100 GALLON CAPACITY—Gas, 2/3 Jacketed Low Rim
Insulated for Safety[™] Deep Drawn Construction
Non-Tilting, Floor Mounted. Made in USA

LOW-RIM [™] MODEL ALLGB-F DIMENSIONS										
Gal.	A	B	C*	D	E	F	J*	S*	V	W
15	22.0	12.9	29.0	24.1	12.9	34.4	61.0	17.2	6.8	16.2
20	23.0	15.0	31.6	24.6	13.4	35.4	64.6	17.7	7.1	16.5
25	25.5	15.5	32.8	25.8	14.6	37.1	68.3	18.9	8.0	17.4
30	25.5	18.0	35.1	25.8	14.6	37.1	70.6	18.9	8.0	17.4
40	29.5	18.5	35.0	27.8	16.6	41.1	74.5	20.9	9.4	18.8

Gal.	BTU RATING		Natural	Propane	Electrical
	Natural	Propane			
15	63,200	59,600	Supply Piping: 1/2" IPS	Supply Piping: 1/2" IPS	120 volt (standard) 208/240 volt (optional) 50/60 Hz 1 Phase 1 Amp
20	66,700	67,800			
25	79,900	83,100			
30	79,900	83,100	Supply Piping: 3/4" IPS	Supply Piping: 3/4" IPS	
40	106,800	108,500			
60	131,400	131,100			
80	154,800	149,200	Supply Pressure: 5-7" W.C. (nominal)	Supply Pressure: 12-14" W.C. (nominal)	
100	154,800	149,200			
			Outlet Pressure Factory Setting: 3.5" W.C.	Outlet Pressure Factory Setting: 10.0" W.C.	

DRAWING REPRESENTS 40 GALLON MODEL

