




Rolled Rim Edge  
For Additional Strength

Item #: \_\_\_\_\_ Qty #: \_\_\_\_\_  
Model #: \_\_\_\_\_  
Project #: \_\_\_\_\_



Fabricated Bowls are  
Welded Together at  
the Seams

#### FEATURES:

8-1/2" Backsplash has tile edge for ease of installation.  
Sink bowls have 3/4" coved corners and meet NSF requirements.  
Rolled Rim Edge for additional strength.  
Adjustable front and side cross-bracing.  
Three 20" x 28" x 14" sink bowls.  
Two 24" Drainboards.

#### CONSTRUCTION:

All TIG welded.  
Welded areas blended to match adjacent surfaces and to a satin finish.  
Gussets welded to a die-formed reinforced plate.

#### MATERIAL:

2 "H" leg assemblies and 1 single leg.  
Legs are 1 5/8" diameter stainless steel with 1" adjustable stainless steel bullet feet.  
Entire unit is 16 gauge 304 stainless steel.  
Gussets - stainless steel.

#### MECHANICAL:

- Supply is 1/2" IPS hot & cold.
- 2 Sets of Faucet holes on 8" centers.
- Faucets are not included **(see accessories)**.
- Waste drains are 1 1/2" IPS S/S basket type, located in center of sink bowl, and are included

Model #	Length L	Width W	Bowl Size A & B	# of Drbds.	Drbd. Location	Approx. Wt.
FC3M-2028-24RLX	112"	33 3/4"	20" x 28"	2	L&R	200 lbs.

ACCESSORIES	Model #	Qty
DRAINS		
FAUCETS		

# DIMENSIONS and SPECIFICATIONS

TOL Overall:  $\pm .500"$   
Interior:  $\pm .250"$

ALL DIMENSIONS ARE TYPICAL

