# U.S. Range

## Summit Series Electric Convection Oven

Project
Item
Quantity
. ,
CSI Section 11400
Approved
Date

#### Models

- SUME-100
- SUME-200



Model SUME-100

#### Standard Features

- Solid-State control with electromechanic timer
- Two-speed fan control (high, low) with 0.6 HP fan motor
- Total of 10.4 kW loading per oven cavity
- · Natural or propane gas
- Stainless steel front, sides, top, and legs
- 60/40 dependent door design with double pane thermal window in lefthand door and interior lighting
- Porcelain enameled oven interior with coved corners
- Five chrome plated ovens racks on 13-position rack guides
- Full length, stainless steel positive door closure
- Double-deck models available, 200 series models
- One-year limited parts and labor warranty (USA and Canada only)
- Five-year limited door warranty, excluding window (USA and Canada only)

# Options & Accessories

- · Stainless steel solid doors
- · Extra oven racks
- Four swivel casters w/ front brakes
- Four low-profile casters w/ front brakes (double ovens only)
- Open base with rack guides and shelf (stainless steel)
- 460 volt, three-phase
- Back enclosure (stainless steel)
- Removable stainless steel drip pan

#### Specifications

U.S. Range Summit full-size standard-depth, electric convection oven.

10.4 kW  $\!\!\!/$  cavity, 0.6 HP fan motor with two-speed fan speed.

Solid-State control with 60-minute timer.

Porcelain enameled oven interior with coved corners, five oven racks and 13-position rack guides.

All model interiors are 29" (736mm) W by 24" (610mm) H, depth is 24" (610mm)

Stainless steel front, sides, top, and legs.

60/40 dependent door design with double pane thermal windows, and interior lighting.

200 Models are double-deck units.

Specify voltage if other than 115 volt, 60 Hz,1 phase. UL, CUL Classified and NSF Listed.

Note: Ovens supplied with casters must be installed with an approved restraining device.









Garland Commercial Ranges Ltd. 1177 Kamato Road, Mississauga, Ontario L4W 1X4 CANADA General Inquires 1-905-624-0260 USA Sales, Parts and Service 1-800-424-2411 Canadian Sales 1-888-442-7526 Canada or USA Parts/Service 1-800-427-6668


www.garland-group.com 8113 09/24



## U.S. Range







This product is not approved for residential use. Many local codes exist and it is the responsibility of the owner and installer to comply with those codes.

Note: Installation clearance reductions are applicable only where local codes permit.

Model	Int. Dimensions :In (mm)				Ext. Dimensions: In	Ship Wt	Ship Dim.	
Wiouei	W	Н	D	W	Н	D (w/motor)	Lbs/kg	Cubic Ft.
SUME-100	29 (736)	24 (610)	24 (610)	38 (965)	57-1/2 (1461)	41-1/4 (1048)	515/230	64
SUME-200	29(736)	24(610)	24(610)	38(965)	70-1/2 (1791)**	41-1/4 (1048)	1030/465	128

<sup>\*\*</sup> Height with or without with standard casters. Height with low profile casters (double-deck) is 68-1/2" (1740mm).

Model	Tota kW	Nominal Amperes Per Line, (includes 0.6 HP fan motor)										
		208V/1Ph	240V/IPh	208V/3Ph		240V/3Ph			460V/3Ph			
				х	Y	z	х	Y	z	х	Y	Z
Single-Deck	10.4	50	43	30	30	28	26	26	24	14	14	13
Double-Deck* each oven	10.4	50	43	30	30	28	26	26	24	14	14	13

<sup>\*</sup> Double-deck models require individual power supply connections

Installation Notes:									
Combustible & Non-Combustible Wall Clearances:									
	wan clearances:								
Sides *1" (25mm) Back 3" (76mm)									
*Note: Installations beside units with high heat sources it is recommended to leave 6" (152mm) on the right side of oven. Refer to the installation manual for more detail.									
	Entry Clearances: In (mm)								
Crated	Crated 47" (1194mm)		32-1/2 (826mm)						

#### Notes:

Electrical specifications include motor requirements. 0.6, HP, 2-speed motor: 1725/1140 rpm, (60Hz). Please specify electrical characteristics when ordering.

Garland/US Range reserves the right to make changes to the design or specifications without prior notice.



