



TS C1 STONEBELT HIGH TEMP ELECTRIC CONVEYOR OVEN

SERIES: CONVEYOR OVEN



FEATURES

- Bake up to **60 New York style (20") pizzas or 385 Neapolitan (12") pizzas per hour**
- **31 1/4" wide** refractory stone belt baking surface (left to right motion)
- Max baking temperature of **842°F**
- 3.5" capacitive touch screen control stores up to 25 different custom recipes
- Stainless steel sheathed heating elements with mesh protection for humidity control
- Independent control of top and bottom heating elements with continuous PID
- Adjustable conveyor speed; set 30 second to 6.5 minute bake cycle
- Smart encoder self-corrects desired conveyor speed via real-time feedback
- Permanent magnet DC motor for consistent conveyor torque
- Authentic Italian-made refractory oven floor slats for enhanced baking and easy replacement
- Sliding removable crumb tray on each end for baking debris collection
- Inlet and outlet pizza-catch diverter extensions (removable) included as standard
- Adjustable height inlet and outlet shutter oven doors
- Stainless steel stand with locking 5" casters

TSC-E-1
*TS C StoneBelt Electric
Conveyor Oven,
1 Oven Chamber,
Fixed Control Panel, Stand*

JOB NAME:

REF INVOICE #:

STAND ☐ YES ☐ NO


ELECTRICAL (3-Ph): ☐ 208V ☐ 230V

REMOTE MOUNT
CONTROL PANEL: ☐ YES ☐ NO

** Made in Italy, learn more at
www.fierogroup.com.*

OPTIONAL

- Stack additional chambers at any time* (maximum 3 conveyor ovens tall)
- See TS*-E-2 and TS*-E-3 configurations
- Requires TS Upgrade Package
- Remote mount oven touch screen control panel configuration
- Replaces the standard fixed controls with a modular control box for mounting on a nearby wall or other convenient location (wired via 10 foot comm. cable)
- Electrical cabinet reduced in height to allow pizza loading from front or back of oven (allowing reversed conveyor motion)
- 208V 3-Phase power supply standard
- 230V 3-Phase available to order



HOURLY PIZZA CAPACITY

	90 second Neapolitan	4 minute New York
10" PIZZAS:	553	246
12" PIZZAS:	384	171
14" PIZZAS:	282	125
16" PIZZAS:		96
18" PIZZAS:		76
20" PIZZAS:		61

BAKING CHAMBER

TOTAL WIDTH:	31.25"
TOTAL LENGTH:	85.75"
CHAMBER SIZE:	31.25" X 59"
OPENING:	31.25" X 3.3"
HEIGHT:	3.3"
TOTAL BAKING SURFACE	18.6 FT ²
QUANTITY:	1

OVEN PERFORMANCE

TEMPERATURE RANGE:	212° – 842° F
CONVEYOR BAKE CYCLE SPEED RANGE:	30 SEC- 6.5 MIN
DAILY PREHEAT TIME:	45 MIN
PREHEAT TIME FROM COLD:	45 MIN
FUEL POWER:	ELECTRIC

ADDITIONAL DIMS

* REMOVABLE PIZZA OUTLET DIVERTER:	7"
* REMOVABLE PIZZA INLET EXTENSION:	16"
** ADJUSTABLE OVEN CHAMBER SHUTTER HEIGHT:	MIN 0.3" MAX 3.3"
GROUND TO BAKING SURFACE:	41.25"
REFRACTORY SLAT WIDTH:	1.8"

FIERO GROUP
601 N Main St, Brewster, NY 10509
Email: info@fierogroup.com
www.fierogroup.com

844-OVEN-INC (844-623-6462)
Toll-free in USA
(Hablamos Español,
Falamos Português)

Listed to: ANSI/UL 197 &
CAN/CSA-C22.2 No. 109 & NSF/ANSI-4
Commercial Cooking Appliance
Electric Baking Oven





TS C1 STONEBELT HIGH TEMP ELECTRIC CONVEYOR OVEN

SERIES: CONVEYOR OVEN




Approved by the
Association of Neapolitan
Pizzaiuoli of America

TSC-E-1 – STANDARD MODEL, 1 CHAMBER, FIXED CONTROL PANEL

WEIGHT:

1031 LB



VENTILATION

Install per NFPA 96 under a commercial kitchen hood that meets local requirements.

REQUIRED AIRFLOW 700 CFM

CLEARANCES

Recommended working clearance at conveyor inlet/outlet of 40".

Do not install oven against walls or heat sources. Do not block/restrict oven vents.

MIN. REQUIRED CLEARANCE: 8" (20 cm)

ELECTRICAL REQUIREMENTS

VOLTAGE	PHASE	FREQ.	MAX POWER	MED. POWER	FULL LOAD AMPERAGE	ELECTRIC PLUG TYPE
208 V	3 Ph	60 Hz	35 Kw	17 Kw	98 Amp	NOT SUPPLIED*
ELECTRICAL CONNECTION NOTES		Requires 3-phase electrical connection to L1, L2, L3 and Ground screw-terminal blocks located in electrical cabinet*. Pre-installed cable gland provided.				
SUPPLY CONNECTION		3-Phase Delta (3-pole 4-wire) connection				
CABLE CONNECTION		Power supply cable not supplied. Use appropriate cable/insulation per NFPA 70/NEC for the calculated rating				
MINIMUM CABLE GAUGE		4 AWG; Copper cables only, consult NEC for appropriate gauge				
MAXIMUM FUSE SIZE		120 A				
- Oven may be special ordered with 230V connection						

SHIPPING SPECS

MIN. FORKLIFT WEIGHT RATING:	1500 LB
SHIPPING DIMENSIONS:	59"W 102"D 28"H
SHIPPING WEIGHT:	1213 LB
SHIPPING VOLUME:	130 FT ³
Ships palletized with carton cover. Oven stand ships disassembled.	

1 year limited warranty.
See warranty document for details.

FIERO GROUP
601 N Main St, Brewster, NY 10509
Email: info@fierogroup.com
www.fierogroup.com

844-OVEN-INC (844-623-6462)
Toll-free in USA
(Hablamos Español,
Falamos Português)

Listed to: ANSI/UL 197 &
CAN/CSA-C22.2 No. 109 & NSF/ANSI-4
Commercial Cooking Appliance
Electric Baking Oven

