

Project	
Item #	
Ouantity	

STOCK POTS

GAS TYPE:

NATURAL

LP



ARSP-18 ARSP-18-2 ARSP-J

SPSH-18 SPSH-18-2

STANDARD FEATURES

- · ARSP models are 24" in height
- · SPSH models are 18" in height
- · Stainless steel front and sides
- SP model- Cast iron 3-ring burner 90,000 BTU/hr.
- Dual control valves, one for inner and middle rings, second for the outer ring
- ARSP-J, model with 23 tip jet burner 24" height
- J model Jet burner with 125,000 BTU/hr.
- · J model Single control valve with lever
- Stainless steel pilots for instant ignition
- Full-width removable crumb tray for easy cleaning
- · Heavy gauge construction
- Chrome plated 6" steel legs, with 3" adjustable bullet feet
- · Two year limited warranty, parts, and labor

OPTIONAL FEATURES

• 6" casters



Model Shown ARSP-18



Model Shown SPSH-18











STOCK POTS


3-RING DUAL CONTROL BURNER








23 TIP JET BURNER













SPSH-18









SPSH-18-2





TOP



SHIPPING WEIGHT*

ARSP MODEL	BURNERS	WIDTH (MM)	DEPTH (MM)	HEIGHT (MM)	BTU/hr.	(KW)	LBS	(KG)
ARSP-18	3-RING	18" (457)	21" (533)	24" (610)	90,000	(26)	134	(61)
ARSP-18-2	3-RING	18" (457)	42" (533)	24" (610)	180,000	(52)	235	(107)
SPSH MODEL	BURNERS	WIDTH (MM)	DEPTH (MM)	HEIGHT (MM)	BTU/hr.	(KW)	LBS	(KG)
SPSH-18	3-RING	18" (457)	21" (533)	18" (457)	90,000	(26)	130	(59)
SPSH-18-2	3-RING	18" (457)	42" (533)	18" (457)	180,000	(53)	230	(104)
ARSP-J MODEL	BURNERS	WIDTH (MM)	DEPTH (MM)	HEIGHT (MM)	BTU/hr.	(KW)	LBS	(KG)
ARSP-J	JET	18" (457)	21" (533)	24" (610)	125,000	(26)	134	(61)

COMBUSTIBLE WALL CLEARANCES:

- Specify type of gas and overhang is required when curb mounts altitude if over 2000 feet.

 (205) from sides and 4! (102) from repr
- Please specify gas type when ordering.

*Shipping weight includes packaging and is approximate.

NATURAL GAS	MANIFOLD PRESSU PROPANE GAS	re Manifold Size
5.0" W.C.	10.0" W.C.	3/4" (19MM)

For use only on non-combustible floors. Legs or casters are required, or 2" (51) overhang is required when curb mounted. Clearance from non-combustible walls is 0". When unit is placed next to combustible walls, clearances must exceed 12" (305) from sides, and 4" (102) from rear.

Commercial cooking equipment requires an adequate ventilation system. For additional information, refer to the National Fire Protection Association's standard.

NFPA96 "Vapor Removal from Cooking Equipment." (NOTE: For North America only)

American Range is a quality manufacturer of commercial cooking equipment. Because of continuing product improvements these specifications are subject to change without prior notice.





