

Stainless Steel Queen Mary

Standard Features & Benefits

- ◆ All welded units to meet the toughest demands
- ◆ Reinforced shelves can handle up to 1500# load capacity per shelf - 16 gauge shelf - 1 1/4" tubing on uprights and bottom frame
- ◆ Shelves standard with 3 lips up one down or optional all flat with marine edges
- ◆ Full wrap around bumper
- ◆ 8" x 2" Heavy duty polyurethane plate casters, 2 swivel and 2 rigid, 2000 lbs. capacity
- ◆ QMSS3.5 allows storage of large items on bottom shelf, like chafing dishes up to 25" high, top shelves spaced 12" on centers
- ◆ Custom sizes available, *NSF Approved*



QMSS-3.5



QMSS-5

MODEL	# OF SHELVES	SHELF SPACING	LxDxH	WGT
SHELVES THREE SIDES UP, ONE DOWN				
QMSS-3	3	25	69.5x29x62	155
QMSS-3.5	3	25 BOTTOM SHELF, 12 TOP TWO	69.5x29x62	175
QMSS-4	4	16	69.5x29x62	175
QMSS-5	5	12	69.5x29x62	195
QMSS-6	6	9	69.5x29x62	205
ALL SHELVES FLAT				
QMSS-3/F	3	25	69.5x29x62	155
QMSS-3.5/F	3	25 BOTTOM SHELF, 12 TOP TWO	69.5x29x62	175
QMSS-4/F	4	16	69.5x29x62	175
QMSS-5/F	5	12	69.5x29x62	195
QMSS-6/F	6	9	69.5x29x62	205

Specifications:

CONSTRUCTION:

Constructed of 16 gauge 304 series stainless steel sheet, hemmed with three lips up and one lip down or four lips down with marine edges. Handles consists of 16 gauge 1 1/4" stainless steel tubing welded to the unit. Uprights and cross braces are 16 gauge 1 1/4" square stainless steel tubing welded to the base. Base of unit is 16 gauge 1 1/4" square stainless steel tubing with a continuous 1" bumper secured to the frame.

CASTERS:

Unit comes with standard 8" x 2" polyurethane casters, two swivel and two rigid, bolted to the frame.

Website: www.kelmax.com

Model:

- ☐ QMSS
☐ QMSS/F

Job Name: _____

Qty: _____

Item: _____

814 Jordan Lane, Decatur, GA 30033
 404-296-9080 1-800-810-9080 Fax: 404-296-3040

KELMAX
 Equipment