



Item: _____
Quantity: _____
Project: _____

Infrared Radiant Broiler

Royal Series

Models: ☐ RIB-24 ☐ RIB-36 ☐ RIB-48 ☐ RIB-60



RIB-36

Gas Type: ☐ Natural ☐ LP

Elevation (if above 2000 ft.): _____

Standard Features

- Full width, removable stainless steel crumb pan for easy cleaning
- Stainless steel sides, front valve cover and ledge
- Easily removable, heavy gauge welded stainless steel radiants protect from spills
- Heavy duty cast iron reversible top grates
- Easily removable independent firebox assembly
- Infrared burners rated at 35,000 BTU/hr each
- Individual burner control
- Standing pilots for instant safe ignition
- Stainless steel tubing for burners and pilots
- 4" high adjustable, heavy duty legs included


Options and Accessories

- ☐ Fish grate
 - ☐ Diamond grate
 - ☐ Stainless steel splash guard tapered to front
 - ☐ Stainless Steel Equipment Stand
 - ☐ Knock Down ☐ All Welded
- Size
- ☐ 24" ☐ 36" ☐ 48" ☐ 60" ☐ 72"
 - ☐ 5" swivel casters (set of four - 2 locking)
 - ☐ 5" swivel casters (set of six - 3 locking) (60" and 72" stands)

LIMITED WARRANTY, TWO YEAR PARTS AND ONE YEAR LABOR



Infrared Radiant Broiler



Model Number	Width (A)	Broiling Grid	Infrared Burners	Total BTU	Ship Weight
RIB-24	24"	21 1/2" x 20"	2	70,000	160 lbs.
RIB-36	36"	21 1/2" x 32"	3	105,000	204 lbs.
RIB-48	48"	21 1/2" x 44"	4	140,000	260 lbs.
RIB-60	60"	21 1/2" x 56"	5	175,000	325 lbs.

Notes:

- Each burner is rated at 30,000 BTU/hr

Gas Connection:

3/4" NPT on the right hand rear of the appliance.

The pressure regulator (supplied) is to be connected by the installer.

Specify type of gas and altitude, if over 2,000 feet, when ordering.

Gas Pressure:

5" W.C.	Natural Gas
10" W.C.	Propane

Clearances:

	Combustible	Non-Combustible
Rear	4"	0"
Sides	15"	0"

Due to continuing product development to ensure best possible performance, these specifications are subject to change without prior notification.

Royal Range of California, Inc.

3245 Corridor Dr. • Eastvale, CA 91752 • (800) 769-2414 • (951) 360-1600
Fax: (951) 360-7500 • www.royalranges.com • sales@royalranges.com