



Project _____
Item No. _____
Model No. _____
Quantity _____

CSI No. 114000

REACH-IN REFRIGERATOR - TWO SECTION



R-50-SS-2S-D
50" Wide, S/S Exterior and Interior

MODEL GUIDE

Model Number	Description
☐ R-50-SS-2S-D	50" Wide, S/S Exterior and Interior
☐ R-50-SA-2S-D	50" Wide, S/S Exterior, Aluminum Interior
☐ R-60-SS-2S-D	60" Wide, S/S Exterior and Interior
☐ R-60-SA-2S-D	60" Wide, S/S Exterior, Aluminum Interior
Options	Model Number Modification
☐ Remote Refrigeration	Add suffix "X" to model number
☐ Half Doors	Change "2S" to "4S"
☐ Pass-Thru	Add prefix "PT" to model number
☐ Narrow Depth	Change suffix "D" to "N"
☐ Glass Door	Change "2S" to "2G"

AGENCY APPROVALS:



Intertek



Intertek

STANDARD FEATURES:

Construction/Cabinet

- Exterior front and sides – heavy gauge stainless steel
- Exterior back and bottom – heavy gauge galvanized
- Stainless steel compressor housing
- Stainless steel front, door, and grille
- Heavy-duty 6" adjustable stainless steel legs
- Cabinet body is foamed-in-place minimum 2-1/2" thick polyurethane insulation
- Fully coved interior with welded radius corners for easy cleaning
- Interior LED lighting
- Stainless steel shelf clips and shelf standards
- Four adjustable chrome plated wire shelves per section

Doors

- Self-closing, lift off door hinges with stay-open feature at 120°
- Standard left door hinged left, right door hinged right (other configurations available)
- Full-length, one-piece recessed Unigrip™ door handle (solid door models)
- Heavy-duty, built-in security cylinder door lock (solid door models)
- Energy saving condensate heater around door opening
- Snap-in magnetic door gasket
- Impact-resistant PVC breaker strip

Refrigeration Package

- Expansion valve refrigeration system for superior recovery and temperature pulldown
- Low Pressure control – prevents compressor burnout in case of refrigerant loss
- Top-mounted compressor
- R-513a, low GWP refrigerant for superior temperature recovery and pulldown
- Hot gas condensate evaporator quickly dissipates condensation using zero additional energy
- Receiver tank and service valves – allows reuse of refrigerant and enables rapid pulldown during times of peak demand
- Integrated sight glass – allows technicians to easily detect leaks or moisture without tools

Control Systems & Warranty Coverage


- Digital temperature control – easily adjust setpoint between 35-40°F
- Master power switch
- One 9 foot electrical cord
- Warranty: 5 year compressor, 5 year parts, 1 year labor

OPTIONS & ACCESSORIES:

- ☐ Stainless steel back ___ top ___ bottom ___ (specify all that apply)
- ☐ Drawers in lieu of lower half door (requires half-door option)
- ☐ Additional chrome wire shelves (specify quantity) _____
- ☐ Stainless steel wire shelves in lieu of chrome shelves
- ☐ Tray slides (specify quantity)
"L" Type ___ Universal slides ___ "R" Type ___
- ☐ Digital temperature control & solenoid for remote models
- ☐ Refrigerant options for remote models-please specify refrigerant type
- ☐ Stainless steel curb base (specify 4" or 6" high)
- ☐ Temperature alarm
- ☐ 6" front locking casters in lieu of legs (no charge)
- ☐ 4" front locking casters in lieu of legs
- ☐ 6" seismic legs
- ☐ Correctional facilities package
- ☐ Top-mounted evaporator coil (std. depth units only)
- ☐ Water-cooled condensing unit
- ☐ 5" high top-mount (remote compressor models)



REACH-IN REFRIGERATOR - TWO SECTION



PRODUCT DATA	R-50 Series Standard Depth	R-50 Series Narrow Depth	R-60 Series Standard Depth	R-60 Series Narrow Depth
KEY DIMENSIONS				
Width (overall)	50.0"	50.0"	60.0"	60.0"
Depth (overall)	34.5"	28.0"	34.5"	28.0"
Depth Pass-Thru Models (overall)	36.5"	30.0"	36.5"	30.0"
Height (overall inc. legs)	84.0"	84.0"	84.0"	84.0"
Door Opening (net width)	18.25"	18.25"	23.25"	23.25"
Door Opening (net height)	57.25"	57.25"	57.25"	57.25"
Half Door Opening (net ht.)	26.75"	26.75"	26.75"	26.75"
CAPACITY				
Capacity (cu. ft.)	43	33	57	44
Number of Shelves	8	8	8	8
Shelf Area (sq. ft., including bottom)	39	29	48	36
ELECTRICAL				
Voltage (dedicated circuit required)	115	115	115	115
SOLID DOOR MODELS				
Amperage solid door models (self-contained)	11.1	11.1	12.9	11.1
Amperage solid door models (remote refrigeration)	8.4	8.4	9.2	8.4
BTU requirement*, remote (solid door models)	2590	2496	3190	2696
GLASS DOOR MODELS				
Amperage glass door models (self-contained)	12.9	12.1	12.9	12.1
Amperage glass door models (remote refrigeration)	9.2	8.4	9.2	8.4
BTU requirement*, remote (glass door models)	3943	3459	4124	3591
NEMA Plug Configuration	5-20 P	5-15 P	5-20 P	5-20 P
Horsepower (self-contained)	1/3	1/3	1/2	1/2
SHIPPING				
Ship Weight (lbs.)	640	530	810	650
Ship Volume, Standard Depth (cu. ft.)	135	118	160	140
Crated Dimensions (87"H)	56"W x 48"D	56"W x 42"D	66"W x 48"D	66"W x 42"D

*90°F ambient, 20°F evaporator, 20' max. line length

Data is for standard models; options may change specifications.

UTILITY REFRIGERATOR

12160 Sherman Way • North Hollywood, CA 91605

Telephone: (818) 764-6200 • Fax: (818) 764-6211

www.utilityrefrigerator.com

DUE TO CONTINUOUS PRODUCT IMPROVEMENTS, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

©/™/® Utility Refrigerator



WARNING - This product can expose you to chemicals including Di(2-ethylhexyl)phthalate (DEHP), which is [are] known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

UR-R2 | MU