



BAKERLUX

Countertop Convection Oven

MODEL: XAFT-03HS-TD

Heavy-Duty 3 Shelf Countertop Convection Oven with Digital Controls & Humidity



208-240
Volt

FEATURES

- Advanced airflow design & automatically reversible fan for even baking
- USB programming capability
- Digital programmable controls: Time, Temperature, Humidity
- Wi-Fi
- Data driven cooking
- Heat settings from 175°-500° F
- Saves up to 99 programs with graphic control panel
- Handles 3 half size sheet pans (not included)
- 3 wire shelves included
- Cooking chamber: 10-1/4" H x 19-1/4" W x 14" D (1.6 cu. ft.)
- 10 hour timer or continuous on
- Light flashes and unit beeps at end of cycle
- Heavy duty stainless steel construction
- Heavy duty door & hinge construction
- Extra large motor for long lasting use
- 2-5/8" between shelves

OPTIONAL ACCESSORIES:

- XAKPT-08HS-C Proofer
- XAKHT-HCHS Ventless Hood
- XWKQT-00HS-E Stacking Kit
- Stands: OST-34A-C, OST-34A-CS
- Heavy-Duty 2-Oven Stand: OV-HDS


- 1 fan; 3 fan speeds
- Interior LED light
- Auto shut off when door is opened
- Includes electro valve for direct plumbed water connection
- "Cool-touch" double wall glass door opens from top
- Stackable with optional XWKQT-00HS-E Stacking Kit
- NSF; MET to UL & CSA Standards/ listed by UNOX S.p.A.
- Energy Star rated
- Chef Support – via phone
- 3 year Limited Warranty (2 year on-site service & parts, 3rd year parts only)**
- **90 day warranty on light bulbs & gasket (not service center items); 30 days on glass; one year on motor
- 208-240 Volts / 3300 Watts / 14 Amps / Single Phase / 60Hz
- NEMA 6-20P Plug
- Freight class 200 NOTE: This model must ship by truck, not UPS



Incoming Water:

The bottom of the appliance contains 6.6 ft 7 in of pipe with a tee for connecting to the water supply (including mechanical filter and fitting (3/4") with non-return valve). A shut-off valve should be positioned between the water mains and the appliance.

We recommend that the end user have a standard machine filter when using a humidity hookup.



Model	Color	Volts	Watts	Amps	Unit Dimensions	Unit Wt.	Ship Wt.	Carton Dimensions	Cube	UPC#
XAFT-03HS-TD	Stainless	208-240	3300	14	w:23.6875", h:16", d:25.5"	85 lbs.	130* lbs.	w:42", h:23", d:48" *	26.8*	654796-55140-8

Made to Cadco Ltd. specifications by UNOX S.p.A., Italy

Cadco Model XAFT-03HS-TD = UNOX Model XAFT-03HS-ETDV-US

• NSF, MET to UL & CSA Standards

*includes dimensions & weight (approx. 40 lbs.) of shipping skid



www.cadco-ltd.com



860.738.2500



info@cadco-ltd.com