

FLOW RATES UP TO 123 GPM

CES 2900 SERIES

Single Tank Water Softener

- 2" porting
- Hardness removal up to 120,000 to 300,000 grains
- Flow rates up to 62 gallons per minute continuous
- Advanced NXT2 digital control and electronic meter
- Easily adjustable 5-cycle control

Designed for operations with high volume soft water usage:

- Cold water fed warewashing
- Laundry - linen & uniform
- Boiler scale control
- Water heater scale protection/reduction
- General housekeeping



Do you know what's in your water?

Determining the quality of your water is the first step to applying the correct water treatment. Hardness, chemicals, total dissolved solids and sediment can all impact your operation. We can analyze your water and your unique situation and recommend the right mix of products to meet your operation's usage requirements.

CES 2900DP Series

Duplex Progressive Flow Water Softener

- 2" porting
- Duplex Parallel twin tank configuration for continuous soft water supply and reduced salt usage
- Hardness removal up to 120,000 to 300,000 grains per tank
- Flow rates up to 123 gallons per minute continuous
- Advanced NXT2 digital control and electronic meter
- Easily adjustable 5-cycle control

Designed for operations with high volume soft water usage:

- Laundry - linen & uniform
- Boiler scale control
- Water heater scale protection/reduction
- Hospitality & grocery
- Cooling towers

SPECIFICATIONS

MODEL	PART NUMBER	TANK	RATED CAPACITY @15 LBS. SALT/CU. FT. (GRAINS)	SERVICE FLOW RATE		PIPE SIZE (IN)	RESIN VOLUME (FT ³) PER TANK	SYSTEM DIMENSIONS* W X D X H (INCHES)	BRINE TANK SALT CAPACITY (LBS)	SHIP WT (LBS)
				CONTINUOUS @ 15 PSI DP (GPM)	INTERMITTENT @ 25 PSI DP (GPM)					
CES-2900E-120	EV998422	Single	120,000	47	60	2	4	49 x 24 x 79	750	360
CES-2900E-150	EV998423	Single	150,000	53	69	2	5	52 x 24 x 82	750	460
CES-2900E-210	EV998424	Single	210,000	57	74	2	7	60 x 30 x 82	1200	630
CES-2900E-300	EV998425	Single	300,000	62	80	2	10	64 x 30 x 89	1200	920
CES-2900E-120-DP	EV998442	Twin	120,000	94	121	2	4	81 x 24 x 79	750	460
CES-2900E-150-DP	EV998443	Twin	150,000	106	137	2	5	92 x 24 x 82	750	880
CES-2900E-210-DP	EV998444	Twin	210,000	114	148	2	7	97 x 30 x 82	1200	1210
CES-2900E-300-DP	EV998445	Twin	300,000	123	159	2	10	105 x 30 x 89	1200	1750

*When determining system space requirements, refer to spec sheet for physical arrangement. Installations requiring re-arrangement of tanks, or separation of tanks, may need additional clearance.