


VOLUME BAGGING ICE DISPENSERS

- ♦ **SD SERIES** - DESIGNED FOR HEAVY DUTY USE BY VOLUME FEEDERS, HOTELS, VENDING OPERATIONS, INSTITUTIONS AND HOSPITALS.
- ♦ **AUTOMATIC** - ICE IS DISPENSED BY FOOT PEDAL CONTROL (AUTOMATIC TIMER CONTROL OPTIONAL).
- ♦ **DELIVERY SYSTEM** - STAINLESS STEEL DELIVERY AUGER DRIVEN BY A HEAVY DUTY GEAR MOTOR THROUGH A ROLLER CHAIN DRIVE SYSTEM. (SD-5000 HAS TWIN AUGERS WITH SEPERATE FOOT PEDALS).
- ♦ **AGITATION SYSTEM** - PUSHBUTTON ACTIVATED ALL STAINLESS STEEL AGITATORS ARE POWERED BY A SEPERATE GEAR MOTOR(S) THROUGH A CONNECTING ROLLER CHAIN DRIVE SYSTEM.
- ♦ **SERVICEABILITY** - THE ENTIRE UNIT IS SERVICEABLE FROM THE FRONT AND REAR. ALL SHAFTS CAN BE REMOVED FROM THE FRONT. THIS ELIMINATES SIDE CLEARANCE AND MINIMIZES SPACE REQUIRED FOR REAR CLEARANCE (12").

GENERAL SPECIFICATIONS

INTERIOR.....	WELDED ANGLE IRON FRAME. STAINLESS STEEL, TYPE 304, TANK, FULLY WELDED SEAMS.
EXTERIOR.....	POLISHED STAINLESS STEEL or STUCCO ALUMINUM. ALUMINUM BACK and GALVANIZED STEEL BOTTOM (STAINLESS STEEL OPTIONAL). TWO SECTION BODY OPTIONAL.
INSULATION.....	2" EXPANDED POLYSTYRENE.
DRAIN.....	1" MPT, CENTER BOTTOM.
LEGS.....	PAINTED PIPE (STAINLESS OPTIONAL) STAINLESS STEEL FEET.
DELIVERY SYSTEM.....	SPIRAL AUGER TYPE, STAINLESS STEEL CONSTRUCTION.
ELECTRICAL.....	208-230v/60hz/1ph (MODEL SD-5000 HAS TWO ELECTRIC BOXES (2) 3/4 HP GEAR MOTOR, 5.5 AMPS EACH, (MODELS SD-1400, SD-2000, and SD-2500). (3) 3/4 HP GEAR MOTOR, 5.5 AMPS EACH, (MODEL SD-3000). (4) 3/4 HP GEAR MOTOR, 5.5 AMPS EACH, (MODEL SD-5000).
OPTIONS.....	BAG BLOWER, PORTION TIMER, BAG TAPER, COIN OR TOKEN MECHANISM.



MODEL NUMBER	APPROX STORAGE (lbs.)	WIDTH (in.)	DEPTH* (in.)	HEIGHT (in.)
SD-1400	1400	60 1/4	54 1/4	78
SD-2000	2000	72 1/4	56 1/4	80
SD-2500	2500	72 1/4	56 1/4	90
SD-3000	2800	86 1/4	56 1/4	92
SD-5000	5000	140 1/4	56 1/4	90

Height includes 32" for stand which can be taller or shorter.

*For overall depth, add 16" for front nozzle and rear cover.

Allow 12" behind unit for servicing.

MGR EQUIPMENT CORP.

22 Gates Avenue, Inwood, New York 11096-1697

Phone: (516) 239-3030

Fax: (516) 239-3602

Toll Free: (800) 486-4647