



Project _____
Item No. _____
Model No. _____
Quantity _____

CSI No. 114000

ROLL-IN REFRIGERATOR "H" SERIES - FOR 72" HIGH CARTS



RIR-30-SS-15-H
30" Wide, One Narrow Door,
S/S Exterior and Interior

MODEL GUIDE

Model Number	Description
☐ RIR-30-SS-15-H	30" Wide, One Narrow Door, S/S Exterior and Interior
☐ RIR-37.5-SS-15-H	37.5" Wide, One Extra Wide Door, S/S Exterior and Interior
☐ RIR-60-SS-25-H	60" Wide, Two Narrow Doors, S/S Exterior and Interior
☐ RIR-68-SS-25-H	68" Wide, Two Doors, S/S Exterior and Interior
☐ RIR-75-SS-25-H	75" Wide, Two Extra Wide Doors, S/S Exterior and Interior
☐ RIR-90-SS-35-H	90" Wide, Three Narrow Doors, S/S Exterior and Interior
☐ RIR-100-SS-35-H	100" Wide, Three Doors, S/S Exterior and Interior
Options	Model Number Modification
☐ Remote Refrigeration	Add suffix "X" to model number
☐ Roll-Thru	Add prefix "RT" to model number
☐ Glass Door	Change "S" to "G"

AGENCY APPROVALS:



Intertek



Intertek

STANDARD FEATURES:

Construction/Cabinet

- Exterior front and sides – heavy gauge stainless steel
- Exterior back and bottom – heavy gauge galvanized
- Stainless steel compressor housing
- Stainless steel front, door, and grille
- Heavy-duty removable stainless steel cart ramp
- Cabinet body is foamed-in-place minimum 2-1/2" thick polyurethane insulation
- Fully coved interior with welded radius corners for easy cleaning
- Interior LED lighting

Doors

- Self-closing, lift off door hinges with stay-open feature at 120°
- Full-length, one-piece recessed Unigrip™ door handle (solid door models)
- Heavy-duty, built-in security cylinder door lock (solid door models)
- Energy saving condensate heater around door opening
- Snap-in magnetic door gasket
- Impact-resistant PVC breaker strip

Refrigeration Package

- Expansion valve refrigeration system for superior recovery and temperature pulldown
- Low pressure control – prevents compressor burnout in case of refrigerant loss
- Top-mounted compressor
- R-513a, low GWP refrigerant for superior temperature recovery and pulldown
- Hot gas condensate evaporator quickly dissipates condensation using zero additional energy
- Receiver tank and service valves – allows reuse of refrigerant and enables rapid pulldown during times of peak demand
- Integrated sight glass – allows technicians to easily detect leaks or moisture without tools

Control Systems & Warranty Coverage


- Digital temperature control – easily adjust setpoint between 35-40°F
- Master power switch
- One 9 foot electrical cord
- Warranty: 5 year compressor, 5 year parts, 1 year labor

OPTIONS & ACCESSORIES:

- ☐ Stainless steel back ___ top ___ bottom___ (specify all that apply)
- ☐ Digital temperature control & solenoid for remote models
- ☐ Refrigerant options for remote models-please specify refrigerant type
- ☐ Temperature alarm
- ☐ Correctional facilities package
- ☐ Water-cooled condensing unit
- ☐ Glass doors
- ☐ Double-deep configuration
- ☐ Shelving options
- ☐ Reach-in half doors on rear side of roll-thru model
- ☐ Quick disconnect condensing units (select models; contact factory for details)



ROLL-IN REFRIGERATOR "H" SERIES - FOR 72" HIGH CARTS



PRODUCT DATA	RIR-30	RIR-375	RIR-60	RIR-68	RIR-75	RIR-90	RIR-100
KEY DIMENSIONS							
Width (overall)	30.0"	37.5"	60.0"	68.0"	75.0"	90.0"	100.0"
Depth (overall)	34.5"	34.5"	34.5"	34.5"	34.5"	34.5"	34.5"
Depth Roll-Thru Models (overall)	36.5"	36.5"	36.5"	36.5"	36.5"	36.5"	36.5"
Height (overall)	90.5"	90.5"	90.5"	90.5"	90.5"	92.5"	92.5"
Maximum Cart Height	72.0"	72.0"	72.0"	72.0"	72.0"	72.0"	72.0"
Maximum Cart Width	23.0"	30.5"	23.0"	27.0"	30.5"	23.0"	27.0"
Maximum Cart Depth	29.0"	29.0"	29.0"	29.0"	29.0"	29.0"	29.0"
CAPACITY							
Capacity (cu. ft.)	28	36	62	71	79	96	108
ELECTRICAL							
Voltage (dedicated circuit required)	115	115	115	115	115	115	115
Amperage (self-contained)	9.4	9.6	10.3	10.5	11.3	20.4	20.7
Amperage (remote refrigeration)	6.0	6.2	7.8	7.8	8.8	10.3	10.6
BTU requirement*, remote							
NEMA Plug Configuration (self-contained only)	5-15P	5-15P	5-15P	5-15P	5-15P	NO CORD/PLUG	NO CORD/PLUG
Horsepower (self-contained)	1/3	1/3	1/2	1/2	1/2	3/4	3/4
SHIPPING							
Ship Weight (lbs.)	675	755	870	940	1100	1300	1450
Ship Volume, Standard Depth (cu. ft.)	99	116	182	204	223	267	278
Crated Dimensions	36"W x 48"D x 99" H	42"W x 48"D x 99" H	66"W x 48"D x 99" H	74"W x 48"D x 99" H	81"W x 48"D x 99" H	96"W x 48"D x 100" H	106"W x 48"D x 100" H

*90°F ambient, 20°F evaporator, 20' max. line length

Data is for standard models: options may change specifications.

UTILITY REFRIGERATOR

12160 Sherman Way • North Hollywood, CA 91605

Telephone: (818) 764-6200 • Fax: (818) 764-6211

www.utilityrefrigerator.com

DUE TO CONTINUOUS PRODUCT IMPROVEMENTS, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

©/™/® Utility Refrigerator



WARNING - This product can expose you to chemicals including Di(2-ethylhexyl)phthalate (DEHP), which is [are] known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

UR-RIRH | MU