



www.BakeMax.com

Project: _____

Item: _____

Qty: _____ Date: _____

BakeMax BMBPEB152 76" Electric Pizza Stone Deck Oven

BakeMax Pizza Ovens are reliable and versatile solutions designed for professional baking applications. Each oven chamber features refractory baking deck with an 8" deck height and independently controlled top and bottom heat for perfectly balanced results. This series is constructed with heavy duty angle iron frame, which is fully welded to allow for double stacking. Oven exteriors are all heavy-duty stainless steel and are fully insulated for cooler outer temperatures and consistent interior temperatures.



Features:

- Constructed of Hygienic & Easy-to-Clean Stainless-Steel, its Heavy-Duty Frame allows for Double Stacking
- Fully Insulated for cool outer temperatures and consistent interior temperatures
- Independently controlled top and bottom temperature control up to 752°F (400°C)
- Deck Height of 8" (203 mm)
- Spring-balanced, Fully Insulated Doors
- Three Refractory Baking Hearth Stones with dimensions of 20" Wide x 36" Deep
- Open door lies flush to hearth stone for easy loading and unloading
- Holds up to Fifteen 9" Pizzas at a time
- 2-Year Limited Warranty



Product Specifications:

- Product Dimensions (WDH): 76" x 46.13" x 49.12"
- Oven Inner Dimensions: 60" Wide x 36" Deep
- Product Weight: 1015 lbs.

Shipping Specifications:

- Shipping Dimensions (WDH): 78" x 51" x 33"
- Shipping Weight: 1169 lbs.

Electrical Specifications (Field Convertible):

- 208V / 36.25A / 13050W / 60Hz / 3 Ph
- 208V / 62.75A / 130050W / 60Hz / 1 Ph

TEMP
DISPLAY →

TOP
HEAT →

BOTTOM
HEAT →

LIGHTS →

ON/OFF
SWITCH →



*Due to continuous product improvement, specifications are subject to change without notice.

BakeMax® / Titan Ventures International Inc.

Warehouses:

20 Caribou St, Moncton, NB E1H 0P3

5705 Valley Belt Rd Independence, OH 44131

1201 E 27th Terrace Pittsburg, KS 66762

Toll Free: 1-800-565-BAKE (2253)

Phone: 506-858-8990

Fax: 506- 859-6929

Email: Sales@BakeMax.com