

Special features:

- **Low water consumption** of 71 gallons (268.8 liters) per hour, 0.29 gallons (1.11 liters) per rack.
- **NSF rated 243 racks per hour.**
- **Glass touch screen control panel** for fully automatic operation and advanced service diagnostics. Messages are displayed in plain text, with a selection of multiple languages including English, Spanish and French.
- **Built-in “smart” booster heater** ensures correct sanitizing temperature of 180°/82°C (incoming water temperature of 110°-140°F/43°- 60°C).
- **“Blue cues” color coding** of components to be touched during daily cleaning makes cleaning intuitive.
- **Modular construction** reduces lead times. Ships as a single unit.

Standard features:


- 3 drive speeds: Wash 243, 202 or 162 racks/hour.
- 304-series stainless steel construction.
- Uniquely-designed center-drive pawl system eliminates water spray blockage from below the rack, while providing reliable operation.
- Double-wall insulated construction on front, top and back to improve operator safety, conserve heating energy, and reduce noise and heat loss into the dishroom.
- Standard vent cowls with collars.
- Sealed, hinged access door(s) are field-reversible by an Authorized Service Agent.
- Stainless steel wash arms are optimally positioned and easily removable for cleaning. Wash arm end caps are cooler to the touch for safety. Nozzles are slotted and concave to minimize clogging.
- Powerful 3hp (2.2 kW) wash pump provides outstanding cleaning results. Pump motor is vertically-mounted for easy servicing.
- Detergent and rinse aid access ports.
- Low-level heater protection.
- Potential-free contacts for external vent fan control.

Specifications:

KA-76: 54" (1372 mm) compartment with wash and final rinse zones. 22" (559 mm) prewash section. Table-to-table length 76" (1,930 mm). Length with hoods 99-3/8" (2,530 mm).



Note: Tabling sold by other manufacturers.



KA-76

TABLE-TO-TABLE DIMENSIONS:
76"L x 76-1/8"H x 31-1/4"D
(1,930 mm x 1,934 mm x 795 mm).

DIMENSIONS WITH HOODS:
99-3/8"L x 76-1/8"H x 31-1/4"D
(2,530 mm x 1,934 mm x 795 mm).

Options:

- **Waste Air Heat Recovery System (WAHRS):** Requires incoming water temperature less than 110°F (43°C). Cold water supply or below 68°F (20°C) recommended.
- **Blower dryer** improves drying of dishes, glassware, crockery and silverware. Adds 23 5/8" (600mm) to machine length.
- **The industry's first 90° mechanical unloader/blower dryer module.**
- **90° mechanical loader and unloader (unhooded).**
- **Single point electrical connection** available. Contact factory for more information.
- **Water hammer arrestor.**
- **Machine separations** for ease of handling and installation, contact factory.
- **Contact factory for drawings** including options.

Accessories:

- Table limit switch.
- Drain water tempering kit.
- Open-ended sheet pan rack.
- Flanged feet.


This dishwasher is compliant with the Reduction of Lead in Drinking Water Act (2011) amendment to the Safe Drinking Water Act (SDWA).




KA-76, Left to right - electric heat

Review the Utility Connections and Technical Specifications pages for additional details.


- | | | | |
|------|--|------|--|
| 1.0 | Drain | 2.02 | Cold water connection
(with WAHRS option) |
| 2.0 | Warm water connection
(without WAHRS) | 3.0 | Electrical connections |
| 2.01 | Warm water connection
(with WAHRS) | 6.01 | Vent connection |
| | | 6.02 | Vent connection |



Front Elevation View



Side Elevation View





Plan View

KA-76, Right to left - electric heat

Review the Utility Connections and Technical Specifications pages for additional details.

- | | | | |
|------|---------------------------------------|------|---|
| 1.0 | Drain | 2.02 | Cold water connection (with WAHRS option) |
| 2.0 | Warm water connection (without WAHRS) | 3.0 | Electrical connections |
| 2.01 | Warm water connection (with WAHRS) | 6.01 | Vent connection |
| | | 6.02 | Vent connection |



KA-76 Utility Connections Detail Page

1.0 Drain

- Vertical, gravity-fed drain outlet (HDPE piping). 2" OD or 1½" pipe via no-hub required for connection.
- Connection pipe work and P-trap to be provided by others (HDPE piping).
- Additional piping to drain (if required) to be provided by others.
- Connection is 13" (330 mm) AFF.
- NOTE: Drain locations may vary.

2.0 Warm water connection (fill and rinse); machines without WAHRS option:

- ¾" NPT pipe connection.
- Temperature: 110° - 140°F (43° - 63°C).
- Initial fill: **KA-76** = 21.1 gallons (80 liters)
- Consumption = 71 gallons (268.8 liters) per hour.
- Recommended hardness = 1-3 grains/gallon.
- Connection = 11" (279 mm) AFF.

2.01 Warm water connection (fill and rinse); machines with WAHRS option:

- 1/2" NPT pipe connection.
- Temperature: 110° - 140°F (43° - 60°C).
- Initial fill: **KA-76** = 21.1 gallons (80 liters)
- Recommended hardness = 1-3 grains/gallon.
- Connection = 11" (279 mm) AFF.

2.02 Cold water connection (final rinse); machines with WAHRS option:

- 1/2" NPT pipe connection.
- Temperature as cold as available: 53° - 68°F (12° - 20°C) recommended.
- Consumption = 71 gallons (268.8 liters) per hour.
- Recommended hardness = 1-3 grains/gallon.
- Connection = 11" (279 mm) AFF.



Equipotential ground lug



3.0 Electrical connections

Values in Amps: 208V/60Hz/3Ph

Model	TB1	TB2	TB3	TB4	TOTAL
KA-76	57.3		50.0	3.9	111.2
Breaker	80.0		70.0	15.0	
<i>with dryer added</i>				16.2	123.5
Breaker				25.0	
<i>with WAHRS added</i>			70.0		131.2
Breaker			90.0		
<i>with both added</i>					143.5

Values in Amps: 230V/60Hz/3Ph

Model	TB1	TB2	TB3	TB4	TOTAL
KA-76	55.1		45.2	3.9	104.2
Breaker	70.0		60.0	15.0	
<i>with dryer added</i>				17.3	117.6
Breaker				25.0	
<i>with WAHRS added</i>			63.3		122.3
Breaker			80.0		
<i>with both added</i>					135.7

Values in Amps: 460V/60Hz/3Ph

Model	TB1	TB2	TB3	TB4	TOTAL
KA-76	29.9			22.6	52.5
Breaker	40.0			30.0	
<i>with dryer added</i>	39.3				61.9
Breaker	50.0				
<i>with WAHRS added</i>				31.6	61.5
Breaker				40.0	
<i>with both added</i>					70.9

Heat values in kW

Latent	Perceptible	Total
3.4	2.8	6.2



6.01 Load-end vent connection:

- See Detail View on Technical Specifications page
- 200 CFM [340 m³/hr]



6.01 Load-end vent connection with WAHRS option:

- See Detail View on Technical Specifications page
- 200 CFM [340 m³/hr]
- Connection must be corrosion-resistant and frost-free. In particular, provisions must be made to prevent air temperatures of 32°F (0°C) or colder from reaching the machine at any time. A provision for draining moisture from the waste air pipe (condensate return) is strongly recommended.

6.02 Unload vent connection:

- See Detail View on Technical Specifications page
- 400 CFM [680 m³/hr]

Note:

- Relative humidity: approximately 98%.
- Machine exhaust (pant leg connection) recommended as per values listed above.
- Machine exhaust hood connection (by others): recommended 100 CFM [170 m³/hr] per lineal foot of hood. Length of hood contingent on machine model and local site conditions at time of installation. MEIKO assumes no responsibility.
 - 18" hood overhang to front of machine.
 - 36" hood overhang on load and unload ends.

KA-76 Technical Specifications Detail Page

Specified dishwasher will be KA-76 high-temp rack conveyor. Low water consumption of 0.29 gallons/rack. NSF rated 243 racks/hour. Blue cues help operators locate important components for cleaning. Touchscreen control panel with advanced diagnostics. 3 conveyor speeds. Stainless steel construction with double wall insulation, plus a built-in booster heater. 20" chamber height accommodates standard-sized sheet pans with an open-ended dish rack. NSF/UL/ES rated.

Performance

Maximum rack capacity/hour	243/202/162
Water consumption (maximum)	71 gal/hr (268.8 liters)
Water consumption/rack	0.29 gal/rack (1.1 liters)

Venting data pant leg

Load end:	200 CFM/340m ³ /h
Unload end:	400 CFM/680m ³ /h
Total:	600 CFM /1,020m ³ /h
Relative humidity (approx.):	98%

Dimensions


KA-76 length, table-to-table	76" (1930 mm)
Length, blower dryer (option)	+ 23½" (600 mm)
Height	76⅞" (1934 mm)
Depth	31¼" (795 mm)
Clearance height inside wash chamber	20" (508 mm)

Recommended Pant Leg Connection

Machines that are not placed underneath a ventilation hood require "pant leg" ventilation ducts. To determine the dimensions of the duct, first determine how they will be installed.

Duct sleeved inside collar **(recommended)**:


4" W x 16" D (102 x 406 mm) **inside dimensions**



Component data

Wash pump motor	3.0 hp (2.2 kW)
Prewash pump motor	3.0 hp (2.2 kW)
Conveyor drive motor	0.13 hp (0.12 kW)
Vent motor (WAHRS option only)	0.17 hp (0.13 kW)
Blower dryer motor (blower dryer option only)	0.67 hp (0.48 kW)

Recommended Tabling Construction



Note: All specifications are subject to change without notice based on MEIKO's dedicated product improvement program.