

**219608 (ECOE62K3L30)**

SkyLine ProS Combi Boilerless Oven with touch screen control, 6x2/1GN, electric, 2 cooking modes (recipe program, manual), automatic cleaning, spray gun, 6-sensor probe, 3-glass door and IoT module - 208V US

Description

**Replaces 219651

Combi oven with high resolution full touch screen interface, multilanguage.

- Boilerless steaming function to add and retain moisture.
- OptiFlow air distribution system to achieve maximum performance with 7 fan speed levels.
- SkyClean: Automatic and built-in self cleaning system. 4 automatic cycles (short, medium, intensive, rinse) and green functions to save energy, water, detergent and rinse aid.
- Cooking modes: Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories); Manual; EcoDelta cooking cycle.
- Special functions: MultiTimer cooking, Plan-n-Save to cut running costs, Make-it-Mine to customize interface, SkyHub to customize homepage, agenda MyPlanner, automatic backup mode to avoid downtime.
- USB port to download HACCP data, programs and setting
- Connectivity for real time access, remote software update, HACCP, recipe and energy management (optional)
- Single sensor core temperature probe.
- Triple-glass door with double LED lights line.
- Stainless steel construction throughout
- Supplied with n.1 tray rack 2/1 GN, 2 1/2 inches pitch.



Main Features

- Dry hot convection cycle (77 °F - 575 °F/25°C - 300 °C): ideal for convection cooking.
- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be group in 16 different categories to better organize the menu. 16-step cooking programs also available.
- Single sensor core temperature probe included.
- Reversible Fan: 7 speed fan levels from 300 to 1500 RPM with reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Automatic cool-down and pre-heat function
- MultiTimer: Special feature to manage up to 60 different cooking cycles at the same time in the same cavity guaranteeing even cooking results. Up to 200 MultiTimer available programs
- EcoDelta cooking: cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber.
- Instant steam generator: Boilerless steaming function to add and retain moisture for high quality, consistent cooking results. Automatic moistener (11 settings)
- Back-up mode: self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- 6-point multi sensor core temperature probe for maximum precision and food safety (optional accessory).
- OptiFlow: air distribution system to achieve maximum performance in chilling/heating evenness and temperature control thanks to a special design of the chamber.
- Electrolux Professional recommends the use of treated water to guarantee optimal cooking results and extend the life of the appliance. Check local water condition to select the appropriate water filter. More info available on the website.
- Short cleaning cycle: optimized cleaning cycle with a duration of just 33 minutes, improving efficiency and reducing downtime.
- SkyClean: Automatic and built-in self cleaning system with 4 automatic cycles (short, medium, intensive, rinse).

Construction

- 304 AISI stainless steel construction throughout.
- IPX 5 spray water protection certification for easy cleaning.
- Seamless hygienic internal chamber with all rounded corners for easy cleaning.
- Triple thermo-glazed door: with 2 hinged inside panels for easy cleaning and double LED lights line.
- Front access to control board for easy service.

User Interface & Data Management

- Picture Management: upload full customized images of cooking cycles or food items
- e-learning: equipment trainings, how-to guides, and technical documentation easily accessible by scanning QR-Code with any mobile device.
- Make-it-mine: feature to allow full personalization or locking of the user interface by selecting what is visible on screen
- SkyDuo: Oven and Blast Chiller automatic communication to guide the user through the cook&chill process by creating a safe controlled environment to optimize time and efficiency (requires optional accessory).
- SkyHub: customizable homepage to allow the user to group their favorite functions for immediate access when operating.
- MyPlanner: on-screen agenda where the user can plan their daily work, set reminders for several users and receive personalized alerts for each activity
- USB port: to download HACCP data, share cooking programs and configurations. USB port also allows to plug-in sous-vide probe (optional accessory).
- Touchscreen: High resolution interface (translated into more than 30 languages including Spanish and French) - color-blind friendly panel.
- Data Analytics: automatic consumption visualization at the end of the cycle.
- Connectivity for remote real time access, easy HACCP management, equipment uptime increase, consumption tracking and energy management (requires optional accessory).



Sustainability

- Reduced-Power Feature: To consume less energy during customized slow cooking cycles.
- Plan-n-Save: the oven organizes the sequence of the chosen cooking cycles to optimize the processes in the kitchen reducing time and energy consumption.
- Door handle: ergonomic wing-shaped design for hands-free door opening with elbow, to allow simple trays management (Registered Design at EPO EM003143551).
- Human centered design: with 4-star certification for ergonomics and usability.
- Save energy, water, detergent and rinse aid with SkyClean green functions.
- C22 and C25 detergents are formulated without phosphates and phosphorus (C25 is also maleic acid-free), making them safe for both the environment and human health.
- Sustainability: The outer cardboard packaging is made from 70% recycled materials and FSC*-certified paper, printed with eco-friendly, water-based ink to support sustainability and environmental responsibility (*Forest Stewardship Council is the world's leading organization for sustainable forest management).
- Triple-glass door minimize your energy loss.* *Approx. -10% of idle energy consumption in convection based on test in compliance with ASTM Standard F2861-20



Technical specifications

Electric

Supply voltage:	208 V/3 ph/60 Hz
Rated amps:	60.1 A
Electrical power max:	21.4 kW
Maximum Over-Current Protection (MOP):	80A

Water:

Pressure:	15-87 psi (1-6 bar)
Max inlet water supply temperature:	30 °C
Chlorides:	<10 ppm
Conductivity:	>50 µS/cm
Drain "D":	50mm
Water inlet "CW" connection:	3/4"
Pressure, bar min/max:	1-6 bar

Capacity:

Tray type:	6 - GN 2/1
Max load capacity:	60 kg
Shelf capacity:	6 Grids


Key Information:

External dimensions, Width:	42 15/16" (1090 mm)
External dimensions, Depth:	38 1/4" (971 mm)
External dimensions, height:	31 13/16" (808 mm)
Net weight:	330 lbs (149.5 kg)
Shipping width:	44 1/2" (1130 mm)
Shipping depth:	43 5/16" (1100 mm)
Shipping height:	40 9/16" (1030 mm)
Shipping weight:	416 lbs (172.5 kg)
Shipping volume:	45.21 ft³ (1.28 m³)
Approvals	ETL C&US;ETL SANITATION;ErgoCert 4*;UL verified V689870


Sustainability

Current consumption:	60.1 Amps
Water consumption:	18.2 lt/hr


Front



Side



Top



CWI1 = Cold Water inlet 1 (cleaning)

D = Drain

EI = Electrical inlet (power)

DO = Overflow drain pipe



Find out more:
ISO Certificates
Electrolux Professional Recognitions

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026/04/14

4/8

Technical specifications

Included Accessories

PNC Code	Description	Quantity
922076	Aisi 304 stainless steel grid (18" x 26")	3

Optional Accessories

PNC Code	Description
----------	-------------

Bases & Base Accessories

922613	Open base with tray support for 62 & 102 combi oven
922616	Cupboard base with tray support for 62 & 102 combi oven
922692	Tray support for 62 & 102 oven base

Cleaning Solutions

922386	HOLDER FOR DETERGENT TANK - WALL MOUNTED
922618	External connection kit for detergent and rinse aid
922699	Detergent tank holder for open base

Containers, Trays and Grids

922017	Pair of half size oven racks, type 304 stainless steel
922036	Chicken racks, pair (2) (fits 8 chickens per rack)
922062	Single 304 stainless steel grid (12" x 20")
922076	Aisi 304 stainless steel grid (18" x 26")
922175	Pair of 304 stainless steel full-size grids (18" x 26")
922189	Baguette tray, made of perforated aluminum, silicon coated, 16" x 24"
922190	Perforated baking tray, made of perforated aluminum, 16" x 24"
922191	Baking tray, made of aluminum 16" x 24"
922239	Pair of frying baskets
922264	Pastry grid 16" x 24"
922266	Grid for whole chicken 1/1GN (8 per grid - 2.6 lbs each)
922325	Kit universal skewer rack & (6) long skewer ovens (TANDOOR)
922348	Multipurpose hook
922362	Grid for 8 whole ducks (1.8KG, 4LBS) - GN 1/1
922651	Dehydration tray, (12" x 20"), H=2/3"
922652	Flat dehydration tray, (12" x 20")
922713	Mesh grilling grid (12" x 20")
922746	Tray for traditional static cooking, H=100mm (12' x 20")



Find out more:
ISO Certificates
[Electrolux Professional Recognitions](#)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026/04/14

5/8

Technical specifications

PNC Code	Description
Containers, Trays and Grids	
922747	Double-face griddle, one side ribbed and one side smooth, 400x600mm
925000	Non-stick universal pan (12" x 20" x 3/4")
925001	Non-stick universal pan (12" x 20" x 1 1/2")
925002	Non-stick universal pan (12" x 20" x 2 1/2")
925003	Frying griddle double sided (ribbed/smooth) 12" x 20"
925004	Aluminum combi oven grill (12" x 20")
925005	Egg fryer for 8 eggs (12" X 20")
925006	Flat baking tray with 2 edges (12" x 20")
925008	Potato baker GN 1/1 for 28 potatoes (12"X20")
925012	6 NON-STICK U-PAN (12" X 20" X 3/4")
925013	6 NON-STICK U-PAN (12"X20"X1 1/2")
925014	6 NON-STICK U-PAN (12"X20"X2 1/2")
Doors and Drawers	
922265	Double-click closing catch for oven door
Drains	
922636	Stainless steel drain kit for all oven sizes (61, 62, 101,102, 201,202)- dia=50mm (2")
922637	Plastic drain kit for all oven sizes (61, 62, 101,102,201, 202), dia=50mm (2")
Feet, Wheels and Ramps	
922003	Caster kit for base for 61, 62, 101 and 102 oven bases only
922351	4 FLANGED FEET FOR 61,62,101,102 OVENS - 2" 100-130MM
922688	4 adjustable feet for 61,62 & 101,102 combi ovens, 100-115mm (5 9/10in -7 9/1in)
922693	4 adjustable feet with black cover for 61,62 & 101,102 combi ovens, 150-200mm (5 9/10in -7 9/1in)
922745	4 high adjustable feet for 61,62 & 101,102 combi ovens, 230-290mm (9in - 11 2/5in)
Food Probes	
922281	USB Probe for sous-vide cooking (only for Touchline ovens)
922390	USB SINGLE POINT PROBE
922714	Probe holder for liquids
Grease/Oil Management	
922357	Grease collection tray (2 2/5") for 62 and 102 ovens
922752	TROLLEY FOR GREASE COLLECTION KIT



Find out more:
ISO Certificates
[Electrolux Professional Recognitions](#)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026/04/14

6/8

Technical specifications

PNC Code	Description
Handling - Gastronorm	
922611	5 Tray Rack with wheels, Full Size Sheet Pans, 3" (80mm) pitch for 62 ovens
922627	Trolley for slide-in rack for 62 & 102 ovens and 102 blast chiller.
922700	6 Tray Rack with wheels, Full Sheet Pans, 2 ½" (65mm) pitch for 62 ovens
Installation Solutions	
922665	Heat shield for 62 combi oven
922666	Heat shield for stacked ovens 62 on 62 combi ovens
922667	Heat shield for stacked ovens 62 on 102 combi ovens
922774	KIT FOR INSTALLATION OF ELECTRIC POWER PEAK MANAGEMENT SYSTEM-6-10 GN OVENS
Other Accessories	
922338	Smoker for ovens
Slide-In Supports	
922605	Slide-in rack with handle for 62, and 102 combi oven
Spray Units	
922171	External side spray unit
Stacking Kits	
922621	Stacking kit for electric 62 combi oven placed on 62 electric combi oven or 102 combi oven
922631	Trolley for mobile rack for 62 on 62 or 102 combi ovens
922633	Riser on feet for 2 stacked 61 combi ovens
922634	Riser on wheels for 2 stacked 62 combi ovens, height=250mm (9 6/7in)
922704	Wheels for stacked ovens
Ventilation	
922440	STEAM OPTIMIZER
922751	Hood Hopper to directly connect the Hood to the centralized ventilation system, for Standard Hoods (with fan motor) and Hoods without fan motor
922776	Extension for condensation tube, 37cm
Wall Mounting Kits	
922644	Wall support for 62 oven
922687	Kit to fix oven to the wall
Water Treatment	
920004	Water filter with cartridge and flow meter for 6 & 10 GN 1/1 ovens (low-medium steam usage - less than 2hrs per day full steam)
920005	Water filter with cartridge and flow meter for medium steam usage



Find out more:
ISO Certificates
[Electrolux Professional Recognitions](#)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026/04/14

7/8

Technical specifications

PNC Code	Description
Other Accessories	
922326	Universal skewer pan for ovens (TANDOOR)
922328	Skewers for ovens, (6) 14" short (TANDOOR)
922421	IoT module for SkyLine ovens and blast chiller/freezers
922435	Connectivity router (WiFi and LAN)
922450	Grease Collection Kit for Oven Cupboard Base GN 1/1-2/1 (trolley with 2 tanks, open/close device for drain)
922451	GREASE COLLECTION KIT FOR OVEN OPEN BASE GN 1/1-2/1 (2 TANKS, OPEN/CLOSE DEVICE FOR DRAIN)
922452	GREASE COLLECTION KIT FOR OVENS GN 1/1-2/1 (2 PLASTIC TANKS, CONNECTION VALVE WITH PIPE FOR DRAIN)
922773	WATER INLET PRESSURE REDUCER

Recommended Detergents

PNC Code	Description
0S2394	C25 Rinse & Descale Tabs, 50 tabs bucket
0S2395	C22 Cleaning Tabs, phosphate-free, 100 bags bucket



Find out more:
[ISO Certificates](#)
[Electrolux Professional Recognitions](#)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.