

**219909 (ECOG101C3O30)**

SkyLine Pro Combi Boilerless Oven with digital control, 10x1/1GN, gas, programmable, automatic cleaning, spray gun, 3-glass door and IoT module - 120V US

Description

**Replaces 219962

Combi oven with digital interface with guided selection.

- Boilerless steaming function to add and retain moisture.
- OptiFlow air distribution system to achieve maximum performance with 5 fan speed levels.
- SkyClean: Automatic and built-in self cleaning system. 4 automatic cycles (short, medium, intensive, rinse).
- Cooking modes: Programs (a maximum of 100 recipes can be stored); Manual; EcoDelta cooking cycle.
- Automatic backup mode to avoid downtime.
- USB port to download HACCP data, programs and settings
- Connectivity for real time access, remote software update, HACCP, recipe and energy management (optional)
- Single sensor core temperature probe.
- Triple-glass door with double LED lights line.
- Stainless steel construction throughout
- Supplied with n.1 tray rack 1/1 GN, 2 1/2 inches pitch.



Main Features

- Dry hot convection cycle (77 °F - 575 °F/25°C - 300 °C): ideal for convection cooking.
- Single sensor core temperature probe included.
- Automatic cool-down and pre-heat function
- Programs mode: up to 100 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. 4-step cooking programs also available.
- EcoDelta cooking: cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber.
- Instant steam generator: Boilerless steaming function to add and retain moisture for high quality, consistent cooking results. Automatic moistener (11 settings)
- Reversible Fan: 5 speed fan levels from 300 to 1500 RPM with reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Back-up mode: self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- 6-point multi sensor core temperature probe for maximum precision and food safety (optional accessory).
- OptiFlow: air distribution system to achieve maximum performance in chilling/heating evenness and temperature control thanks to a special design of the chamber.
- Electrolux Professional recommends the use of treated water to guarantee optimal cooking results and extend the life of the appliance. Check local water condition to select the appropriate water filter. More info available on the website.
- Short cleaning cycle: optimized cleaning cycle with a duration of just 33 minutes, improving efficiency and reducing downtime.
- SkyClean: Automatic and built-in self cleaning system with 4 automatic cycles (short, medium, intensive, rinse).

Construction

- 304 AISI stainless steel construction throughout.
- IPX 5 spray water protection certification for easy cleaning.
- Seamless hygienic internal chamber with all rounded corners for easy cleaning.
- Triple thermo-glazed door: with 2 hinged inside panels for easy cleaning and double LED lights line.
- Front access to control board for easy service.

User Interface & Data Management

- USB port: to download HACCP data, share cooking programs and configurations. USB port also allows to plug-in sous-vide probe (optional accessory).
- Digital screen: interface with LED backlight buttons with guided selection.
- Connectivity for remote real time access, easy HACCP management, equipment uptime increase, consumption tracking and energy management (requires optional accessory).

Sustainability

- Energy Star 2.0 certified product
- Door handle: ergonomic wing-shaped design for hands-free door opening with elbow, to allow simple trays management (Registered Design at EPO EM003143551).
- Human centered design: with 4-star certification for ergonomics and usability.
- Save energy, water, detergent and rinse aid with SkyClean green functions.
- C22 and C25 detergents are formulated without phosphates and phosphorus (C25 is also maleic acid-free), making them safe for both the environment and human health.
- Sustainability: The outer cardboard packaging is made from 70% recycled materials and FSC*-certified paper, printed with eco-friendly, water-based ink to support sustainability and environmental responsibility (*Forest Stewardship Council is the world's leading organization for sustainable forest management).





- Triple-glass door minimize your energy loss.* *Approx. -10% of idle energy consumption in convection based on test in compliance with ASTM Standard F2861-20
- Uses 33% less water and 22% less detergent while cleaning, as compared to previous model.



Technical specifications

Electric

Supply voltage:	120 V/1 ph/60 Hz
Rated amps:	9.1 A
Electrical power max:	1.1 kW

Gas

Total thermal load:	84618 BTU (24.8 kW)
Gas Power:	24.8 kW
ISO 7/1 gas connection diameter:	1/2" MNPT

Water:

Pressure:	15-87 psi (1-6 bar)
Max inlet water supply temperature:	30 °C
Chlorides:	<10 ppm
Drain "D":	50mm
Water inlet "CW" connection:	3/4"
Pressure, bar min/max:	1-6 bar

Capacity:

Tray type:	10 - GN 1/1
Max load capacity:	50 kg
Shelf capacity:	10 Grids


Key Information:

External dimensions, Width:	34 1/8" (867 mm)
External dimensions, Depth:	30 1/2" (775 mm)
External dimensions, height:	41 5/8" (1058 mm)
Net weight:	316 lbs (143.5 kg)
Shipping width:	36 5/8" (930 mm)
Shipping depth:	36 5/8" (930 mm)
Shipping height:	50 3/8" (1280 mm)
Shipping weight:	356 lbs (161.5 kg)
Shipping volume:	39.09 ft ³ (1.11 m ³)
Approvals	ENERGY STAR;ETL C&US;ETL SANITATION;ErgoCert 4*;UL verified V689870


Sustainability

Current consumption:	9.1 Amps
Water consumption:	13.8 lt/hr


Front



Side



Top



CW11 = Cold Water inlet 1 (cleaning)

D = Drain

G = Gas connection

E1 = Electrical inlet (power)

DO = Overflow drain pipe



Find out more:
ISO Certificates
Electrolux Professional Recognitions

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026/04/14

4/8

Technical specifications

Included Accessories

PNC Code	Description	Quantity
922062	Single 304 stainless steel grid (12" x 20")	5

Optional Accessories

PNC Code	Description
----------	-------------

Bases & Base Accessories

922612	Open base with tray support for 61 & 101 combi oven
922614	Cupboard base with tray support for 61 & 101 combi oven
922615	HOT CUPBOARD BASE WITH TRAY SUPPORT FOR 61 AND 101 OVEN HALF SHEET PANS (12" X 20")
922690	Tray support for 61 & 101 oven base
922702	Bakery/pastry runners 400x600mm for 6 & 10 GN 1/1 oven base

Cleaning Solutions

922386	HOLDER FOR DETERGENT TANK - WALL MOUNTED
922618	External connection kit for detergent and rinse aid
922699	Detergent tank holder for open base

Containers, Trays and Grids

922017	Pair of half size oven racks, type 304 stainless steel
922036	Chicken racks, pair (2) (fits 8 chickens per rack)
922062	Single 304 stainless steel grid (12" x 20")
922086	Stainless steel 304 grids (GN ½) with spikes, fits 4 chickens
922189	Baguette tray, made of perforated aluminum, silicon coated, 16" x 24"
922190	Perforated baking tray, made of perforated aluminum, 16" x 24"
922191	Baking tray, made of aluminum 16" x 24"
922239	Pair of frying baskets
922264	Pastry grid 16" x 24"
922266	Grid for whole chicken 1/1GN (8 per grid - 2.6 lbs each)
922324	Kit universal skewer rack & (4) long skewer ovens (TANDOOR)
922348	Multipurpose hook
922362	Grid for 8 whole ducks (1.8KG, 4LBS) - GN 1/1
922651	Dehydration tray, (12" x 20"), H=2/3"
922652	Flat dehydration tray, (12" x 20")
922709	Spit for lamb or suckling pig (up to 26lbs) for 61,101,201



Find out more:
ISO Certificates
[Electrolux Professional Recognitions](#)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026/04/14

5/8

Technical specifications

PNC Code	Description
Containers, Trays and Grids	
922713	Mesh grilling grid (12" x 20")
922746	Tray for traditional static cooking, H=100mm (12' x 20")
922747	Double-face griddle, one side ribbed and one side smooth, 400x600mm
925000	Non-stick universal pan (12" x 20" x 3/4")
925001	Non-stick universal pan (12" x 20" x 1 1/2")
925002	Non-stick universal pan (12" x 20" x 2 1/2")
925003	Frying griddle double sided (ribbed/smooth) 12" x 20"
925004	Aluminum combi oven grill (12" x 20")
925005	Egg fryer for 8 eggs (12" X 20")
925006	Flat baking tray with 2 edges (12" x 20")
925007	Baking tray for (4) baguettes (12" x 20")
925008	Potato baker GN 1/1 for 28 potatoes (12"X20")
925009	Non-stick U-pan (12" x 10" x 3/4")
925010	Non-stick U-pan (12" x 10" x 1 1/2")
925011	Non-stick U-pan (12" x 10" x 2 1/2")
925012	6 NON-STICK U-PAN (12" X 20" X 3/4")
925013	6 NON-STICK U-PAN (12"X20"X1 1/2")
925014	6 NON-STICK U-PAN (12"X20"X2 1/2")
Doors and Drawers	
922265	Double-click closing catch for oven door
Drains	
922636	Stainless steel drain kit for all oven sizes (61, 62, 101,102, 201,202)- dia=50mm (2")
922637	Plastic drain kit for all oven sizes (61, 62, 101,102,201, 202), dia=50mm (2")
Feet, Wheels and Ramps	
922003	Caster kit for base for 61, 62, 101 and 102 oven bases only
922351	4 FLANGED FEET FOR 61,62,101,102 OVENS - 2" 100-130MM
922394	4 SERVICE FEET FOR 6&10 GN OVENS, 100MM - MARINE
922688	4 adjustable feet for 61,62 & 101,102 combi ovens, 100-115mm (5 9/10in -7 9/1in)
922693	4 adjustable feet with black cover for 61,62 & 101,102 combi ovens, 150-200mm (5 9/10in -7 9/1in)
922745	4 high adjustable feet for 61,62 & 101,102 combi ovens, 230-290mm (9in - 11 2/5in)



Find out more:
ISO Certificates
[Electrolux Professional Recognitions](#)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026/04/14

6/8

Technical specifications

PNC Code	Description
Food Probes	
922390	USB SINGLE POINT PROBE
922714	Probe holder for liquids
Grease/Oil Management	
922321	Grease collection tray (4") for 61 and 101 ovens
922329	Grease collection tray (1 1/2") for 61 and 101 ovens
922752	TROLLEY FOR GREASE COLLECTION KIT
Handling - Bakery	
922608	Bakery/pastry tray rack with wheels holding 400x600mm grids for 10 GN 1/1 oven and blast chiller freezer, 80mm pitch (8 runners)
922656	Bakery/pastry rack kit for 10 GN 1/1 oven with 8 racks 400x600mm and 80mm pitch
Handling - Banqueting	
922364	Thermal blanket for 101 oven (trolley not included)
922648	Banquet rack with wheels holding 30 plates for 101 oven and blast chiller freezer, 65mm pitch (2 1/2")
922649	Banquet rack with wheels 23 plates for 101 oven and blast chiller freezer, 85mm pitch
Handling - Gastronorm	
922601	10 Tray Rack with wheels, Half Sheet Pans, 2 1/2" (65mm) pitch for 101 ovens and blast chillers
922602	8 Tray Rack with wheels, Half Sheet Pans, 3" (80mm) pitch, for 101 ovens and blast chillers
922626	Trolley for slide-in rack for 61 and 101 combi oven and blast chiller freezer
922694	Reinforced tray rack with wheels, lowest support dedicated to a grease collection tray for 101 oven pitch: 2 1/2"
Handling - Multipurpose	
922685	Fixed tray rack for 10 GN 1/1 and 400x600mm grids
Installation Solutions	
922661	Heat shield for stacked ovens 61 on 101 combi ovens
922663	Heat shield for 101 combi oven
922670	Kit to convert from natural gas to LPG
922671	Kit to convert from LPG to natural gas
Slide-In Supports	
922610	Slide-in rack with handle for 61 and 101 combi oven
Spray Units	
922171	External side spray unit



Find out more:
ISO Certificates
[Electrolux Professional Recognitions](#)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026/04/14

7/8

Technical specifications

PNC Code	Description
Stacking Kits	
922623	Stacking kit for gas 6l combi oven placed on gas 10l combi oven
922630	Trolley for mobile rack for 6l on 6l or 10l combi ovens
922704	Wheels for stacked ovens
Ventilation	
922440	STEAM OPTIMIZER
922678	Flue condenser for gas oven
922751	Hood Hopper to directly connect the Hood to the centralized ventilation system, for Standard Hoods (with fan motor) and Hoods without fan motor
922776	Extension for condensation tube, 37cm
Wall Mounting Kits	
922645	Wall support for 10l oven
922687	Kit to fix oven to the wall
Water Treatment	
920004	Water filter with cartridge and flow meter for 6 & 10 GN 1/1 ovens (low-medium steam usage - less than 2hrs per day full steam)
920005	Water filter with cartridge and flow meter for medium steam usage
Other Accessories	
922326	Universal skewer pan for ovens (TANDOOR)
922327	Skewers for ovens, (4) 24" long (TANDOOR)
922421	IoT module for SkyLine ovens and blast chiller/freezers
922435	Connectivity router (WiFi and LAN)
922450	Grease Collection Kit for Oven Cupboard Base GN 1/1-2/1 (trolley with 2 tanks, open/close device for drain)
922451	GREASE COLLECTION KIT FOR OVEN OPEN BASE GN 1/1-2/1 (2 TANKS, OPEN/CLOSE DEVICE FOR DRAIN)
922452	GREASE COLLECTION KIT FOR OVENS GN 1/1-2/1 (2 PLASTIC TANKS, CONNECTION VALVE WITH PIPE FOR DRAIN)
922773	WATER INLET PRESSURE REDUCER

Recommended Detergents

PNC Code	Description
0S2394	C25 Rinse & Descale Tabs, 50 tabs bucket
0S2395	C22 Cleaning Tabs, phosphate-free, 100 bags bucket



Find out more:
ISO Certificates
[Electrolux Professional Recognitions](#)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026/04/14

8/8