

VWR60A

Worktop 60" Refrigerator

VWR60A
05/07/26
Item #13764

VALIANCE®

by  HOSHIZAKI

PRELIMINARY

Item #: _____
Project: _____
Qty: _____
AIA#: _____

FEATURES

- Engineered to maintain NSF-7 temperatures of 100° ambient
- Stainless steel exterior front, sides, and top
- Front breathing air flow design
- Environmentally friendly R290 hydrocarbon refrigerant
- Spring assisted self-closing doors with stay open feature
- Stainless steel exterior doors, sides, and top
- Single section doors are field reversible (no kit needed)
- Stainless steel interior floor with aluminum sides, rear, and top
- Heavy duty grey epoxy coated shelves are adjustable in 1/2" increments; 1 per section. 105 lbs. capacity
- Aluminum shelf supports are adjustable in 1/2" increments
- Standard with 6" casters (two with brakes)
- 9 ft. cord and plug

W x D x H

60" x 30" x 40.25"
(including 6" casters)



VWR60A ★



Dimensions / Capacity

One Section VWR60A

Interior Storage Capacity (CF) (AHAM)	15.37 ft³
Overall Width x Depth (including 1" bumper)	59.75" x 30"
Height (including 6" casters)	40.25"
Door Opening (W x H)	30" x 28"
Depth with Door Open at 90°	59"
Adjustable Shelves	2
Shelf Dimensions (W x D)	27.25" x 16"
Crated Shipping Weight	370 lbs.
Crated Length x Depth x Height	64" x 33" x 40.25"

Electrical / Refrigeration

One Section VWR60A

Voltage	115/60/1
HACR Breaker	15.0 Amps
Electrical Connection (NEMA)	5-15P 
Voltage Range	115-127
Ambient Temp. Range	45° to 100°F
Control Setpoint Range	29.5° to 33.5°F
Amperage	1.2
Energy Consumption (kWh/day) @ASHRAE	3.67
Approx. Nominal Compres. BTU/HR (HP)	993(1/5)
Refrigerant / Charge Amount (oz.)	R290 / (2.8oz)

Options

- ☐ 4" Casters (set of 4) (HS-5035) ☐ Single overshelf for 60" (HS-5174)
☐ 2.25" Casters (set of 4) (HS-5037) ☐ Double overshelf for 60" (HS-5165)

Warranty

3 Year - Labor on entire machine.
4 Year - Parts on entire machine.
5 Year - Parts on Compressor

Valid in United States, Canada, Puerto Rico and U.S. Territories.
Contact factory for warranty in other countries.

If GFCI is required, a GFCI breaker MUST be used in lieu of GFCI receptacle

We reserve the right to change specifications without notice.