

# VWF27A/48A

Worktop 27"/48" Freezer

VWF27A/48A  
05/07/26  
Item #13763

VALIANCE

by  HOSHIZAKI

PRELIMINARY

Item #: \_\_\_\_\_  
Project: \_\_\_\_\_  
Qty: \_\_\_\_\_  
AIA#: \_\_\_\_\_

## FEATURES

- Engineered to maintain NSF-7 temperatures of 100° ambient
- Stainless steel exterior front, sides, and top
- Front breathing air flow design
- Environmentally friendly R290 hydrocarbon refrigerant
- Spring assisted self-closing doors with stay open feature
- Stainless steel exterior doors, sides, and top
- Single section doors are field reversible (no kit needed)
- Stainless steel interior floor with aluminum sides, rear, and top
- Heavy duty grey epoxy coated shelves are adjustable in 1/2" increments; 1 per section. 105 lbs. capacity
- Aluminum shelf supports are adjustable in 1/2" increments
- Standard with 6" casters (two with brakes)
- 9 ft. cord and plug
- Container Qty:  
VWF27A: 88  
VWF48A: 46

### W x D x H

27" x 30" x 40.25"  
(including 6" casters)

### W x D x H

47.75" x 30" x 40"  
(including 6" casters)



VWF27A★



VWF48A★



### Dimensions / Capacity

|                                             | One Section<br>VWF27A | Two Section<br>VWF48A |
|---------------------------------------------|-----------------------|-----------------------|
| Interior Storage Capacity (CF) (AHAM)       | 6.33 ft <sup>3</sup>  | 12.09 ft <sup>3</sup> |
| Overall Width x Depth (including 1" bumper) | 27" x 31.25"          | 47.75" x 31.25"       |
| Height (including 6" casters)               | 40.25"                | 40.25"                |
| Door Opening (W x H)                        | 22.6" x 22.75"        | 19.5" x 22.75"        |
| Depth with Door Open at 90°                 | 55.75"                | 52.75"                |
| Adjustable Shelves                          | 1                     | 2                     |
| Shelf Dimensions (W x D)                    | 22" x 16"             | 21.25" x 16"          |
| Crated Shipping Weight                      | 200 lbs.              | 290 lbs.              |
| Crated Length x Depth x Height              | 33" x 29" x 40.25"    | 52" x 33" x 40.25"    |

### Electrical / Refrigeration

|                                      | One Section<br>VWF27A | Two Section<br>VWF48A |
|--------------------------------------|-----------------------|-----------------------|
| Voltage                              | 115/60/1              | 115/60/1              |
| HACR Breaker                         | 15.0 Amps             | 15.0 Amps             |
| Electrical Connection (NEMA)         | 5-15P ⚡               | 5-15P ⚡               |
| Voltage Range                        | 115-127               | 115-127               |
| Ambient Temp. Range                  | 45° to 100°F          | 45° to 100°F          |
| Control Setpoint Range               | -5° to 5°F            | -5° to 5°F            |
| Amperage                             | 1.2                   | 1.7                   |
| Energy Consumption (kWh/day) @ASHRAE | 1.92                  | 3.44                  |
| Approx. Nominal Compres. BTU/HR (HP) | 993(1/5)              | 1468(1/3)             |
| Refrigerant / Charge Amount (oz.)    | R290 / (1.9oz)        | R290 / (2.3oz)        |

### Options

- ☐ 4" Casters (set of 4) (HS-5035)
- ☐ 2.25" Casters (set of 4) (HS-5037)
- ☐ Rearmount undrcntr shelf for 27" (HS-5794)
- ☐ Rearmount undrcntr shelf for 48" (HS-5795)
- ☐ Single oversheff for 27" (HS-5172)
- ☐ Single oversheff for 48" (HS-5173)
- ☐ Double oversheff for 27" (HS-5163)
- ☐ Double oversheff for 48" (HS-5164)

### Warranty

- 3 Year - Labor on entire machine.
- 4 Year - Parts on entire machine.
- 5 Year - Parts on Compressor

Valid in United States, Canada, Puerto Rico and U.S. Territories.

Contact factory for warranty in other countries.

If GFCI is required, a GFCI breaker MUST be used in lieu of GFCI receptacle

We reserve the right to change specifications without notice.