

VWR27A/48A

Worktop 27"/48" Refrigerator

VWR27A/48A
05/07/26
Item #13762

VALIANCE®

by  HOSHIZAKI

PRELIMINARY

Item #: _____
Project: _____
Qty: _____
AIA#: _____

FEATURES

- Engineered to maintain NSF-7 temperatures of 100° ambient
- Stainless steel exterior front, sides, and top
- Front breathing air flow design
- Environmentally friendly R290 hydrocarbon refrigerant
- Spring assisted self-closing doors with stay open feature
- Stainless steel exterior doors, sides, and top
- Single section doors are field reversible (no kit needed)
- Stainless steel interior floor with aluminum sides, rear, and top
- Heavy duty grey epoxy coated shelves are adjustable in 1/2" increments; 1 per section. 105 lbs. capacity
- Aluminum shelf supports are adjustable in 1/2" increments
- Standard with 6" casters (two with brakes)
- 9 ft. cord and plug
- Container Qty:
VWR27A: 88
VWR48A: 46

W x D x H

27" x 30" x 40.25"
(including 6" casters)

W x D x H

47.75" x 30" x 40.25"
(including 6" casters)



VWR27A★



VWR48A★



Dimensions / Capacity

	One Section VWR27A	Two Section VWR48A
Interior Storage Capacity (CF) (AHAM)	6.33 ft ³	12.09 ft ³
Overall Width x Depth (including 1" bumper)	27" x 31.25"	47.75" x 31.25"
Height (including 6" casters)	40.25"	40.25"
Door Opening (W x H)	22.6" x 22.75"	19.5" x 22.75"
Depth with Door Open at 90°	54.5"	51.5"
Adjustable Shelves	1	2
Shelf Dimensions (W x D)	22" x 16"	21.25" x 16"
Crated Shipping Weight	200 lbs.	290 lbs.
Crated Length x Depth x Height	33" x 29" x 40.25"	52" x 33" x 40.25"

Electrical / Refrigeration

	One Section VWR27A	Two Section VWR48A
Voltage	115/60/1	115/60/1
HACR Breaker	15.0 Amps	15.0 Amps
Electrical Connection (NEMA)	5-15P ⚡	5-15P ⚡
Voltage Range	115-127	115-127
Ambient Temp. Range	45° to 100°F	45° to 100°F
Control Setpoint Range	33° to 39°F	33° to 39°F
Amperage	1.5	1.8
Energy Consumption (kWh/day) @ASHRAE	0.95	1.21
Approx. Nominal Compres. BTU/HR (HP)	1289(1/6)	1709(1/6)
Refrigerant / Charge Amount (oz.)	R290 / (1.9oz)	R290 / (2.5oz)

Options

- ☐ 4" Casters (set of 4) (HS-5035)
- ☐ 2.25" Casters (set of 4) (HS-5037)
- ☐ Rearmount undrcntr shelf for 27" (HS-5794)
- ☐ Rearmount undrcntr shelf for 48" (HS-5795)
- ☐ Single oversheff for 27" (HS-5172)
- ☐ Single oversheff for 48" (HS-5173)
- ☐ Double oversheff for 27" (HS-5163)
- ☐ Double oversheff for 48" (HS-5164)

Warranty

- 3 Year - Labor on entire machine.
- 4 Year - Parts on entire machine.
- 5 Year - Parts on Compressor

Valid in United States, Canada, Puerto Rico and U.S. Territories.
Contact factory for warranty in other countries.

If GFCI is required, a GFCI breaker MUST be used in lieu of GFCI receptacle
We reserve the right to change specifications without notice.