



UTILITY REFRIGERATOR
PEOPLE • PRODUCT • PERFORMANCE • PRIDE

Project _____
Item No. _____
Model No. _____
Quantity _____

CSI No. 114000

RAISED RAIL PIZZA PREP TABLES



PPR-60-2S-D-EM
78" overall width, 2 doors,
self-contained

MODEL GUIDE

Model Number	Description
☐ PPR-30-1S-EM	48" Overall Width, One Doors
☐ PPR-50-2S-EM	68" Overall Width, Two Doors
☐ PPR-60-2S-EM	78" Overall Width, Two Doors
Options	Model Number Modification
☐ Remote Refrigeration	Delete suffix "EM" from model number

AGENCY APPROVALS:



STANDARD FEATURES:

Refrigerated Prep Rail

- Rugged construction - designed to perform in the most demanding environments
- Air cooled pan rail - eliminates the defrosting, ice buildup, and cleaning associated with cold wall systems
- Removable stainless steel pan frame - securely holds pans (by others) and can be removed for easy cleaning
- Removable stainless steel night cover - reduces warm air infiltration when rail is not in use; removable for easy pan access
- Engineered two zone cooling airflow - gentle flow of air over the top cools without drying food; faster airflow on bottom and sides enables pans to stay cold in high ambient conditions
- Minimal recessing of pans - keeps food cold while allowing easy access to ingredients

Refrigeration Package

- Slideout condensing unit - enables fast and easy service
- Energy efficient, service friendly expansion valve refrigeration system for superior recovery and temperature pulldown
- Pressure control - prevents compressor burnout in case of refrigerant loss
- R-290 low GWP refrigerant for superior temperature recovery and pulldown
- Hot gas condensate evaporator
- Service ports allow easy access to refrigerant enabling safe, quick recharging as needed
- Integrated sight glass - allows technicians to easily detect leaks or moisture without tools

Construction/Cabinet

- Exterior sides and top - heavy gauge stainless steel
- Exterior back and bottom - heavy gauge galvanized
- Stainless steel front, door, rails, end mount, and interior
- Heavy-duty 6" adjustable stainless steel legs
- Cabinet body is foamed-in-place polyurethane insulation
- Fully coved interior with welded radius corners for easy cleaning
- Optional drawers hold two 12" x 20" pans or fractional pans (pans by others)
- Welded stainless steel door handle or drawer pull
- Compressor housing located on left side (optional on right side)
- Heavy duty stainless steel shelf clips and shelf standards
- Shelves adjustable in 1 inch increments
- One chrome plated wire shelf per section

Doors

- Self-closing door hinges with stay-open feature at 120°
- Energy saving condensate heater around door opening
- Snap-in magnetic door gasket
- Impact-resistant PVC breaker strip

Control Systems & Warranty Coverage

- Digital temperature control - easily adjust setpoint between 35-40°F
- Master power switch
- One 9 foot electrical cord
- Warranty: 5 year compressor, 5 year parts, 1 year labor

OPTIONS & ACCESSORIES:

- ☐ Stainless steel back ___ and/or bottom ___ (specify either or both)
- ☐ Additional chrome wire shelves (specify quantity) _____
- ☐ Poly cutting board
- ☐ 6" front locking casters in lieu of legs (no charge)
- ☐ 2 or 3 drawers in lieu of door (std depth only; 60", 90" models only)
- ☐ Interior LED lighting
- ☐ Compressor on right side



Technical drawings of the 52-inch wide chest freezer, showing dimensions in inches and millimeters.

Top View Dimensions:

- Self-Contained:** Overall width 78 [1981.20], depth 32.5 [825.50], and 62.0 [1574.80]. A note indicates the compressor housing can be mounted left or right.
- Remote:** Overall width 60 [1524.00], depth 32.5 [825.50], and 62.0 [1574.80].

Front View Dimensions:

- Self-Contained:** Features a digital temperature control, liquid line solenoid, and removable access panel.
- Remote:** Similar front view with a removable access panel.

Side View Dimensions:

- Self-Contained:** Overall height 52 [1325.44], depth 35 [889.00], and 3.0 [76.20]. A removable night cover is shown.
- Remote:** Overall height 52 [1325.44], depth 37.5 [952.51], and 6 [152.41].

ALL DIMENSIONS IN INCHES EXCEPT () IN MILLIMETERS

PRODUCT DATA	PPR-30	PPR-50	PPR-60
KEY DIMENSIONS			
Width, Self-Contained (overall)	48.0"	68.0"	78.0"
Width, Remote (overall)	36.0"	56.0"	66.0"
Depth (overall)	34.5"	34.5"	34.5"
Height (incl. 6" legs or casters)	34.5"	34.5"	34.5"
CAPACITY			
Capacity (cu.ft.)	9	16	19
Number of Pans	3 pans	6 pans	7 pans
ELECTRICAL			
Voltage (dedicated circuit required)	115	115	115
Amperage (self-contained)	6.3	6.8	7.0
Amperage (remote refrigeration)	3.9	4.4	4.6
BTU requirement*, remote	1403	1845	1971
NEMA Plug Configuration (self-contained only)	5-15P	5-15P	5-15P
Horsepower (self-contained)	1/3	1/3	1/3
SHIPPING			
Ship Weight, Self-Contained (lbs.)	430	550	610
Ship Weight, Remote (lbs.)	300	320	400
Ship Volume, Self-Contained (cu.ft.)	72	85	99
Ship Volume, Remote (cu.ft.)	56	76	80
Crated Dimensions, Self-Contained (48" H)	54" W x 48" D	74"W x 48"D	84"W x 48"D
Crated Dimensions, Remote (48" H)	42" W x 48" D	62"W x 48"D	72"W x 48"D

Data is for standard models: options may change specifications.

WARNING - This product can expose you to chemicals including Di(2-ethylhexyl)phthalate (DEHP), which is [are] known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

5/12/26 11:20 AM