

"ST4R5-SSW" STAINLESS STEEL TOP WORK TABLES

14GA Top w/5" Riser - Stainless Steel Legs & Fixed Undershelf

FEATURES:

- 14GA Stainless Steel Top w/5" Riser & Turndown
- Type 300 Stainless Steel With #4 Polish, Satin Finish
- Top Is Sound Deadened
- Reinforced With 1"x2" Channel Running Entire Length Of Table
- 1-1/2" Stallion Edge On Front Side Edges 90 Degree Bend Down For Table Line-Up
- Stainless Steel Base With Fixed Undershelf
- Adjustable Bullet Feet
- Ships Welded

SPECIFICATIONS:

- Top: Stainless Steel Tops Are TIG Welded, Exposed Welds Are Polished To Match Adjacent Surface
- Top: 14GA Stainless Steel Type 300 Stainless Steel With #4 Polish, Satin Finish
- Shelf: 18GA Stainless Steel, (36" Wide Tables, 16GA Lower Shelf)
- Legs: 1-5/8" Round O.D. 16GA Tubular Stainless Steel
- Gussets: Stainless Steel
- Feet: 1" Adjustable Stainless Bullet Feet

CERTIFICATIONS:


ST4R5-3048SSW

ACCESSORIES
DESCRIPTION

Drawer

Drawer Lock

Casters

Overshelves

Sinks


Pot Rack

"ST4R5-SSW" STAINLESS STEEL TOP WORK TABLES


LENGTH	24" WIDE	WT	WT CAP	30" WIDE	WT	WT CAP	36" WIDE	WT	WT CAP
24"	ST4R5-2424SSW	48	1000	ST4R5-3024SSW	54	1000	ST4R5-3624SSW	63	1000
30"	ST4R5-2430SSW	54	1000	ST4R5-3030SSW	61	1000	ST4R5-3630SSW	75	1000
36"	ST4R5-2436SSW	61	1000	ST4R5-3036SSW	69	1000	ST4R5-3636SSW	84	1000
48"	ST4R5-2448SSW	75	1000	ST4R5-3048SSW	86	1000	ST4R5-3648SSW	104	1000
60"	ST4R5-2460SSW	89	720	ST4R5-3060SSW	103	720	ST4R5-3660SSW	124	720
72"	ST4R5-2472SSW	104	470	ST4R5-3072SSW	119	470	ST4R5-3672SSW	145	470
84"	ST4R5-2484SSW	125	1500	ST4R5-3084SSW	143	1500	ST4R5-3684SSW	176	1500
96"	ST4R5-2496SSW	139	1500	ST4R5-3096SSW	160	1500	ST4R5-3696SSW	197	1500
108"	ST4R5-24108SSW	153	1500	ST4R5-30108SSW	176	1500	ST4R5-36108SSW	217	1500
120"	ST4R5-24120SSW	166	1330	ST4R5-30120SSW	193	1330	ST4R5-36120SSW	238	1330
132"	ST4R5-24132SSW	180	1060	ST4R5-30132SSW	209	1060	ST4R5-36132SSW	258	1060
144"	ST4R5-24144SSW	194	830	ST4R5-30144SSW	226	830	ST4R5-36144SSW	278	830

OVERALL WEIGHT (WT) AND MAX WEIGHT CAPACITY (WT CAP) ARE IN POUNDS (LBS). MAX WEIGHT CAPACITY EVENLY DISTRIBUTED.
ALL DIMENSIONS ARE TYPICAL. TOLERANCE +/- .500". JOHN BOOS & CO. RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE.

DETAILED SPECIFICATIONS



MODEL # STRUCTURE



"ST4R5-SSW" STAINLESS STEEL TOP WORK TABLES

LENGTH	24" WIDE	WT	WT CAP	30" WIDE	WT	WT CAP	36" WIDE	WT	WT CAP
24"	ST4R5-2424SSW	48	1000	ST4R5-3024SSW	54	1000	ST4R5-3624SSW	63	1000
30"	ST4R5-2430SSW	54	1000	ST4R5-3030SSW	61	1000	ST4R5-3630SSW	75	1000
36"	ST4R5-2436SSW	61	1000	ST4R5-3036SSW	69	1000	ST4R5-3636SSW	84	1000
48"	ST4R5-2448SSW	75	1000	ST4R5-3048SSW	86	1000	ST4R5-3648SSW	104	1000
60"	ST4R5-2460SSW	89	720	ST4R5-3060SSW	103	720	ST4R5-3660SSW	124	720
72"	ST4R5-2472SSW	104	470	ST4R5-3072SSW	119	470	ST4R5-3672SSW	145	470
84"	ST4R5-2484SSW	125	1500	ST4R5-3084SSW	143	1500	ST4R5-3684SSW	176	1500
96"	ST4R5-2496SSW	139	1500	ST4R5-3096SSW	160	1500	ST4R5-3696SSW	197	1500
108"	ST4R5-24108SSW	153	1500	ST4R5-30108SSW	176	1500	ST4R5-36108SSW	217	1500
120"	ST4R5-24120SSW	166	1330	ST4R5-30120SSW	193	1330	ST4R5-36120SSW	238	1330
132"	ST4R5-24132SSW	180	1060	ST4R5-30132SSW	209	1060	ST4R5-36132SSW	258	1060
144"	ST4R5-24144SSW	194	830	ST4R5-30144SSW	226	830	ST4R5-36144SSW	278	830

OVERALL WEIGHT (WT) AND MAX WEIGHT CAPACITY (WT CAP) ARE IN POUNDS (LBS). MAX WEIGHT CAPACITY EVENLY DISTRIBUTED.
ALL DIMENSIONS ARE TYPICAL. TOLERANCE +/- .500". JOHN BOOS & CO. RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE.