

Specification

Flexeserve Zone Lite 1 Tier, Square



Flexeserve Zone Lite,
double stacked.

MODEL TYPE	600 SQUARE
PRODUCT CODE	LT1U60EWSS
UNIT H / W / D inches	17.1 / 23.6 / 24.4
SHELF SIZE W / D inches / CAPACITY m³	22.6 / 16.5 / 0.065
UNIT WEIGHT lb	72.8
ELECTRICAL INFORMATION*	
POWER SUPPLY	Nema 5-15P Plug 120V 2 Pole 3 Wire (1Ph), 60Hz
TOTAL POWER PER ZONE	7.1A / 850W
TOTAL POWER PER UNIT	7.1A / 850W
ENERGY CONSUMPTION - HOURLY	
ONE ZONE	0.85 kWh
SHIPPING CRATE	
SIZE H / W / D inches / WEIGHT lb**	30.3 / 27.9 / 23.5 / 33

Plug Type




US
Nema 5-15P

* All models require a dedicated power supply.

** For accurate shipping weights including accessories and customization, contact help@flexeserve.com


UNIT VENTILATION - A 2" ventilation gap is required between the back of the unit and all solid surfaces. If located within housing or under a bulkhead, open ventilation above is required.

Front View




MODEL 600


Profile View




Interior Zone Dimensions



Power Cord Height / Length*



Shelf Footprint & Merchandising Volume*



FLEXESERVE ZONE PATENTS

WO2014072693, WO2015044637, EP2916692, EP3048931, GB2509207, GB2518524, US2016213168, US2016235218, HK1193011, CA2925157, AU2014326399.

ACCREDITATIONS

Conforms to Standard UL 197 and NSF-4.
Certified to CSA C22.2 No. 109.



FLEXESERVE | © 2024 Flexeserve Reserve the right to alter information due to continued improvement in design. Flexeserve Zone is tested at conditions of +64.4°F.

flexeserve™

For further information

help@flexeserve.com
flexeserve.com

Flexeserve Technical Service

Call Toll-Free (833) 955-8300
service@flexeserve.com

