# Threaded Stem Casters

## 5/8" - 11 x 1" Threaded Stem Casters With Hard Rubber Wheel

### Certifications:


NSF

### Features:


- Double Ball Bearing Raceway for Long Wear and Added Strength
- With or Without Top Lock Brake
- Raceway Dust Cover



TLB version
(Top Lock Brake)




3SBR




4SBR




5SBR

### Material:

- High Impact Molded Rubber
- Temperature Range -40° to 160°F
- Nylon Bearing Sleeve
- Zinc Plated
- Hard Rubber Wheel

| Part Number | Brake | Wheel Size | Capacity |
|---|---|---|---|
| 3SBR-5ST-HR | - | 3" | 300 LBS |
| 3SBR-5ST-HR-TLB | TLB | 3" | 300 LBS |
| 4SBR-5ST-HR | - | 4" | 300 LBS |
| 4SBR-5ST-HR-TLB | TLB | 4" | 300 LBS |
| 5SBR-5ST-HR | - | 5" | 300 LBS |
| 5SBR-5ST-HR-TLB | TLB | 5" | 300 LBS |

PRODUCT DATA SHEET

BK RESOURCES

© BK Resources August 2026

Phone: 888-310-4393 | Fax: 888-310-4394 | Website: www.bk-resources.com | Email: sales@bk-resources.com