

Side-Mount Undercounter Refrigerators

SIDE-MOUNT UNDERCOUNTER REFRIGERATORS WITH DRAWERS



BUILT TO PERFORM, DESIGNED TO DELIVER

The Asber ASUR Series delivers exceptional performance, flexibility, and efficiency in a compact design. Designed for versatile use as either undercounter or worktop units, side-mounted refrigeration system maximizes storage space while keeping cold air away from heat zones for superior performance. Featuring an improved airflow and easier maintenance access to reduce downtime and boost kitchen efficiency. Built with a full stainless-steel exterior and interior, it ensures long-lasting durability in high-demand environments.

INSULATION & ENERGY EFFICIENCY

High Performance, Environmentally Responsible Design

- Ecomate™ insulation: Industry-leading, eco-friendly technology (ODP-0, GWP-3), provides superior temperature retention and energy-savings even under heavy-duty kitchen conditions.
- Maximum thermal efficiency: 2" thick insulation throughout.

REFRIGERATION SYSTEM & PERFORMANCE

Efficient, Reliable, and Environmentally Friendly

- R290 Hydrocarbon refrigerant: Delivers quicker temperature recovery and lower energy consumption, ensuring environmental responsibility.
- Reversible Condensing Fan Motor: Ensuring optimal airflow, reduced maintenance, and improved long-term efficiency.
- Hermetic compressor system with epoxy-coated evaporator provides long-lasting performance and corrosion resistance operation.
- Electronic controller with digital display provides accurate, easy-to-monitor temperature management.
- Temperature range: Maintains 32°F to 38°F in ambient conditions up to 100°F and 65% RH.

DRAWER SYSTEM & STORAGE FLEXIBILITY

Durable, Safe, and Easy to Maintain

- Accepts standard 18" x 26" sheet pans, providing flexible storage options for busy commercial kitchens.

- All-stainless-steel drawers: Built for durability and ease of use, providing long-lasting performance in busy kitchen environments.
- High-strength slides: Designed for smooth operation and dependable support under heavy use, rated for up to 110 pounds per drawer.
- Flexible configurations: Each drawer accommodates pan sizes from 1/9 to 1/1, up to 6" deep (pans sold separately).
- Fixed pan dividers: ensure stable pan positioning, reducing cross-contamination risk and keeping ingredients perfectly organized for a clean and efficient workflow.

OPERATOR-FOCUSED DESIGN

Ergonomic, Practical, and Sanitary

- Designed for space optimization, fitting seamlessly beneath standard countertops or work surfaces.
- Full-length recessed handles: Provide ergonomic access while maintaining a clean, professional appearance.
- Factory-installed stainless-steel drawer kits for maximum flexibility.
- In-step interior design: provides a superior door seal, reducing energy loss, and preventing condensation.
- Magnetic one-piece door gaskets: Ensure a tight seal to preserve internal temperatures; tool-free removable, simplifying cleaning and maintenance.
- Standard 5" casters (front with brakes) provide stability, mobility, and easy access for cleaning and maintenance.

CERTIFICATIONS

- NSF-7 Certified: Meets rigorous food safety and sanitation standards.
- ETL Listed: Certified for electrical and mechanical safety.
- DOE Compliant: Meets U.S. Department of Energy efficiency standards.

OPTIONS & ACCESSORIES

- Overshelf.
- Extra shelves.
- 4" Stainless-steel backsplash.



ASUR 46 D2

ASUR 67 D2

ASUR 93 D6

MODEL	DOORS	DRAWERS	CAPACITY	VOLTS - FREQUENCY	POWER	AMP.	EXTERIOR DIMENSIONS (in)			SHIPPING	
			ft³		HP		Width	Depth	Height	Lbs	ft³
SIDE-MOUNT UNDERCOUNTER REFRIGERATORS WITH DRAWERS											
ASUR 46 D2	0	2	11.6	115V. - 60Hz.	1/3	3.0	46-1/4	36-1/8	36	298	42.4
ASUR 67 D2	1	2	20.8	115V. - 60Hz.	1/3	3.0	67-1/2	36-1/8	36	366	60.0
ASUR 67 D4	0	4	20.8	115V. - 60Hz.	1/3	3.0	67-1/2	36-1/8	36	366	60.0
ASUR 93 D2	2	2	30.2	115V. - 60Hz.	1/3	3.0	93-3/4	36-1/8	36	617	84.8
ASUR 93 D4	1	4	30.2	115V. - 60Hz.	1/3	3.0	93-3/4	36-1/8	36	617	84.8
ASUR 93 D6	0	6	30.2	115V. - 60Hz.	1/3	3.0	93-3/4	36-1/8	36	617	84.8


SPECIFICATIONS MAY CHANGE WITHOUT PRIOR NOTICE | HEIGHT INCLUDES CASTERS. | VALID FOR CONTINENTAL USA & CANADA. | SEP, 2026

Side-Mount Undercounter Refrigerators


SIDE-MOUNT UNDERCOUNTER REFRIGERATORS WITH DRAWERS





ASUR 46



ASUR 67



ASUR 93



MODEL	ASUR 46 D2	ASUR 67 D2	ASUR 93 D2
ELECTRICAL DATA			
Volts - Frequency	115V. - 60Hz.		
Power (HP)	1/3		
Full Amp Load	3.0		
Plug Type	NEMA 5-15P		
Refrigerant	R290		
SHIPPING DIMENSIONS (in)			
Width	48-7/8	70-1/8	96-1/8
Depth	36-1/4		
Height	41-3/8		



INSTALLATION REQUIREMENTS

- ELECTRICAL CONNECTION:** Units pre-wired at factory with chord and NEMA 5-15P plug set included for 115/60/1 phase.
- REFRIGERANT:** R290 is classified as A3 flammable refrigerant; risk of fire or explosion due to puncture of refrigerant tubing; follow handling instructions carefully.

- RESIDENTIAL APPLICATIONS DISCLAIMER:** Asber assumes no liability for parts or labor coverage for component failure, factory defect or any other damages for units installed in non-commercial foodservice or residential applications.

SPECIFICATIONS MAY CHANGE WITHOUT PRIOR NOTICE | HEIGHT INCLUDES CASTERS. | VALID FOR CONTINENTAL USA & CANADA. | SEP, 2026