

Self-Contained Back Bar Refrigeration

ROYAL SERIES






NS48-KSS-R

Base Model	Length	Doors	Amps	Bottle Capacity	HP	Weight
NS48	48"	2	2.1	285	1/4	224 lbs.

Case Capacity

Model	Long Neck Bottles	Wine Bottles
NS48	13	126



Standard Features

- 35" High without Top, 36" High with 1" Optional Top
- 24" Front to Back Depth (25" with Top)
- Coved corner stainless steel interior
- Heavy duty Self-Closing 20"W Door
- Stainless steel door handles with built-in locks
- Digital thermostat
- Built-in Cool White LED Lighting (7000K)
- DynamicChill 360° Technology
- Heated mullion to minimize condensation
- Approved for NSF 7 Open Food Storage
- Pre-drilled bottom for optional legs or casters (uses 1/4-20 self tapping 1/2"L screw)
- Eco-friendly Refrigerant and Insulation
- 5-Year Compressor Warranty
- 2-Year Parts & Labor Warranty

Specifications

Electrical	115 V, 1 Phase, 60 Hz
	Furnished with 8' plug-in cord, which exits left or right rear of cooler
	NEMA 5-15P plug configuration
	Dedicated 15 amp circuit recommended
Refrigeration	R290 Hydrocarbon Refrigerant
	30°F - 40°F operating range
Plumbing	No drain required
	Condensate evaporator pan included
Insulation	2" thick foamed-in-place polyurethane
Interior	20 gauge stainless steel walls with coved corners NSF epoxy coated durable shelves - one bottom and two adjustable shelves per door
Exterior	Sides & Front: 20 gauge stainless steel
	Top: 20 gauge stainless steel with option of 1" top
Doors	Self-closing 20"W doors available in black vinyl, stainless steel, glass with black vinyl, or glass with stainless steel
	15-3/4"W x 29-11/16" H door opening

This equipment is intended for the storage and display of non-potentially hazardous bottle or canned products only.

This equipment is intended for use in an area where the ambient temperature typically does not exceed 75 °F.

Krowne • 100 Haul Rd. Wayne, NJ 07470 • P: (800) 631-0442 • F: (973) 872-1129 • support@krowne.com • krowne.com

Due to our commitment to continued product improvement, specifications are subject to change without notice.

Rev 0 • 08/2026 • Self-Contained Refrigeration