

Lobster King[™]

- · Makes lobster tails ready for preparation in one clean cut of the shell
- · Also works on crab legs
- Handle-up dimensions (w x d x h): 10" x 15½" x 16" (25.4 x 38.7 x 40.6 cm)
- Handle-down dimensions (w x d x h): 10" x 191/2" x 41/4" (25.4 x 49.5 x 10.8 cm)

COMPLETE UNIT # DESCRIPTION		REPLACEMENT KNIFE ITEM #: 10" (25.4 CM)*	CASE LOT	
1851	Lobster King™	5103	1	

^{*}Vollrath warranty policies do not cover blades







one simple, safe stroke Durable steel point blade

Opens oysters and clams with

- Handle-up dimensions (w x d x h): 5%" x $10\frac{1}{2}$ " x 15" (14.9 x 26.7 x 38.1 cm)
- Handle-down dimensions (w x d x h): 5% x 14% x 4%(14.9 x 37.5 x 10.8 cm)

COMPLETE UNIT #	DESCRIPTION	REPLACEMENT BLADE ITEM #	CASE LOT
1853	Oyster King™	5382	1

Grill Tender®



- · Splash guard and extra-long handle offer added protection from burns and kickback of debris
- · Durable steel point blade

COMPLETE	DESCRIPTION	DIMENSIONS	REPLACEMENT	CASE
UNIT #		(W X D X H): IN (CM)	BLADE ITEM #	LOT
1101	Grill Tender®	21% x 6 x 3% (54.9 x 15.2 x 7.9)	1102R*	1

^{*}Vollrath warranty policies do not cover blades

Petro-Gel®

- Designed specifically to lubricate all manual food processors
- Tasteless and odorless
- A food-safe lubricant



ITEM #	DESCRIPTION	CASE LOT
15149	4 oz petrol sanitary gel lubricant	1

GRINDERS

Grinders

- · Sausage stuffer and feed stick accessories included
- · Stainless steel body, cylinder, worm gear, and ring
- Supplied with $\frac{1}{8}$ " (3.2 mm) and $\frac{5}{16}$ " (7.9 mm) grinder plates
- · Dishwasher-safe grinding head, pan, and attachment
- Heavy-gauge product tray with 21/4" (5.7 cm) diameter food chute



Visit VOLLRATH.com/grinder for grinder accessories, images, and other resources.







ITEM #	MODEL	DESCRIPTION	DIMENSIONS (W X D X H): IN (CM)	OUTPUT	HP	VOLTAGE	AMPS	PLUG
40743	MIN0012	Meat grinder No. 12	103/16 x 153/4 x 197/16 (25.9 x 40 x 49.4)	264 lb (120 Kg)/hr	1	110 AC	8	5-15P
40744	MIN0022	Meat grinder No. 22	10 ³ / ₁₆ × 20 ¹ / ₄ × 24 ¹ / ₄ (27.5 × 51.4 × 61.6)	528 lb (240 Kg)/hr	11/2	110 AC	16	5-20P