

Camshelving® Elements XTRA Series

High Density Storage Top Rail System

High Density Mobile Units

4 Vented, Solid, or VS (3 Vented + 1 Solid)

HEIGHTS	DEPTHES	LENGTHS
1	3	5
80" (2032 mm)	18" (460 mm)	36" (915 mm) 54" (1375 mm)
	21" (540 mm)	42" (1070 mm) 60" (1525 mm)
	24" (610 mm)	48" (1220 mm)

- **Top Rail Mobile Unit includes:**

2 factory assembled mobile post kits, 8 mobile traverses, traverse dovetails, shelf plates, 4 casters, and 4 top roller kits. Units ship complete in 1 box.

Features & Benefits

- Trackless, open-floor design offers an alternative for environments where floor tracks may be less practical—such as uneven floors or high-traffic area requiring frequent cleaning. The open space beneath units allows for easy access and simplified maintenance, while still delivering smooth mobility and high-density storage.
- System composed of Top Rail End Kits installed onto Top Rail Stationary Units, joined by Top Rail Middle Kits. Top Rail Mobile Units with top rollers nest securely within the rail system.
- Withstands storage temperatures from -36° to 190°F (-38° to 88°C). Use in walk-in coolers, freezers, dry storage, warewashing areas, loading docks or front of the house. Impervious to moisture, chemicals, salt, food acids, and humidity.
- Posts and traverses are made of revolutionary, extremely strong composite material with a smooth, easy-to-clean surface. Stronger than common wire shelving and lighter in weight than Camshelving Premium Series. Shelf traverse dovetails snap easily and quickly into place.
- Top Rail mobile traverses are unique to the line and feature a wraparound end-piece design that fully engages with the both dovetail and post. This ensures shelves remain securely in place and stable when mobile units are moved back and forth.
- Anodized, matte-finish aluminum top rails and type 304 stainless-steel hardware are rust resistant. Top-mounted rollers glide effortlessly, regardless of unit weight or floor surface, for smooth, reliable mobility.
- Non-marking, chemical-resistant casters provide smooth gliding performance with minimal floor contact to help preserve floor surfaces.
- Removable polypropylene shelf plates have permanent, molded-in Camguard®, an antimicrobial technology that inhibits the growth of mold, fungus and bacteria.
- Shelf traverses can be removed and adjusted easily at 4" (10,2 cm) increments.
- Recommend installing a stationary unit every 15' (4,6 m) of top rail to stabilize the system (must be bolted to the floor).
- Lifetime warranty against rust and corrosion.
- Available in 1 color – Speckled Gray (480).

Project _____

Item No. _____

Model No. _____

Quantity _____



camguard
ANTIMICROBIAL SHELF PLATES

Mobile Traverse

Top Roller

Weight Bearing Capacity

Weight must be evenly distributed across the entire shelf.

UNIT LENGTH
36" – 60" (915 - 1525 mm)

MOBILE UNIT	Unit only*	900 lbs. (408 kg)*
-------------	------------	--------------------

* Due to the weight bearing capacity of casters, maximum weight load on an entire Mobile Unit is 900 lbs. (408 kg).

Top Rail Middle and Extension Kits

CODE	DESCRIPTION	CASE PACK
Top Rail Middle Kits		
CSTRK10PKG	10' (3 m) Top Rail Kit for 3 Mobile Units*	1
CSTRK12PKG	12' (3,7 m) Top Rail Kit for 4 Mobile Units*	1
CSTRK145PKG	14.5' (4,4 m) Top Rail Kit for 5 Mobile Units*	1
Top Rail Extension Kits		
CSTRKEXT45PKG	4.5' (1,4 m) Top Rail Extension Kit	1
CSTRKEXT5PKG	5' (1,5 m) Top Rail Extension Kit	1
CSTRKEXT6PKG	6' (1,8 m) Top Rail Extension Kit	1

Color: Silver (000). *Based on 24" (610 mm) deep mobile units.

- **Top Rail Middle Kit includes:**
4 or 6 Aluminum rails, 4 or 8 joiners and hardware.
- **Top Rail Extension Kit includes:**
2 Aluminum rails, 4 joiners and hardware.

Approvals



Post Connectors, Identification Tags, Security Cages, Peg Board, Shelf Rails, Divider Bars, High Density Rail and Extension Kits are not NSF Listed.

COMPONENT

Camshelving® Elements XTRA Series

High Density Storage Top Rail System

High Density Mobile Units

4 Vented, Solid, or VS (3 Vented + 1 Solid)

80"
HEIGHT

18"
DEPTH

21"
DEPTH

24"
DEPTH

V4 4-Shelf Vented High Density Mobile Units

CODE	DIM. D x L x H
EMT183680V4	18" x 36" x 80" (460 x 915 x 2032 mm)
EMT184280V4	18" x 42" x 80" (460 x 1070 x 2032 mm)
EMT184880V4	18" x 48" x 80" (460 x 1220 x 2032 mm)
EMT185480V4	18" x 54" x 80" (460 x 1375 x 2032 mm)
EMT186080V4	18" x 60" x 80" (460 x 1525 x 2032 mm)
EMT213680V4	21" x 36" x 80" (540 x 915 x 2032 mm)
EMT214280V4	21" x 42" x 80" (540 x 1070 x 2032 mm)
EMT214880V4	21" x 48" x 80" (540 x 1220 x 2032 mm)
EMT215480V4	21" x 54" x 80" (540 x 1375 x 2032 mm)
EMT216080V4	21" x 60" x 80" (540 x 1525 x 2032 mm)
EMT243680V4	24" x 36" x 80" (610 x 915 x 2032 mm)
EMT244280V4	24" x 42" x 80" (610 x 1070 x 2032 mm)
EMT244880V4	24" x 48" x 80" (610 x 1220 x 2032 mm)
EMT245480V4	24" x 54" x 80" (610 x 1375 x 2032 mm)
EMT246080V4	24" x 60" x 80" (610 x 1525 x 2032 mm)

Color: Speckled Gray (480).

VS4 4-Shelf, 3 Vented + 1 Solid High Density Mobile Units

CODE	DIM. D x L x H
EMT183680VS4	18" x 36" x 80" (460 x 915 x 2032 mm)
EMT178280VS4	18" x 42" x 80" (460 x 1070 x 2032 mm)
EMT178880VS4	18" x 48" x 80" (460 x 1220 x 2032 mm)
EMT185480VS4	18" x 54" x 80" (460 x 1375 x 2032 mm)
EMT186080VS4	18" x 60" x 80" (460 x 1525 x 2032 mm)
EMT213680VS4	21" x 36" x 80" (540 x 915 x 2032 mm)
EMT214280VS4	21" x 42" x 80" (540 x 1070 x 2032 mm)
EMT214880VS4	21" x 48" x 80" (540 x 1220 x 2032 mm)
EMT215480VS4	21" x 54" x 80" (540 x 1375 x 2032 mm)
EMT216080VS4	21" x 60" x 80" (540 x 1525 x 2032 mm)
EMT243680VS4	24" x 36" x 80" (610 x 915 x 2032 mm)
EMT244280VS4	24" x 42" x 80" (610 x 1070 x 2032 mm)
EMT244880VS4	24" x 48" x 80" (610 x 1220 x 2032 mm)
EMT245480VS4	24" x 54" x 80" (610 x 1375 x 2032 mm)
EMT246080VS4	24" x 60" x 80" (610 x 1525 x 2032 mm)

Color: Speckled Gray (480).

CAMBRO®

www.cambro.com

Information and specifications are subject to change without notice. Please confirm at time of order.

© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056, U.S.A.

Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003 Email: customerservice@cambro.com

Printed in USA. REV. 09/25

Project _____

Item No. _____

Model No. _____

Quantity _____

S4 4-Shelf Solid High Density Mobile Units

CODE	DIM. D x L x H
EMT183680S4	18" x 36" x 80" (460 x 915 x 2032 mm)
EMT184280S4	18" x 42" x 80" (460 x 1070 x 2032 mm)
EMT184880S4	18" x 48" x 80" (460 x 1220 x 2032 mm)
EMT185480S4	18" x 54" x 80" (460 x 1375 x 2032 mm)
EMT186080S4	18" x 60" x 80" (460 x 1525 x 2032 mm)
EMT213680S4	21" x 36" x 80" (540 x 915 x 2032 mm)
EMT214280S4	21" x 42" x 80" (540 x 1070 x 2032 mm)
EMT214880S4	21" x 48" x 80" (540 x 1220 x 2032 mm)
EMT215480S4	21" x 54" x 80" (540 x 1375 x 2032 mm)
EMT216080S4	21" x 60" x 80" (540 x 1525 x 2032 mm)
EMT243680S4	24" x 36" x 80" (610 x 915 x 2032 mm)
EMT244280S4	24" x 42" x 80" (610 x 1070 x 2032 mm)
EMT244880S4	24" x 48" x 80" (610 x 1220 x 2032 mm)
EMT245480S4	24" x 54" x 80" (610 x 1375 x 2032 mm)
EMT246080S4	24" x 60" x 80" (610 x 1525 x 2032 mm)

Color: Speckled Gray (480).

Optional Accessories

- Shelf Identification Tags
- Single Shelf Sheet Pan/Tray Rack
- Shelf Divider Panel
- Single Shelf Security Cage
- Shelf Divider Bars (Straight or Angled)
- Shelf Traverses (Single or Double)
- Shelf Rails
- Single and Add-on Can Racks

Architect Specs

Posts and Traverses: Proprietary non-corrosive composite material.

Post Connectors: Reinforced polypropylene.

Shelf Plates: Reinforced polypropylene with Camguard® antimicrobial.

Traverse Dovetails: Reinforced nylon.

Post Connector Collar Wedges: Reinforced nylon.

High Density Casters: Polyolefin resin with zinc plated post.

Approvals



Post Connectors, Identification Tags, Security Cages, Peg Board, Shelf Rails, Divider Bars, High Density Rail and Extension Kits are not NSF Listed.

COMPONENT

EXTRM4

D092501